



KETT BLADES

* The tables below explain blade applications and compatibility with the different models of Kett Saws

Saw-Blade Compatibility Table

SAW MODEL	BLADE DIAMETER
KS-221, KS-21AM, PS-521	1-1/4" and 1-1/2"
KS-226, KS-426, KS-22AM, KS-25AM, PS-526	1-3/4" and 2"
KS-423, KS-23AM, KSV-432, PS-523, PSV-532	2" and 2-1/2"
KS-224, KS-4AM, KS-424, PS-524 (obsolete)	2-1/2" and 3-3/8"
KS-444, KS-44AM, KSV-434, KSV-34AM, PS-544, PSV-534	2-1/2" and 3-1/2"

Blade Description Table

SAW BLADE DIAMETER	BLADE PART NUMBER	BORE	TEETH PER INCH	# OF TEETH	MAX DEPTH OF CUT	APPLICATION legend
1-1/4"	157-12	1/4"	5.61	22	3/16"	E,G,H,L,K
	157-14	1/4"	11.21	44	3/16"	B,F,H,J,K
	157-16	1/4"	15.29	60	3/16"	C,H

	157-66	7/16"	7.64	60	5/8"	D,H,J,K
	157-68	7/16"	10.19	80	5/8"	B,C,H,J,K
	157-68Z	7/16"	10.19	80	5/8"	K
3-3/8"						
	157-710Z	7/16"	9.44	100	1"	K
3-1/2"	157-800	7/16"			1-1/16"	H,K
	157-810	7/16"	9.1	100	1-1/16"	D,H,J,K
	157-810Z	7/16"	9.1	100	1-1/16"	
	157-813	7/16"	12.37	136	1-1/16"	C
	157-86	7/16"	5.46	60	1-1/16"	H,L,K
	157-88	7/16"	7.28	80	1-1/16"	D,H,J,K

Materials Legend

- A** Mild Steel 14 to 15 Gauge
- B** Mild Steel 16 to 23 Gauge
- C** Mild Steel 24 Gauge and Lighter
- D** Hard Aluminum
- E** Soft Aluminum
- F** Brass
- G** Copper and Lead
- H** Fiberglass
- L** Plywood, Hardboard, Pressed Board, etc.
Alliance Wall, Color Wall, Mirawal and
similar metal laminated panels, drywall,
fiber cement board
- J** Plastics, plain as Lucite, Plexiglas and
decorative laminates as Consoweld,
Formica, Micarta, Texolite and Panelyte
- K**