

WRENCHES

9724 OIL PRESSURE INDICATOR GAUGE SENDING UNIT WRENCH



- Special low profile reversible ratcheting wrench used to remove/install the oil pressure indicator gauge sending unit on Harley-Davidson® FL Touring® motorcycles (1999 and up)
- Vinyl grip prevents the wrench from scratching or marring the bike

9793 SIX SPLINE RATCHETING OUTPUT WRENCH



- Reversible offset ratcheting EZ Grip wrench contains a 1" drive to service a six spline crankshaft
- Used for rotation of the crankshaft check engine timing and parts clearance on Sportster® motorcycles

9794 TEN SPLINE RATCHETING OUTPUT WRENCH



- Reversible offset ratcheting EZ Grip wrench contains a 1-1/8" drive to service a ten spline crankshaft
- Used for rotation of the crankshaft/ check engine timing and parts clearance on Sportster® motorcycles

SPARK PLUG GAP

712A RAMP GAUGE LARGE CHROME



- Spark plug tool adjusts spark plug gap in graduated ramp sequence
- Sizes: SAE - .020 - .100; Metric - .60 - 2.40mm

2633A HIGH-ENERGY SPARK GAUGE



- Contains: Six round wires - .040, .044, .045, .050, .060, .080 with double end electrode adjusting tool
- Popular sizes required to gap spark plugs
- Round wire in this gauge permit exact gap checking at all angles

2634A ROUND STYLE WIRE GAUGE



- Contains: Six round wires - .025, .030, .034, .035, .040, .045 with double end electrode adjusting tool
- Most popular "standard ignition" spark plug gapping wire sizes
- Round wire in this gauge permit exact gap checking at all angles

4450A E-Z GRIP SPARK PLUG RAMP GAUGE



- Full range coverage for all spark plug gapping requirements from .020 to .080 (.60 to 2.00mm)
- Applications include those with distributor-less ignition systems
- Tool includes a recess specifically designed to adjust electrodes

GENERIC

The sizes, both decimal and metric equivalent, are permanently etched on each blade

21A 9-BLADE FEELER GAUGE

- 3" x 1/2" blades
- Steel ruler
- For ignition and general purpose



28A 9-BLADE TUNE-UP GAUGE

- 3" x 1/2" blades and five - 1" x 1/4" blades
- Steel ruler and adjusting tool



36A 32-BLADE FEELER GAUGE

- 3" x 1/2" blades
- Thirty-one steel and one .010 brass blade for transistorized engines



3013A 22-BLADE GO-NO-GO GAUGE

- 3" x 1/2" step-ground blades that are ground at the tip .002" less than the normal blade thickness to permit a quick check for proper setting or clearances



9-3MC 9-BLADE FEELER GAUGE

- 3" x 1/2" blades




FG-2 25-BLADE FEELER GAUGE

- 3" x 1/2" blades



FG-135 36-BLADE COMBINATION STANDARD AND BRASS FEELER GAUGE

- Thirty steel and six brass blades - 3" x 1/2" blades



27A 15-BLADE FEELER GAUGE

- 3" x 1/2" blades
- Steel ruler



29A 26-BLADE FEELER GAUGE

- 3" x 1/2" blades



36XK MASTER THICKNESS GAUGE

- 3" x 1/2" blades
- Thirty-one steel and one .010 brass blade for transistorized engines



4046A 26-BLADE FEELER GAUGE

- 3" x 1/2" blades



16-3-5/16MC 15-BLADE FEELER GAUGE WITH STEEL RULER

- 3" x 1/2" blades



FG-35-A 35-BLADE FEELER GAUGE

- 3" x 1/2" blades



(See chart on page 66 for sizes included in sets.)

	21A	27A	28A	29A	36A	36XK	3013A	4046A	9-3MC	16-3-5/16MC	FG-2	FG-35-A	FG-135
0.50-in Width	.0015"			•	•	•		•	•		•	•	
	.002"	•	•	•	•	•		•	•	•	•	•	•
	.0025"			•	•	•		•					•
	.003"	•	•	•	•	•		•	•	•	•	•	•
	.004"	•	•	•	•	•		•	•	•	•	•	•
	.005"		•	•	•	•		•	•	•	•	•	•
	.006"	•	•	•	•	•	•	•	•	•	•	•	•
	.007"			•	•	•		•			•	•	•
	.008"	•	•	•	•	•	•	•	•	•	•	•	•
	.009"			•	•	•	•	•			•	•	•
	.010"			•	•	•	•	•	•		•	•	•
	.011"		•	•	•	•	•	•		•	•	•	•
	.012"	•	•	•	•	•	•	•	•	•	•	•	•
	.013"	•	•	•	•	•	•	•		•	•	•	•
	.014"		•	•	•	•	•	•		•	•	•	•
	.015"			•	•	•	•	•	•		•	•	•
	.016"		•	•	•	•	•	•		•	•	•	•
	.017"			•	•	•	•	•			•	•	•
	.018"		•	•	•	•	•	•		•	•	•	•
	.019"			•	•	•	•	•			•	•	•
	.020"	•	•	•	•	•	•	•	•	•	•	•	•
	.021"			•	•	•	•	•			•	•	•
	.022"		•	•	•	•	•	•	•	•	•	•	•
	.023"			•	•	•	•	•			•	•	•
	.024"			•	•	•	•	•			•	•	•
	.025"	•	•	•	•	•	•	•	•	•	•	•	•
	.026"				•	•	•	•			•	•	•
	.027"						•	•			•	•	•
	.028"				•	•					•	•	•
	.029"										•	•	•
	.030"				•	•					•	•	•
	.031"										•	•	•
	.032"				•	•					•	•	•
	.033"										•	•	•
	.034"										•	•	•
	.035"				•	•					•	•	•
	.040"												
0.25-in Width	.025"		•										
	.030"		•										
	.035"		•										
	.040"		•										
	.044"		•										
Brass	.006"												•
	.008"												•
	.010"				•	•							•
	.012"												•
	.014"												•
	.016"												•
Steel Rule		•	•	•					•				
Electrode Tool			•										
Knurl Lock-Nut						•	•		•	•	•	•	•
Rivet	•	•	•	•	•								

LONG

The sizes, both decimal and metric equivalent, are permanently etched on each blade except where noted *

	12025	8-9MC	8-12MC	22-2-5/16MC
0.50-in Width	.0015"	•		
	.002"	•	•	
	.0025"			
	.003"	•	•	
	.004"	•	•	•
	.005"	•	•	•
	.006"	•	•	•
	.007"	•		•
	.008"	•	•	•
	.009"	•		•
	.010"	•	•	•
	.011"	•		•
	.012"	•		•
	.013"	•		•
	.014"	•		•
	.015"	•	•	•
	.016"	•		•
	.017"	•		•
	.018"	•		•
	.019"	•		•
	.020"	•		•
	.021"	•		•
	.022"			•
	.023"			•
	.024"			•
	.025"	•		•
	.026"			
	.027"	•		
	.028"			
	.029"			
	.030"	•		
	.031"			
	.032"			
	.033"			
	.034"			
	.035"			
	.040"	•		•
Knurl Lock-Nut	•	•	•	•

12025

25-BLADE FEELER GAUGE

• 12" x 1/2" blades



8-9MC

8-BLADE FEELER GAUGE

• 9" x 1/2" blades



8-12MC

8-BLADE FEELER GAUGE

• 12" x 1/2" blades



22-2-5/16MC

22-BLADE FEELER GAUGE

• 2-5/16" x 1/2" blades



METRIC

* Only metric sizes etched on blades.

342A *

15-BLADE METRIC FEELER GAUGE

• 3" x 1/2" blades



	342A	343A	FG-30
0.50-inch Width	0.04 mm	•	•
	0.05 mm		•
	0.06 mm	•	•
	0.07 mm	•	•
	0.08 mm	•	•
	0.09 mm		•
	0.10 mm	•	•
	0.15 mm	•	•
	0.20 mm	•	•
	0.25 mm	•	•
	0.30 mm	•	•
	0.35 mm	•	•
	0.40 mm	•	•
	0.45 mm	•	•
	0.50 mm	•	•
	0.55 mm	•	•
	0.60 mm	•	•
	0.65 mm		•
	0.70 mm	•	•
	0.75 mm		•
	0.80 mm	•	•
	0.85 mm		•
	0.90 mm	•	•
	0.95 mm		•
	1.00 mm	•	•
	Rivet	•	•
Knurl Lock-Nut		•	•

343A *

25-BLADE METRIC FEELER GAUGE

• 3" x 1/2" blades



FG-30 *

25-BLADE METRIC FEELER GAUGE

• 3" x 1/2" blades

