0015"			21A	27A	28A	29A	36A	36XK	3013A	4046A	9-3MC	16-3-5/16MC	FG-2	FG-35-A	FG-135
COO25"		0015"													
10025"															
COO3"			Ť	Ť	Ť										
COST															
## COS** COS** CO															
1000 1000			•		•						•				
The content of the				•		•	•	•		•		•	•	•	•
Bar			•	•	•	•	•	•	•	•	•	•	•	•	•
100°		.007"				•	•	•	•	•			•	•	•
## 1000" 1010"		.008"	•	•	•	•	•	•	•	•	•	•	•	•	•
Ham		.009"				•	•	•	•	•			•	•	•
Ham		.010"				•	•	•	•	•	•		•	•	•
### 1002" 0.012" 0 0 0 0 0 0 0 0 0				•		•	•	•	•	•		•	•	•	•
Steel Rule Ste			•		•						•				
Hand						_									
Ham 1015"															
49 0.16"															
No.	_										•				
1021" 1022" 10 10 10 10 10 10 10 1	ቱ			•								•	•		
1021" 1022" 10 10 10 10 10 10 10 1	Š					•	•	•	•	•				•	•
1021" 1022" 10 10 10 10 10 10 10 1	i.			•		•	•	•	•	•		•	•	•	•
1021" 1022" 10 10 10 10 10 10 10 1	0.0					•	•	•	•	•				•	•
March Marc	0.5	.020"	•	•	•	•	•	•	•	•		•	•	•	•
1023" 1024" 1025" 1026		.021"				•	•	•	•	•				•	•
1023" 1024" 1025" 1026		.022"		•		•	•	•	•	•		•	•	•	•
March Marc						•	•	•	•	•				•	•
1025"													•		
1026"															
1027"															
1.028"							•	•							•
1.029"									•						
1.030"							•	•					•		•
031"															
1032" 1033" 1033" 1034" 1035							•	•					•	•	•
1033" 1034" 1035" 1040" 1050														•	
1.034"		.032"					•	•					•	•	•
100 100		.033"												•	
100 100		.034"												•	
The state of the							•	•					•	•	•
Steel Rule Ste															
0.030" 0.035" 0.040" 0.044" 0.006" 0.008" 0.010" 0.012" 0.014" 0.016" 0	_														
1.006"	dth														
1.006"	Š														
1.006"	무.														
1.006"	.25														
0.008"	0.				•										
Steel Rule Old	Brass	.006"													•
Steel Rule Old		.008"													•
.014"							•	•							•
.014"															
.016" • Steel Rule • Electrode Tool • Knurl Lock-Nut •															
Steel Rule •															
Electrode Tool ● ■															
Knurl Lock-Nut ●	mt :											•			
					lacksquare										
Rivet • • • • • • • • •								•	•	•	•	•	•	•	•
		Rivet	•	•	•	•	•								

66

LONG

The sizes, both decimal and metric equivalent, are permanently etched on each blade except where noted *

ĺ		T			
		12025	8-9MC	8-12MC	22-2-5/16MC
	.0015"	•			
	.002"	•	•	•	
	.0025"				
	.003"	•	•	•	
	.004"	•	•	•	•
	.005"	•	•	•	•
	.006"	•	•	•	•
	.007"	•			•
	.008"	•	•	•	•
	.009"	•			•
	.010"	•	•	•	•
	.011"	•			•
	.012"	•			•
	.013"	•			•
	.014"	•			•
	.015"	•	•	•	•
ቱ	.016"	•			•
Vid	.017"	•			•
0.50-in Width	.018"	•			•
0-i	.019"	•			•
0.5	.020"	•			•
	.021"	•			•
	.022"				•
	.023"				•
	.024"				•
	.025"	•			•
	.026"				
	.027"	•			
	.028"				
	.029"				
	.030"	•			
	.031"				
	.032"				
	.033"				
	.034"				
	.035"				
	.040"	•			
Knu	rl Lock-Nut		•		•
KITU	II LOCK NUL	•	_	_	•

12025

25-BLADE FEELER GAUGE

• 12" x 1/2" blades



8-9MC

8-BLADE FEELER GAUGE



8-12MC

8-BLADE FEELER GAUGE

• 12" x 1/2" blades



22-2-5/16MC

22-BLADE FEELER GAUGE

• 2-5/16" x 1/2" blades



0.04 mi

0.05 mr

0.06 mm

METRIC

* Only metric sizes etched on blades.

342A *

15-BLADE METRIC

FEELER GAUGE
• 3" x 1/2" blades





343A *

25-BLADE METRIC FEELER GAUGE

• 3" x 1/2" blades



FG-30 *

25-BLADE METRIC FEELER GAUGE

• 3" x 1/2" blades



	0.07 mm	•	•
	0.08 mm	•	•
	0.09 mm		•
	0.10 mm	•	•
	0.15 mm	•	•
	0.20 mm	•	•
	0.25 mm	•	•
	0.30 mm	•	•
	0.35 mm	•	•
5	0.40 mm	•	•
	0.45 mm	•	•
	0.50 mm	•	•
	0.55 mm	•	•
	0.60 mm	•	•
	0.65 mm		•
	0.70 mm	•	•
	0.75 mm		•
	0.80 mm		•
	0.85 mm		•
	0.90 mm		•
	0.95 mm		•
	1.00 mm		•
	Rivet	•	

•



67