

Workforce® Retractable Open Face Hose Reels - Single Axle Arm

These retractable, open face hose reels are ideal for indoor shop and industrial applications.

FEATURES:

- **Multi-Position Guide Arm** - Allows mounting on wall, tank or overhead
- **Durable Heavy-Duty Steel Construction** - Provides strength and stability to the reel and bracket
- **Corrosion-Resistant Powder Coating** - Provides extra measure of protection against the elements
- **Four-Way Direction Rollers** - Allow the hose to be easily pulled from the reel
- **Self-Locking Fasteners** - Stay tight even in mobile installations
- **Narrow Size** - Ideal for easy placement and storage
- **Multi-Position Release Ratchet** - Allows appropriate amount of hose to be extended for each job site
- **Metal Latching Pawl** - Makes an audible clicking sound allowing the latching zone to be locked quickly and easily
- **Fully-Enclosed Spring** - Packed with grease for extended life
- **Lead-in Hose Included** - 5 ft. Rubber or SAE 100R1 or R2 lead-in hose (1/4 in. MNPT x 1/4 in. NPSM female swivel)



L8641

Reel Part No.	Application	Hose I.D.	Hose Length	Hose Material	Working Pressure @ 70°F	Temperature Range (F°)	Reel Inlet	Hose Outlet	Weight	Retail Packaging
L8611	Compressed Air	3/8 in.	50 ft.	Rubber	300 psi	-4° to 140° F	3/8 in. FNPT	1/4 in.*	36 lbs.	●
L8621	Grease	1/4 in.	50 ft.	SAE 100R2	5,000 psi	0° to 190° F	1/4 in. FNPT	1/4 in. MNPT	62 lbs.	-
L8631	Oil	1/2 in.	50 ft.	SAE 100R1	2,000 psi	0° to 190° F	1/2 in. FNPT	1/2 in. MNPT	62 lbs.	-
L8632	Oil	1/2 in.	30 ft.	SAE 100R1	2,000 psi	0° to 190° F	1/2 in. FNPT	1/2 in. MNPT	55 lbs.	-
L8641**	Air/Water	1/2 in.	50 ft.	Rubber	300 psi	-4° to 140° F	1/2 in. FNPT	1/2 in. MNPT	57 lbs.	●

*1/4 in. MNPT x 3/8 in. bushing included

**40°F to 140°F for water application