

RESISTANCE SPOT WELDERS

LAS-8 AUTOSPOT

The LAS-8 is a compact, but powerful mulitfuntion resistance spot welder. Generating 8,000 amps, the LAS-8 can do both squeeze type and single sided welding, as well as dent pulling.

- · Programmable keypad for precise weld settings
- · Pinch Gun suspended for convenient, easy use
- Single sided welding capability
- Includes dent pulling attachment
- Carbon arc shrinking capability



Part No.	Ordering No.	Description	Primary Voltage	KVA Rating	Line Fuse	Size	Power Input Cable	Maximum Welding Capacity			
LAS-8	20908	AUTOSPOT®	208/230Single Phase 60/50HZ	8	50 Amp	44" H x 20"W x 26"L	25', No. 10/3 wire	20 ga. (single sided) 3 pc. 18 ga. (smartgun)	285 lbs.		
LAS-945	20945	Long reach e	Long reach electrode arms - 22"								
LAS-947	20947	Mid-depth arr	Mid-depth arms - 14"								
LAS-946	20946	Wheelhouse	Wheelhouse electrode arms								
LAS-5210	2095210	Standard Sma	Standard Smart Gun Tips (each)								
LAS-5211	2095211	Long Reach	Long Reach Tips (each)								
LAS-7335	2097335	Wheelhouse	Wheelhouse tips (used with one LAS-5210 tip)								
LAS-7654	2097654	Single Side V	Single Side Weld Tip (for accessory multi-funtion gun)								

LENCOSPOT® MARK II®

With the *LENCOSPOT® MARK II®* Welder, you can make factory type spot welds in the shop. It's simple to operate...simply press the two electrode guns against the work, press the button and the welder does the work. Two spot welds every time. Time of the welds are automatically controlled by solid state electronic circuitry. No guess work...no gases or wire to buy...no warpage...no flame...and perfect welds time after time, panel after panel. It is the perfect answer to lower the ever rising labor costs.

THE LENCOSPOT® MARK II® Autobody Dual-Spot Welder Offers All These Features:

- Protected Control Panel
- Streamlined Construction
- On/Off Indicating Switch
- Solid State Timer
- Tool Storage Space
- Easy Portability

Part No. L-4000



ORDERING INFORMATION

	ONDERING IN ONMATION												
Part No.	Ordering No.	Description	Primary Voltage	KVA Rating	Line Fuse	Size	Power Input Cable	Welding Cable Length	Maximum Welding Capacity	Weight			
L-4000	20400	LENCOSPOT® Mark II®	208/230Single Phase 60/50HZ	4	50 Amp	20 1/2"Hx11"Wx16"L	50',No.10/3 wire	5'	20 Gauge Autobody Steel	110 lbs.(49.9kg)			
L-4480	20480	LENCOSPOT® Mark II®	480 Single Phase 60/50HZ	4	30 Amp	20 1/2"Hx11"Wx16"L	Not Available	5'	20 Gauge Autobody Steel	97 lbs. (44kg)			
A-260	29130	5' Cable Assembly						5'		12 lbs. (5.44Kg)			
A-144	21050	Regular Welding Tips (pkg 2)											
Δ-145	21040	Drin Bail Welding Tips (pkg 2)											