

## Lincoln-style air couplers and nipples

Model 815 1/4 in. (f)



Model 815 cut-away 1/4 in. (f)



Model 11659 1/4 in. (m)  
Model 11660 1/8 in. (m)



Model 11661 1/4 in. (f)



**Coupler and nipple can be joined without user pulling back on sleeve. A true quick-connect design!**

Lincoln air couplers provide split-second coupling of grease guns, impact wrenches, paint sprayers and other air-operated equipment. Air flow products from Lincoln have the features and durability you demand for your business.

- Positive action locking mechanism so coupler cannot be detached accidentally.
- Extra large air passage insures greater air flow.
- Automatic air check valve shuts off air instantly when uncoupled, providing leak-proof seal.
- Corrosion-resistant steel plug and stainless steel check and check spring for long service life.
- Free swiveling action prevents curling or kinking of air hose.

**Lincoln-style couplers and nipples for 1/4 in. ID**

**Models 815, 11659, 11660, 11661**

250 psi (17 bar) maximum operating pressure. Extra-long stem of nipple and coupler body assures long service life, easy connections under severe operating conditions. Maximum air flow 52 scfm (1,5 sm<sup>3</sup>/min.) at 100 psi (7 bar). Model 815 length 2 1/2 in. (65 mm); diameter 1 1/16 in. (37 mm); weight 4 1/2 oz. (126 g).

**Note:** Model 11659 is available non-packaged for bulk orders as model 238394.