

# Suction guns

### Model 616 fluid extractor/dispenser

Simple-to-use, syringe-action tools feature a large, 1.5-liter fluid reservoir, twist-valve and dual-seal piston designed to transfer fluids quickly with no mess.

- Sturdy, polymer-based construction
- Cylinder marked with fluid levels
- Rubber grip for operator convenience
- Double-seal design prevents leaks at the piston
- Integrated stand to prevent rolling
- Twist-valve on hose end eliminates fluid leaks
- Clear, 16-inch hose enables operator to see fluid being transferred

### Model 617 DEF fluid extractor/dispenser

Same as model 616 except comes with DEF compatible hose.

### Model 615 suction gun

18 oz. (532 cm<sup>3</sup>) capacity with 12 in. (304,8 mm) flex hose. Perfect for draining and filling differentials, clutches, power steering reservoirs and transmissions. Needs no priming. Features heavy-duty steel barrel and non-slip knurling.

### Model G150 suction gun

Holds up to 17 oz. (503 cm<sup>3</sup>) of fluid. Flexible nozzle.



### Suction guns

Model	Capacity size		Extension	Size <sup>1)</sup>	
	Bulk			in.	mm
–	oz.	cm <sup>3</sup>	–	in.	mm
616	50.7	1 500	16 in. (406 mm)		
617	50.7	1 500	16 in. (406 mm)		
615*	18	532	12 in. (305 mm)	14	356
G150*	17	503	12 in. (305 mm)	13 1/2	343

<sup>1)</sup> Includes rigid extension  
 Specifications: output 1 oz. (28 cm<sup>3</sup>) per 33 strokes using No. 1 grease at 70 °F (21 °C). Barrel diameter 2 1/4 in. (57 mm)  
 \***⚠️WARNING** California Proposition 65: Cancer and reproductive harm. [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Portable used fluid handling equipment – collection equipment, general



Model 91197



Model 82786



Model 3608



Model 66493



Model 70526



Model 247748

Optional accessories

Model	Name	Description	Compatible models
91197	14 in. (356 mm) diameter bowl	Standard on models 613 and 613DK; optional on model 3644	613, 613DK, 3644
82786	14 in. (356 mm) diameter bowl with lid	Includes hinged lid with latch	613, 613DK, 3644
3608	20 in. (508 mm) diameter bowl	Standard on model 3644; optional on models 613 and 613DK	613, 613DK, 3644
66493	16 gallon/120 lb. (60 liter/54 kg) drum	Steel drum with 1 in. NPT port for drain spigot. Standard on model 613DK; optional on models 613 and 3644	613, 613DK, 3644
70526	Drain spigot	Gravity drain spigot with 1 in. male NPT. Standard on model 613DK; optional on models 613 and 3644	613, 613DK, 3644
247748	Diaphragm pump evacuation kit	Includes fluid pick-up tube and 3/4 in. male camlock fitting for connection to diaphragm pump or other fluid transfer system. Installs to lid so that fitting extends straight up	613, 613DK, 3644

**Model 615\* suction gun**

Holds up to 18 oz. (532 cm<sup>3</sup>) of fluid. Flexible nozzle for transmission, differential or oil filter service. Precision follower fitted to barrel for superior suction and is impervious to oil, grease and water. Finished in rust-resistant, powder coated blue paint.

**Model G150\* suction gun**

17 oz. (503 cm<sup>3</sup>) capacity with 12 in. (304,8 mm) flex hose. Perfect for draining and filling differentials, clutches, power steering reservoirs and transmissions. Needs no priming. Features heavy-duty steel barrel, electro-static, corrosion-resistant finish and non-slip knurling.



Model 615

**\* ⚠ WARNING**  
 California Proposition 65:  
 Cancer and reproductive harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Model G150



## Suction guns

### Model 615\*

Holds up to 18 oz. (532 cm<sup>3</sup>) of fluid. Flexible nozzle for transmission, differential or oil filter service. Precision follower fitted to barrel for superior suction and is impervious to oil, grease and water. Finished in rust-resistant, powder coated blue paint.

### Model G150\* suction gun

17 oz. (503 cm<sup>3</sup>) capacity with 12 in. (304,8 mm) flex hose. Perfect for draining and filling differentials, clutches, power steering reservoirs and transmissions. Needs no priming. Features heavy-duty steel barrel, electro-static, corrosion-resistant finish and non-slip knurling.

**\* ⚠ WARNING**  
 California Proposition 65:  
 Cancer and reproductive harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## Oilers and measurers

### Oiler cans

Guardian offers oilers in a variety of sizes with rigid or flexible spouts to fit your needs.

#### Oiler cans

Model	Description
G502	6 oz. (170 ml), rigid spout
G503	6 oz. (170 ml), flexible spout
G504	12 oz. (340 ml), rigid spout
G507	16 oz. (454 ml), flexible spout

### Flexible spout measures

Guardian's flexible spout measures are designed for one-hand operation. Thumb-operated valve controls flow. 14 in. (355,6 mm) flexible spout with tapered tip swings into the necessary angle for hard-to-reach spots. Recessed bottom drains fully and guards against puncture. Rolled-edge top helps prevent spilling.

#### Flexible spout measures

Model	Description	
	qt.	liter
G524	4	3,8
G525	5	4,7
G528	8	7,6