ENGINE



## **52500 MECHANIC'S STETHOSCOPE**

Unique Sound Chamber & Super Thin Diaphragm Greatly Amplifies Sounds.

Quickly pinpoints the source of mechanical noises in engines, transmissions, differentials and bearings. 52500 Stethoscope. Skin-packed. Shipping wt. 6 oz.



## **52700** AUDIO STETHOSCOPE

Detects Noise From Vacuum Leaks, Exhaust Leaks, Wind Noise & Air Leaks.

Detects air induced sounds not detected by conventional stethoscopes. Place funnel over suspected air leak.


52700 Audio Stethoscope. Skin-packed. Shipping wt. 9 oz.

## **52750** STETHOSCOPE SET

Dual Purpose Set Detects Both Mechanical & Air Induced Sounds.

Use the black diaphragm chamber & screw-in metal probe to detect mechanical sounds from bearings, engines, transmissions, etc. For air induced sounds, attach the vinyl hose to hollow tube and funnel assembly. The funnel amplifier will detect noises from vacuum leaks, exhaust leaks, air leaks and wind noise. For hard to reach locations, remove the funnel and use the hollow tube.

52750 Stethoscope Set. Clam Shell. Shipping wt. 10 oz.







MECHANICAL SOUNDS



77060 77080 HARMONIC BALANCER SOCKETS

## Heavy-Duty Impact Sockets Designed with More Than the Standard Socket Mass to Direct More Energy to Removing the Bolt.

77060 has more than two times the standard socket mass. Can be used on Honda Civic engines that use a 17mm hex pulley damper bolt or other 17mm applications. 77080 can used on Honda Accord engines that use a 19mm hex pulley damper bolt or other 19mm applications. Heat-treated, impact-quality alloy steel. Use with 1/2" drive.

77060 17mm Harmonic Balancer Socket. Box with Color Label. Shipping wt. 2 lbs. 77080 19mm Harm Bal Sckt Honda. Box with Color Label. Shipping wt. 2 lbs.

www.lislecorp.com



U.S. Pat No. 10,040,176