

## 13300 5 PC. FILTER SOCKET SET

Set of 5 Low Profile Oil and Fuel Filter Canister Sockets in One Handy Case.

Contains very low profile, 6 point 24mm, 27mm, 29mm, 32mm and 35/36mm sockets for use on oil and fuel filter canisters when replacing the element. Use with 3/8" drive. 5 pc. Set includes:

**13310** - 24mm for Cadillac and some BMW

**13320** - 27mm for 2003 and later Mercedes 1.8L, Smart and some VW



**\*14500** - 35/36mm for Ford 6.0L Diesel Fuel and Oil Filter Housings, Mini Cooper and some BMW Oil Filter Housings, and Mack Truck Oil Filter Housing

**\*14600** - 29mm (1-1/8") for Dodge Cummins Fuel Filter Housing

**\*14700** - 32mm (1-1/4") for GM Ecotec, 2.0L, 2.2L and 2.4L Four Cylinder Oil Filter Housing; Some Saturn & Saab

**13300 5 Pc. Filter Socket Set.** Molded Case. Shipping wt. 1 lb. 13 oz.

\*Available individually packaged for display.



## 60200 HEAVY DUTY STRAP FILTER WRENCH

A Heavy-Duty Heat Treated Alloy Steel Yoke and Strong Web Strap.

Use with 1/2" drive to remove or install filters and other objects up to 6-1/2" in diameter. 3-5/8" long yoke fits into tight areas.

**60200 Heavy Duty Strap Filter Wrench.** Skin-packed. Shipping wt. 8 oz.




FILTER

## 63500 "BIG RANGE" FILTER WRENCH

For Filters Up to 6" (152.4mm).

Adjusts quickly to fit any spin-on oil filter up to 6" diameter. Use with 1/2" drive or 3/4" wrench. Strong polypropylene belt.

**63500 Big Range Filter Wrench.** Skin-packed. Shipping wt. 10 oz.



## 63250 63600 FILTER WRENCHES

**63250** Range from 3-1/8" to 3-7/8".

**63600** Range from 2-1/2" to 3-1/8".

Steel jaws grip filter without slipping. Works in tight spots from the front of the filter using 3/8" drive.


**63250 Wide Range Filter Wrench.** Skin-packed. Shipping wt. 14 oz.

**63600 Import Car Filter Wrench.** Skin-packed. Shipping wt. 14 oz.

**63630 Replacement Spring**



63250



63600