

49200 HEAVY DUTY INTERNAL / EXTERNAL SNAP RING PLIERS

Reversible Action for Internal and External Applications.

The heavy duty plier construction and larger tips are designed for larger snap rings. The tool quickly converts from internal to external use by pivoting the handles. Tough tool easily compresses internal rings and expands external rings. Conical tip ends prevent the snap ring from slipping off the tips. Ten tip sets in a handy plastic pouch are included to fit a wide range of snap ring sizes. Tips are easily interchanged by turning a set screw, wrench included.

49200 Heavy Duty Snap Ring Pliers. Skin-packed. Shipping wt. 12 oz. 49460 Replacement Tips

46200 SNAP RING PLIERS, SMALL

Reversible Action for Both Internal and External Snap Rings. Smaller Design to Fit Tight Spaces.

The tool quickly converts from internal to external use. Simply pivot each handle to the opposite side to reverse action. Includes four pairs of tips to fit a wide range of snap ring sizes. 45° and 90° tips for hard to reach areas. Conical tip ends prevent the snap ring from slipping off of the tips.

46200 Snap Ring Pliers, Small. Skin packed. Shipping wt. 4 oz.

46250 Replacement Tip Set.

46000 Combination Internal / External Snap Ring Pliers

A Handy Combination Tool for Internal and External Snap Rings.

Compresses internal rings in one position. Move the quick-change reversing lever to expand external rings. Four sets of tips in a plastic box.

46000 Snap Ring Pliers. Skin-packed. Shipping wt. 7 oz.

46250 Replacement Tip Set

44900 LOCK RING PLIERS

For Removing and Installing All Types of Lock Rings. Spreads lock rings commonly found on transmissions, master cylinders, brakes and other applications. Specially designed jaws are knurled on the end to prevent slipping.

44900 Lock Ring Pliers. Skin-packed. Shipping wt. 8 oz.

42400 5 PC. AIR LINE DISCONNECT SET

Disconnects Quick Connect Push-In Connectors Found on Heavy-Duty Truck Air Systems and More.


Disconnects air systems on brakes, suspension, steering, engine, transmission and other auxiliary equipment. Also disconnects other quick connect push-in fittings, including: flow control valves, check valves, shuttle valves, quick exhaust valves and other function control fittings. Smallest size works on automatic adjusting air suspension systems for automobiles. Five popular sizes: 1/8-5/32", 1/4", 3/8", 1/2" and 5/8". Each tool is double-ended for hard-to-reach areas.

 42400 5 pc. Air Line Disconnect Set. Skin-packed. Shipping wt. 1 lb.


 42100 1/4" Air Line Disconnect
 42110 3/8" Air Line Disconnect

 42120 1/2" Air Line Disconnect
 42130 5/8" Air Line Disconnect

 42470 1/8-5/32" Air Line Disconnect
 42130 5/8" Air Line Disconnect




46250 Replacement Tip Set Includes: .045" straight tips .060" straight tips .045" 45 degree tips .035" 90 degree tips




EXPANDS

EXTERNAL RINGS







56