

58100 INNER TIE ROD TOOL SET, 12 PC.

Improved Socket Design to Work on Longer Applications.

The long socket slips over tie rod end and crowfoot engages on socket for easy removal and installation of tie rods with inaccessible wrench flats. Includes 12 crowfeet, sizes 1-3/16", 1-1/4", 1-3/8", 1-1/2", 1-5/16", 1-7/16", 29mm, 32.5mm, 33.6mm, 38.4mm, 40mm and 42mm, to fit many cars, trucks and SUVs.

58100 Inner Tie Rod Tool Set 12pc. Molded Case. Shipping wt. 7 lbs. 2 oz.

54490 40mm Crowfoot	54550 Retainer	54560 33.6mm Crowfoot
54570 1-7/16" Crowfoot	54580 38.4mm Crowfoot	54590 42mm Crowfoot
58101 1-3/16" Crowfoot	58020 1-1/4" Crowfoot	58030 1-5/16" Crowfoot
58050 1-3/8" Crowfoot	58070 1-1/2" Crowfoot	58080 29mm Crowfoot
58090 32.5mm Crowfoot	58110 Socket	58130 Case for 58100

Supersedes 46800 & 54500



72450 MANIFOLD DRILL TEMPLATE FOR FORD 6.2L

Removes Broken Exhaust Manifold Bolts Without Damaging the Head.

Tapered bolts center base plate over bolt holes and slip fit bushing allows you to move from hole to hole without moving base plate. Drill depth gauge to make sure water jacket is not pierced. The screw extractor is then used to remove the broken bolt. Includes bushing to drill to tap size when extractor cannot be used.

72450 Drill Kit Ford 6.2L. Molded Case. Shipping wt. 4 lb. 12 oz.

68690 Stud Extractor	71530 3/16" Cobalt Drill
71540 17/64" Cobalt Drill	72310 .322 Q Cobalt Drill
72320 3/16" Drill Bushing, Large	72330 17/64" Drill Bushing, Large
72340 .322 Q Drill Bushing, Large	72360 Lock Screw
72370 10mm Tap Guide	72460 Drill Plate for Ford 6.2L
72470 Drill Depth Gauge for Ford 6.2L	72480 Alignment Bolt 10mm x 1.25, 1 pc.
72490 Alignment Nut 10mm x 1.25, 1 pc.	72510 Case for 72450



52460 RAZOR BLADE SCRAPER

Strong, Solid Handle Ideal for Stripping Paint, Caulk, Labels, Overspray, Gasket Material, Urethane and Glue.

No sharpening needed, just replace the blade. Protective cover keeps blade sharp and prevents cuts. Includes one standard single edge blade.

52460 Razor Blade Scraper. Skin Packed. Shipping wt. 3 oz.

