

38700 SPINDLE SNAP RING PLIERS FOR FORD SUPER DUTY

Used to Replace the Spindle Snap Rings Found on 2007 and Newer Ford Super Duty Pickups.

Rigid plier design with narrow tips to fit into the 2-1/2" inside diameter of the hub. Ratcheting lock mechanism holds the snap ring open for easy removal and installation.

38700 Spindle Pliers Ford. Skin-Packed. Shipping wt. 15 oz.

38710 Straight Tip Set

59330 Screw

67940 Washer



Patent Pending

61840 Engine Barring Tool for Paccar

Allows the Engine Crank to Be Manually Adjusted.

Works on Paccar MX-13 engines, found on Kenworth and Peterbilt trucks. Can be used to make sure the engine rotates freely while troubleshooting other issues. Use with 1/2" square drive.

61840 Engine Barring Tool for Paccar. Box. Shipping wt. 10 oz.





22130 36MM 12 PT. BARRINGWRENCH FOR DURAMAX

Works on 2001 and Newer Duramax Engines to Turn the Crankshaft Allowing Access to the Torque Converter Bolts.

The 22-1/2" long, offset design allows the 36mm 12 point wrench to clear the stabilizer bar from under the truck. The wrench can also be used to make sure the engine rotates freely while troubleshooting other issues. Dual material grip for comfort.

22130 36mm Barring Wrench. Label. Shipping wt. 1 lb. 14 oz.



59600 DEUTSCH TERMINAL TOOL

Works on OEM Electrical Connectors Used on Trucks and Equipment Such as Caterpillar, Kenworth, Peterbilt, Freightliner, Mack & More.

Also used on some Harley Davidson and industrial equipment connectors. Slotted tubes are made from stainless steel which is more durable than plastic. Built in a convenient "spider" design so the most popular sizes are always available. To use, slide appropriate size slotted tube over wire. Push the tool into the grommet, bottoming out the tool on the terminal. DO NOT TWIST THE TOOL. Pull the wire-terminal out of the connector.

59600 Deutsch Terminal Tool. Skin-Packed. Shipping wt. 2 oz.





■ YouTube

Three Tip Sizes to Fit:

14-16 AWG and size 14 contacts
16-18 AWG and size 18 contacts
20-24 AWG and size 20 contacts

21520 Truck Pedal Depressor

Depresses & Holds Clutch Pedals & Brake Pedals.

The two-piece, telescoping tool extends to pedal & locks in position. Brace the formed plate against the seat or steering wheel for support. Tool extends from 18-1/2" to 34-1/2".

21520 Truck Pedal Depressor. Skin-Packed. Shipping wt. 2 lb.s 4 oz.

45980 Replacement Rubber Tip

