

Commercial Air Circulators - 115V

Pedestal & Wall / Vertical Mount Unit Packs

Non-Oscillating



Adjustable Floor Model
Solid Base



Vertical Mount



Wall Mount

2 Year Warranty

Features

- 115V, 1/4 HP, 1 Phase, 3 Speed, TEAO Ball Bearing Motor
- A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.
- Unit Pack ships with Motor, Specified Style Mounting, Propeller & Guard In One Carton
- Pedestal Models Adjust 43" - 63" ; 26" Base Diameter
- Wall / Vertical Mount Models Include Safety Cable
- 15' Supply Cord and Three Prong Plug Included
- Models are UPS Shippable in One Carton
- Guard Meets OSHA Standards
- Galvanized Steel Propeller
- All Stocked



Type	Tilt (In Degrees) Non-Oscillating	
	Up	Down
Floor	30°	15°
Wall	30°	50°
Vertical	0°	90°

0° = Horizontal Plane

EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	CFM			RPM			F.L. Amps	Ship Wt.
					High	Med	Low	High	Med	Low		
71584	CA24APE	24"	Adjustable Floor (S.B.)	1/4	4400	3460	2460	1100	800	600	3.5	82
71572	CA24WC	24"	Wall / Vertical Mount	1/4								42
71586	CA30APE	30"	Adjustable Floor (S.B.)	1/4	6100	4400	2700	1100	800	600	3.5	87
71573	CA30WC	30"	Wall / Vertical Mount	1/4								49

Non-Oscillating Assembled Fan Heads



Features

- Motor, Guard, and Propeller are Pre-Assembled
- 30" Head Assembly is UPS OverSize 2

EDP No.	Catalog No.	Prop Dia.	HP	Ship Wt.
71590	CA24	24"	1/4	39
71591	CA30	30"	1/4	48

