

Commercial Air Circulators - 115V

Pedestal & Wall / Vertical Mount Unit Packs

Non-Oscillating



2 Year Warranty Features

- 115V, 1/4 HP, 1 Phase, 3 Speed, TEAO Ball Bearing Motor
- A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.
- Unit Pack ships with Motor, Specified Style Mounting, Propeller & Guard In One Carton
- Pedestal Models Adjust 43" 63"; 26" Base Diameter
- Wall / Vertical Mount Models Include Safety Cable
- 15' Supply Cord and Three Prong Plug Included
- Models are UPS Shippable in One Carton
- Guard Meets OSHA Standards
- · Galvanized Steel Propeller
- · All Stocked







Туре	Tilt (In Degrees) Non-Oscillating				
	Up	Down			
Floor	30°	15°			
Wall	30°	50°			
Vertical	0°	90°			

0° = Horizontal Plane

EDP No. Ca	Catalog No. Prop D	Prop Dia.	. Fan Style	НР	CFM		RPM			El Amno	Ship Wt.	
	Catalog No.	Ргор Біа.			High	Med	Low	High	Med	Low	F.L. Amps	Snip Wt.
71584	CA24APE	24"	Adjustable Floor (S.B.)	1/4	4400	2460	2460	1100	900	600	2.5	82
71572	CA24WC	24"	Wall / Vertical Mount	1/4	4400	3460	2400	1100	800	600	3.5	42
71586	CA30APE	30"	Adjustable Floor (S.B.)	1/4	6100	4400	2700	1100	800	600	3.5	87
71573	CA30WC	30"	Wall / Vertical Mount	1/4		J 4400	2700	1100	000	000	3.5	49

Non-Oscillating Assembled Fan Heads



Features

- Motor, Guard, and Propeller are Pre-Assembled
- 30" Head Assembly is UPS OverSize 2

EDP No.	Catalog No.	Prop Dia.	HP	Ship Wt.
71590	CA24	24"	1/4	39
71591	CA30	30"	1/4	48