Accessories > POLISHING / WIRE BRUSHES & WHEELS



		Sanding /	Polishi
Description	Grinder/Polish Size	ier Model	Part #
Rubber Pad	4"	GA4030/K	743009-6
	4"	PW5001C 9557NB/PB, 9564CV/P/PC,	743079-5
	4-1/2"	GA4530, GA4534 XAG01, XAG03, XAG06	743036-3
	5" 90	005B/BZ, 9015A,9565CV/PC, GA5010Z, GA5020/Y	743015-1
	6"	9566CV/PC, GA6010, GA6020	743016-9
		GA7001L, GA7911, GV7000C, 9077SL,	
		9218SB, 9227C, 9227CY, 9237C, GA7011C, GA7020,	192978-2
Plastic Pad	5"	GA7021, GA7040S GV5000, GA5010	743025-8
Hook-and-Loop Backing Pad	7"	9227C/CY, 9237C, PV7001C	743052-5

Wire Brushes								
	Description	Diameter	Arbor	Max. RPM	l Model	Carbon Steel Part #	Stainless Steel Part #	
Crimped Cup		3"	M10 x 1.25	14,000	GA4030	743201-4		
Knot Cup	 Excellent for flat surfaces, edges, paint, scale, light rust removal Use with spindle mount washer (261039-0) 	3"	5/8" - 11	14,000	9005B/BZ,9557NB/PB, 9558PB, 9564CV/PC, 9565CV/PC, GA4530, GA4534, GA5010Z, GA5020/Y	743205-6		
		4"	5/8" - 11	10,000	9566CV, GA7001L,GA7011C, GA7040S	743207-2		
		6"	5/8" - 11	6,600	GA7001L, GA7011C, GA7020, GA7021, GA9020, GA9040S	743206-B		
	Ideal for tight operations, corners	2-3/4"	M10 X 1.25	14,000	GA4030	743201-5A	743204-A	
	and angle welds Rugged knot construction .020" Type 302 stainless steel wire is corrosion	2-3/4"	5/8" - 11	14,000	9005B/BZ,9557NB/PB, 9558PB, 9564CV/PC, 9565CV/PC, GA4530, GA4534, GA5010Z, GA5020/Y	743209-A	743209-B	
	resistant • Use with spindle mount washer (261039-0)	4"	5/8" - 11	10,000	9564CV/PC/P, 9565CV/PC, 9566CV/PC, GA7001L, GA7011C, GA7020, GA7021, GA7040S	743208-0A		
		6"	5/8" - 11	6,600	GA7001L, GA7011C, GA7020, GA7021, GA9020, GA9040S, GA9040S	743206-A		

			Vire Whe	els				
	Description	Diameter	Arbor	Max. RPM	Model	Carbon Steel Part #	Stainless Stee Part #	
tringer Bead Twist Wheel		4"	M10 x 1.25	20,000	GA4030	743203-5A	743204-B	
	3/16" face width for stringer weld, piping, pipe grooves, and hard to reach areas 020" Type 302 stainless steel wire is highly	4"	5/8" - 11	20,000	9005B/BZ, 9557NB/PB, 9558PB, GA4530, GA4534, GA5010Z, GA5020/Y	743213-A	743213-B	
	corrosion resistant —	5"	5/8" - 11	12,500	9005B/BZ, 9557NB/PB, 9558PB, GA7001L, GA7011C, GA7020/21, GA9020, GA9040S	743216-A		
not Full Cable Twist Wheel		4"	M10 X 1.25	20,000	GA4030		743203-4B	
	1/4" face width for narrow to medium width work, excellent for cleaning welds .020" Type 302 stainless steel wire is highly corrosion resistant	4"	5/8" - 11	20,000	9564CV/PC/P, 9565CV/PC, 9566CV/PC, GA7001L, GA7011C, GA7020, GA7021, GA7040S	743211-A	743214-A	
		5"	5/8" - 11	12,500	9564CV/PC/P, 9565CV/PC, 9566CV/PC, GA7001L, GA7011C, GA7020, GA7021, GA7040S	743217-A		
		6"	5/8" - 11	12,500	GA7001L, GA7011C, GA7020, GA7021, GA70405, GA9020, GA9040S	743218-A		
Cnot Standard Twist Wheel		4"	M10 X 1.25	20,000	GA4030	743203-4C		
	1/2" face width for broader cleaning coverage. For deburring, edge blending & finishing. Removes rust, scale, and weld splatter	4"	5/8" - 11	20,000	9005B/BZ, 9557NB/PB, 9558PB, GA4530, GA4534	743212-A		
					eel with 5/8"-11	_ p	art #	
Small Angle Grir		All	323015-A					
	Allows cup or wheel with 5/8"-11 arbors to fit M10 x 1.50 arbors					323016-A		

Warning: Consult owner/operator manual and adhere to all safety precautions for accessory items. Always use recommended guards. Failure to do so may result in serious injury or death from exploding wheels. Refer to ANSI B7.1 and owner/operator manual for proper accessory mounting and grinding procedures. Always wear eye protection that meets ANSI Z87.1 requirements plus a face shield wherever possible. Tools must always be properly guarded.