

CAPACITY



Miters 0-47° left and 0-57° right; bevels 0-45° left and 0-5° right

TECHNOLOGY



Automatic Speed Change™ adjusts cutting speed and torque during cut for optimum performance

PERFORMANCE

Two 18v LXT® Batteries deliver the power and performance of a corded miter saw

PORTABLE & POWERFUL



NEW XSL02Z

18v X2 LXT® BRUSHLESS 7-1/2" COMPOUND MITER SAW
Powerful BL™ Brushless Motor Delivers 5,700 RPM for Faster Cutting

- Two 18v LXT® Lithium-Ion Batteries deliver the power and performance of a corded miter saw without leaving the 18v LXT® platform
- Automatic Speed Change™ technology adjusts cutting speed and torque during cut for optimum performance
- The BL™ Brushless Motor eliminates carbon brushes, enabling the BL Motor to run cooler and more efficiently for longer life
- Efficient BL™ Brushless motor is electronically controlled to optimize battery energy use for up to 50% longer run time per charge

Model XSL02Z Includes: 7-1/2" 40T C.T. Miter Saw Blade (A-90629); Battery and Charger not included

Blade Diameter	7-1/2"
Arbor	5/8"
Max. Cutting Capacity (Bevel/Miter): 90°/90° (2-1/16" x 11-3/4"), 45°/45° (2-1/16" x 8-3/8")	
No Load Speed	5,700 RPM
Battery	2X 18v LXT® Lithium-Ion
Dimensions (LxWxH)	25-3/4" x 17" x 17-1/2"
Net Weight (with battery)	28.9 lbs.
Shipping Weight	38 lbs.

Tool only - battery and charger not included



XSL01

18v LXT® 7-1/2" COMPOUND MITER SAW KIT
Large Cutting Capacity up to 2-1/16" and 11-3/4" Crosscuts at 90°

- Powerful Makita-built motor delivers 2,200 RPM
- Weighs only 27.5 lbs. with battery for reduced operator fatigue
- Four steel rail sliding system increases rigidity to produce superior accurate cuts
- Miters 0-47° left and 0-57° right; bevels 0-45° left and 0-5° right

Model XSL01 Includes: (2) 18v LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18v Lithium-Ion Rapid Optimum Charger (DC18RC), 7-1/2" 40T C.T. Miter Saw Blade (A-90912), (2) Extension Wing (322312-4), Vertical Vise (122571-8), Dust Bag (122852-0), Triangular Rule (762001-3), Socket Wrench (782223-9)

Model XSL01Z Includes: Tool Only; Battery and Charger not included

Blade Diameter	7-1/2"
Arbor	5/8"
Max. Cutting Capacity (Bevel/Miter): 90°/90° (2-1/16" x 11-3/4"), 45°/45° (1" x 11-3/4")	
No Load Speed	2,200 RPM
Battery	18v LXT® Lithium-Ion
Dimensions (LxWxH)	25-3/4" x 17" x 17-7/8"
Net Weight (with battery)	27.5 lbs.
Shipping Weight	44 lbs.



XMT035

XMT035

18v LXT® MULTI-TOOL KIT
"Tool-less" Clamp System for Fast Accessory Installation

- 18v LXT® Lithium-Ion battery provides up to 20 minutes of continuous run time
- Variable speed control dial (6,000-20,000 OPM) enables user to match the speed to the application
- 3.2° oscillation angle engineered for faster, more aggressive cutting and sanding
- Large on/off slide switch with lock-on button for operator convenience

Model XMT035 Includes: (2) 18v LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18v Lithium-Ion Rapid Optimum Charger (DC18RC), 1-1/4" Plunge Blade (BiM) (A-95255), Multi-Tool Adapter (313249-6), Multi-Tool Adapter (313248-8), Tool Bag

Model XMT03Z Includes: Tool Only; Battery and Charger not included

Oscillations Per Minute	6,000 - 20,000 OPM
Oscillation Angle	3.2°
Battery	18v LXT® Lithium-Ion
Overall Length	13-3/8"
Net Weight (with battery)	4.9 lbs.
Shipping Weight	14.1 lbs.



XOB01

XOB01

18v LXT® 5" RANDOM ORBIT SANDER KIT
Corded Performance without the Cord

- Three speed settings (7,000/9,500/11,000 OPM) engineered for fast material removal
- Up to 40 minutes (low speed) and 20 minutes (high speed) of run time on a single charge
- Large 1/8" random orbit action engineered for fast sanding and swirl-free finish
- One-touch electronic speed control switch provides fast, medium and low settings
- Ergonomically designed body and grip for increased operator comfort

Model XOB01 Includes: (2) 18v LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18v Lithium-Ion Rapid Optimum Charger (DC18RC), Tool Bag

Model XOB01Z Includes: Tool Only; Battery and Charger not included

Pad Size (round)	4-7/8"
Abrasive Disc Size	5"
Orbits Per Minute (3 speed)	7,000, 9,500, 11,000 OPM
Orbit Diameter	1/8"
Battery	18v LXT® Lithium-Ion
Overall Length	6-7/8"
Net Weight (with battery)	3.6 lbs.
Shipping Weight	12 lbs.



XPK01

XPK01

18v LXT® 3-1/4" PLANER KIT
Planes Up to 3-1/4" Wide and 5/64" Deep in a Single Pass

- 2-blade cutter head with double edge carbide blades for added performance and smooth finish
- High power-to-weight ratio; weighs only 7.4 lbs.
- 14,000 RPM motor engineered for fast stock removal
- Click depth adjustment knob with easy-to-read scale with settings from 0" to 5/64"
- Spring-loaded stand elevates the base to protect the blades and workpiece

Model XPK01 Includes: (2) 18v LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18v Lithium-Ion Rapid Optimum Charger (DC18RC), 3-1/4" Planer Blade Set (D-46246), Blade Gauge (123062-2), Socket Wrench (782209-3), Tool Bag

Model XPK01Z Includes: Tool Only; Battery and Charger not included

Planing Width	3-1/4"
Planing Depth	5/64"
No Load Speed	14,000 RPM
Battery	18v LXT® Lithium-Ion
Overall Length	13-1/8"
Net Weight (with battery)	7.4 lbs.
Shipping Weight	16.3 lbs.



XJP03Z

18v LXT® PLATE JOINER
Delivers up to 300 Cuts for #0 Biscuits on a Single Charge

- Rack-and-pinion vertical fence system engineered for accurate fence adjustments
- Cast aluminum pivot fence with three positive stops at 0°, 45° and 90°, and easy centering on 3/4" material
- Six depth settings with one-touch stops for #0, #10, and #20 and most common biscuits sizes
- Cordless plate joiner provides portability and performance in the field or in the shop without the cord
- Large and easy-to-operate cam locks for fence adjustments

Model XJP03Z Includes: Tool Only; Battery and Charger not included

Blade Diameter	4"
Cutting Capacity (depth)	3/4"
No Load Speed	6,500 RPM
Battery	18v LXT® Lithium-Ion
Overall Length	13-3/4"
Net Weight (with battery)	6.7 lbs.
Shipping Weight	8.2 lbs.

LARGE & ACCURATE CUTS



CAPACITY

Cuts up to 8" crown molding (nested) and 6-1/2" baseboard (vertical)



VERSATILITY

5-1/2" tall fence system features upper and lower fence adjustments for more precise cuts



ACCURACY

6 linear ball bearings and 4-steel rail sliding system deliver maintenance-free "dead-on" accurate cuts



LS1216L

12" DUAL SLIDE COMPOUND MITER SAW

Cuts Up to 8" Crown Molding and 15" at 90°

- 4-Steel Rail Sliding System increases rigidity to produce superior cuts
- 6 linear ball bearings deliver adjustment-free "dead-on" accurate cuts
- 5-1/2" tall dual sliding fence system
- Independent laser indicates line-of-cut whether blade is turning or not
- Electronic speed control maintains constant speed

Model LS1216L Includes: 12" x 1" 60T Micro-Polished Miter Saw Blade (A-93712), Vertical Vise (122854-6), Dust Bag (122852-0), Triangular Rule (762001-3), Blade Wrench (783208-8), Socket Wrench (782232-8)

Blade Diameter	12"
Arbor	1"
Max. Cutting Capacities:	
at 90° (3-5/8" x 15"), at 45° L/R (3-5/8" x 10-1/2")	
No Load Speed	3,200 RPM
Dimensions (LxWxH)	31-3/4" x 25-1/4" x 28-3/8"
Net Weight	58.6 lbs.
Shipping Weight	74 lbs.



LS1216LX4

12" DUAL SLIDE COMPOUND MITER SAW

Cuts Up to 8" Crown Molding and 15" at 90°

- 4-Steel Rail Sliding System increases rigidity to produce superior cuts
- 6 linear ball bearings deliver adjustment-free "dead-on" accurate cuts
- Independent laser indicates line-of-cut whether blade is turning or not
- Includes a durable stand for easier job-site portability that features up to 9' material support extensions and adjustable leg supports

Model LS1216LX4 Includes: 12" x 1" 60T Micro-Polished Miter Saw Blade (A-93712), Vertical Vise (122854-6), Dust Bag (122852-0), Triangular Rule (762001-3), Straight Guide (164834-6), Socket Wrench (782232-8), Jobsite Miter Saw Stand (WST05)

Blade Diameter	12"
Arbor	1"
Max. Cutting Capacities:	
at 90° (3-5/8" x 15"), at 45° L/R (3-5/8" x 10-1/2")	
No Load Speed	3,200 RPM
Dimensions (LxWxH)	31-3/4" x 25-1/4" x 28-3/8"
Net Weight	116.2 lbs.
Shipping Weight	162 lbs.



LS1016

10" DUAL SLIDE COMPOUND MITER SAW

Largest Crown Molding Cutting Capacity in its Class

- 10" slide miter saw with the crown molding cutting capacity of a 12" saw
- Innovative direct drive gearbox and guard system is engineered for increased vertical cutting capacity (4-3/4")
- Exclusive 6 linear ball bearings engineered to deliver "dead-on" accurate cuts
- Capacity: 6-5/8" crown molding (nested), 4-3/4" baseboard (vertical)
- Compact design with a patented 4-Steel Rail Sliding System

Model LS1016 Includes: 10" x 5/8" 60T Micro-Polished Miter Saw Blade (A-93675), Vertical Vise (122854-6), Dust Bag (122852-0), Triangular Rule (762001-3), Socket Wrench (782232-8)

Blade Diameter	10"
Arbor	5/8"
Max. Cutting Capacities:	
at 90° (2-13/16" x 12"), at 45° L/R (2-13/16" x 8-1/2")	
No Load Speed	3,200 RPM
Dimensions (LxWxH)	28-1/4" x 25-1/4" x 26-1/2"
Net Weight	53.1 lbs.
Shipping Weight	66.85 lbs.



LS1016L

10" DUAL SLIDE COMPOUND MITER SAW

Largest Crown Molding Cutting Capacity in its Class

- 10" slide miter saw with the crown molding cutting capacity (6-5/8" vertically-nested) of a 12" saw
- Built-in laser clearly indicates line-of-cut whether blade is turning or not
- Compact design with a patented 4-Steel Rail Sliding System further increases rigidity to produce superior cuts
- Exclusive 6 linear ball bearings engineered to deliver "dead-on" accurate cuts

Model LS1016L Includes: 10" x 5/8" 60T Micro-Polished Miter Saw Blade (A-93675), Vertical Vise (122854-6), Dust Bag (122852-0), Triangular Rule (762001-3), Socket Wrench (782232-8)

Blade Diameter	10"
Arbor	5/8"
Max. Cutting Capacities:	
at 90° (2-13/16" x 12"), at 45° L/R (2-13/16" x 8-1/2")	
No Load Speed	3,200 RPM
Dimensions (LxWxH)	28-1/4" x 25-1/4" x 26-1/2"
Net Weight	53.3 lbs.
Shipping Weight	68.5 lbs.



LS1016LX5

10" DUAL SLIDE COMPOUND MITER SAW

Largest Crown Molding Cutting Capacity in its Class

- 10" slide miter saw with the crown molding cutting capacity (6-5/8" vertically-nested) of a 12" saw
- Built-in laser clearly indicates line-of-cut whether blade is turning or not
- Includes a durable stand for easier job-site portability that features up to 9' material support extensions and adjustable leg supports
- Exclusive 6 linear ball bearings engineered to deliver "dead-on" accurate cuts

Model LS1016LX5 Includes: Jobsite Miter Saw Stand (WST05), 10" x 5/8" 60T Micro-Polished Miter Saw Blade (A-93675), Vertical Vise (122854-6), Dust Bag (122852-0), Triangular Rule (762001-3), Socket Wrench (782232-8)

Blade Diameter	10"
Arbor	5/8"
Max. Cutting Capacities:	
at 90° (2-13/16" x 12"), at 45° L/R (2-13/16" x 8-1/2")	
No Load Speed	3,200 RPM
Dimensions (LxWxH)	28-1/4" x 25-1/4" x 26-1/2"
Net Weight	110.2 lbs.
Shipping Weight	135 lbs.



LS1018

10" DUAL SLIDE COMPOUND MITER SAW

Large Cutting Capacity in a Compact Design and Less Weight

- Powerful 13.0 AMP direct drive motor requires less maintenance and delivers 4,300 RPM
- Meters 0° - 47° left and 0° - 60° right, with positive stops at 0°, 15°, 22.5°, 31.6°, 45° (left and right)
- Linear ball bearing system engineered to deliver "dead-on" accurate cuts
- Less weight (43.7 lbs.) and compact design for job site portability

Model LS1018 Includes: 10" 40T Miter Saw Blade (JM23000176), Triangle Rule for Miter Saws (JM27000328), Vice Assembly, LS1018 (JM23100502), Dust Bag Assembly, LS1018 (JM23100501), Extension Wing, LS1018 (JM23100500), Wrench 13 (782230-2)

Blade Diameter	10"
Arbor	5/8"
Max. Cutting Capacities:	
at 90° (3-5/8" x 12"), at 45° L/R (3-5/8" x 8-1/2")	
No Load Speed	4,300 RPM
Dimensions (LxWxH)	21-1/8" x 32-1/2" x 25"
Net Weight	43.7 lbs.
Shipping Weight	51.7 lbs.

PORTABLE & POWERFUL



NEW XSL02Z Tool only - battery and charger not included

18v X2 LXT® BRUSHLESS 7-1/2" COMPOUND MITER SAW
 Powerful BL™ Brushless Motor Delivers 5,700 RPM for Faster Cutting

- Two 18V LXT® Lithium-Ion Batteries deliver the power and performance of a corded miter saw without leaving the 18V LXT® platform
- Automatic Speed Change™ technology adjusts cutting speed and torque during cut for optimum performance
- The BL™ Brushless Motor eliminates carbon brushes, enabling the BL Motor to run cooler and more efficiently for longer life
- Efficient BL™ Brushless motor is electronically controlled to optimize battery energy use for up to 50% longer run time per charge

Model XSL02Z Includes: 7-1/2" 40T C.T. Miter Saw Blade (A-90912); Battery and Charger not included

Blade Diameter	7-1/2"
Arbor	5/8"
Max. Cutting Capacity (Bevel/Miter): 90°/90° (2-1/16" x 11-3/4"), 45°/45° (2-1/16" x 8-3/8")	
No Load Speed	5,700 RPM
Battery	2X 18V LXT® Lithium-Ion
Dimensions (LxWxH)	25-3/4" x 17" x 17-1/2"
Net Weight (with battery)	28.9 lbs.
Shipping Weight	38 lbs.



XSL01 3.0Ah BATTERY

18v LXT® 7-1/2" COMPOUND MITER SAW KIT
 Large Cutting Capacity up to 2-1/16" and 11-3/4" Crosscuts at 90°

- Powerful Makita-built motor delivers 2,200 RPM
- Weights only 27.5 lbs. with battery for reduced operator fatigue
- Four steel rail sliding system increases rigidity to produce superior accurate cuts
- Miters 0-47° left and 0-57° right; bevels 0-45° left and 0-5° right

Model XSL01 Includes: (2) 18V LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18V Lithium-Ion Rapid Optimum Charger (DC18RC), 7-1/2" 40T C.T. Miter Saw Blade (A-90912), (2) Extension Wing (322312-4), Vertical Vise (122571-8), Dust Bag (122852-0), Triangular Rule (762001-3), Socket Wrench (782223-9)

Model XSL012 Includes: Tool Only; Battery and Charger not included

Blade Diameter	7-1/2"
Arbor	5/8"
Max. Cutting Capacity (Bevel/Miter): 90°/90° (2-9/16" x 11-3/4"), 45°/45° (1" x 11-3/4")	
No Load Speed	2,200 RPM
Battery	18V LXT® Lithium-Ion
Dimensions (LxWxH)	25-3/4" x 17" x 17-7/8"
Net Weight (with battery)	27.5 lbs.
Shipping Weight	44 lbs.



LS0815F

8-1/2" SLIDE COMPOUND MITER SAW
 Compact and Lightweight Design for Job Site Portability

- Powerful 10.5 AMP direct drive motor requires less maintenance and delivers 5,000 RPM
- Cuts up to 12" at 90° and 8-1/2" at 45°
- Miters 0°- 50° left and 0°- 60° right, with positive stops at 0°, 15°, 22.5°, 31.6°, 45° (right or left)
- Compact and lightweight (31.1 lbs.) for job site portability

Model LS0815F Includes: 8-1/2" 48T Carbide-Tipped Miter Saw Blade (A-95934), Triangle Rule for Miter Saws (JM27000328), Vertical Vise, LS0815F (JM23510009), Dust Bag, LS0815F (JM23510010), Box Wrench, LS0815F (782230-2), (2) Extension Wing (JM23000127)

Blade Diameter	8-1/2"
Arbor	5/8"
Max. Cutting Capacities: at 90° (2-9/16" x 12"), at 45° L/R (2-9/16" x 8-1/2")	
No Load Speed	5,000 RPM
Dimensions (LxWxH)	29-3/4" x 17-3/4" x 19-1/4"
Net Weight	31.1 lbs.
Shipping Weight	41.8 lbs.



LS1221

12" COMPOUND MITER SAW
 Consistently Precise Cutting Performance

- Large cutting capacity (3-7/8" x 6" at 90°)
- 4-1/2" tall pivoting fence for cutting up to 5-1/2" crown molding
- Powerful 15 AMP direct drive motor delivers 4,000 RPM for smooth performance
- Positive stops at 9 settings; 15°, 22.5°, 31.6°, 45° right or left and 0°
- Horizontal D-handle design for easy and comfortable operation
- Electric brake for maximum productivity

Model LS1221 Includes: 12" x 1" 40T Micro-Polished Miter Saw Blade (A-93706), Vertical Vise (122540-9), Extension Wing (323726-0), Socket Wrench (782232-8), Dust Bag (122852-0)

Blade Diameter	12"
Arbor	5/8"
Max. Cutting Capacities: at 90° (3-7/8" x 6"), at 45° L/R (2-3/4" x 5-7/8")	
No Load Speed	4,000 RPM
Dimensions (LxWxH)	24" x 26-1/2" x 23-7/8"
Net Weight	37 lbs.
Shipping Weight	50 lbs.



LS1040

10" COMPOUND MITER SAW
 Pivoting Fence for Supporting Larger Material

- Powerful 15 AMP direct drive motor for improved performance
- Dual post compound pivoting arm; bevel cuts up to 45° to the left
- Weights only 24.2 lbs. for easy portability
- Positive stops at 9 settings; 15°, 22.5°, 30°, 45° right or left & 0° (90° cuts)
- Miter cuts 0 - 45° left and 0 - 52° right

Model LS1040 Includes: 10" x 5/8" 40T Micro-Polished Miter Saw Blade (A-93669), Dust Bag (122852-0), Triangular Rule (762001-3), Vertical Vise (122536-0), Socket Wrench (782232-8)

Blade Diameter	10"
Arbor	5/8"
Max. Cutting Capacities: at 90° (2-3/4" x 5-1/8"), at 45° L/R (1-3/8" x 3-5/8")	
No Load Speed	4,600 RPM
Dimensions (LxWxH)	20-7/8" x 18-3/4" x 21"
Net Weight	27.3 lbs.
Shipping Weight	28 lbs.

Jobsite Miter Saw Stands

Fits All Makita® Miter Saws



WST05

Large Solid Rubber Wheels for Easier Jobsite Portability

- Material support extensions (extend 9") with adjustable leg supports for increased cutting accuracy
- Spring-loaded mechanism engineered for quick and easy jobsite set up
- Durable duty aluminum feed roller and adjustable material stop engineered for increased speed on repetitive cuts
- Compact design (46" folded) for convenient transportation to and from the jobsite, and easy vertical or horizontal storage
- 2-Position adjustable stand provides additional height set up for increased comfort
- Adjustable non-marring rubberized feet provide additional support when leveling stand on uneven surfaces

Material Support Extensions	9"
Spring Loading Mechanism	Yes
In-Feed Roller	Yes
Material Stop	Yes
Folded Dimensions (W)	46"
Dimensions (LxWxH)	46" x 19-3/4" x 15-3/4"
Net Weight	58.0 lbs.
Shipping Weight	66.0 lbs.



195083-4

Ideal for Jobsite Use

- Large platform base for additional work space
- 5-position adjustable stand fits different height requirements
- Material support extensions (extends 9") with feed roller deliver enhanced convenience and work speed
- Solid rubber 12" wheels for easy portability, job to job
- Spring loaded mechanism for quick and easy setups

Extends to 9ft.

Material Support Extensions	9"
Spring Loading Mechanism	Yes
In-Feed Roller	Yes
Material Stop	Yes
Folded Dimensions (W)	50-1/2"
Dimensions (LxWxH)	50-1/2" x 21-1/2" x 15-3/4"
Net Weight	79.0 lbs.
Shipping Weight	90.7 lbs.