



INCLUDES
(1) Hex Wrench
(1) Hammer Cart
(2) Flat Chisels
(2) Bull Points

NEW HM1812X3

70 lb. ADVANCED AVT® BREAKER HAMMER
Hits Like Air Without the Vibration

- Efficient 15 AMP motor with improved hammer mechanism delivers 53.9 ft.lbs./72.8 joules of impact energy
- Advanced AVT® is a mechanical counterbalance, vibration absorbing housing and rubberized fixed handles designed to more effectively reduce vibration
- Soft start is designed to suppress start-up reaction for greater accuracy on start up
- L.E.D. light indicates electrical failure or notifies the user approximately 8 hours before brushes need to be replaced

Model HM1812X3 Includes: Hex Wrench (783203-B), Premium Hammer Cart (T-02892), (2) 1-1/8" x 20-1/2" Flat Chisel, 1-1/8" Hex (D-21369), (2) 16" Self Sharpening Bull Point, 1-1/8" Hex (B-45559)

Blows Per Minute	870 BPM
Impact Energy	53.9 ft.lbs. / 72.8 J
AMPS	15
Noise Level	106 dB
Vibration (m/s²)	6.5
Cord Length (ft)	16.4'
Overall Length	33-1/4"
Net Weight	69.1 lbs.
Shipping Weight	140 lbs.
Bit Type	1-1/8" Hex



INCLUDES
(1) Hex Wrench
(1) Hammer Cart
(2) Flat Chisels
(2) Bull Points

HM1810X3

70 lb. AVT® BREAKER HAMMER
Anti-Vibration Technology for 2X Less Vibration

- Efficient 15 AMP motor with improved hammer mechanism delivers 46.5 ft.lbs. of impact energy
- Anti-Vibration Technology is an internal counterbalance system that greatly reduces vibration
- Fixed movement handles for more control and better accuracy
- AC/DC switch for use with alternative power source
- L.E.D. power light indicates switch failure or cord damage

Model HM1810X3 Includes: Hex Wrench (783203-B), Premium Hammer Cart (T-02892), (2) 1-1/8" x 20-1/2" Flat Chisel, 1-1/8" Hex (D-21369), (2) 20-1/2" Bull Point, 1-1/8" Hex (D-21353)

Blows Per Minute	1,100 BPM
Impact Energy	46.5 ft.lbs. / 63 J
AMPS	15
Noise Level	107 dB
Vibration (m/s²)	9
Cord Length (ft)	16.4'
Overall Length	32-1/2"
Net Weight	71.3 lbs.
Shipping Weight	141.3 lbs.
Bit Type	1-1/8" Hex



AVT®
Anti Vibration Technology

HM1317CB

42 lb. AVT® DEMOLITION HAMMER
Anti-Vibration Technology for 2X Less Vibration

- Powerful 14 AMP motor delivers 25.7 ft.lbs. of impact energy to handle the most demanding applications
- Variable speed control dial enables user to match the speed to the application for greater versatility
- L.E.D. service light notifies the user approximately 8 hours before the brushes need to be replaced
- L.E.D. power light indicates switch failure or cord damage
- Rubberized ergonomic soft grip provides more comfort

Model HM1317CB Includes: 20-1/2" Bull Point, 1-1/8" Hex (D-21353), Tool Case w/Wheels

Blows Per Minute (variable speed)	730 - 1,450 BPM
Impact Energy	25.7 / 34.9 J
AMPS	14
Noise Level	101 dB
Vibration (m/s²)	7
Cord Length (ft)	16.4'
Overall Length	32-1/2"
Net Weight	41.9 lbs.
Shipping Weight	60.39 lbs.
Bit Type	1-1/8" Hex



HM1500B

42 lb. DEMOLITION HAMMER
Rugged All Metal Housing for Longer Tool Life

- Powerful 13.5 AMP motor delivers 18.4 ft.lbs. of impact energy
- Pneumatic compression system automatically adjusts air in the cylinder to minimize power loss and deliver unmatched power-to-weight ratio
- "Soft no-load" function automatically reduces the speed of the motor when idling
- Makita Motor Advantage engineered for more power and longer tool life
- Automatic brush cut-off protects commutator from damage for longer tool life

Model HM1500B Includes: Steel Tool Case

Blows Per Minute	1,300 BPM
Impact Energy	18.4 / 25 J
AMPS	13.5
Noise Level	101 dB
Vibration (m/s²)	26
Cord Length (ft)	17"
Overall Length	31-3/4"
Net Weight	44.1 lbs.
Shipping Weight	66.7 lbs.
Bit Type	1-1/8" Hex



AVT®
Anti Vibration Technology

HM1307CB

35 lb. DEMOLITION HAMMER
Electronic Controller for Operator Convenience

- Powerful 14 AMP motor delivers 25.7 lbs. of impact energy to handle the most demanding applications
- Constant Speed Control automatically applies additional power to the motor to maintain consistent speed under load for the most challenging jobs
- Soft Start suppresses start-up reaction for smoother start-ups and better accuracy
- L.E.D. Service Light notifies the user approximately 8 hours before the brushes need to be replaced
- L.E.D. Power Lights indicate switch failure or cord damage

Model HM1307CB Includes: 20-1/2" Bull Point, 1-1/8" Hex (D-21353), Tool Case

Blows Per Minute (variable speed)	730 - 1,450 BPM
Impact Energy	25.7 / 34.9 J
AMPS	14
Noise Level	101 dB
Vibration (m/s²)	12
Overall Length	32-1/2"
Net Weight	38.2 lbs.
Shipping Weight	56.422 lbs.
Bit Type	1-1/8" Hex



HM1214C

27 lb. AVT® DEMOLITION HAMMER
Anti-Vibration Technology for 2X Less Vibration

- Powerful 14 AMP motor delivers 19 ft.lbs. of impact energy to handle the most demanding applications
- Anti-Vibration Technology is an internal counterbalance system that greatly reduces vibration
- Constant speed control automatically applies additional power to the motor to maintain speed under load
- Soft start suppresses start-up reaction for more precision and better accuracy

Model HM1214C Includes: Side Handle (135283-4), 12" Bull Point, SDS-MAX (751423-A), Hammer Bit Grease (194683-7), Tool Case

Blows Per Minute (variable speed)	950 - 1,900 BPM
Impact Energy	19 / 25.7 J
AMPS	14
Noise Level	101 dB
Vibration (m/s²)	8
Overall Length	27-1/2"
Net Weight	27.1 lbs.
Shipping Weight	46.284 lbs.
Bit Type	Accepts SDS-MAX



HM1203C

20 lb. DEMOLITION HAMMER
Compact Power with Less Weight

- Powerful 14 AMP motor delivers 18.8 ft.lbs. of impact energy to handle the most demanding applications
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- Variable speed control dial enables user to match the speed to the application for greater versatility
- Soft start suppresses start-up reaction for precision and better accuracy
- L.E.D. service light notifies the user approximately 8 hours before the brushes need to be replaced

Model HM1203C Includes: Side Handle (135283-4), 12" Bull Point, SDS-MAX (751423-A), Hammer Bit Grease (194683-7), Tool Case

Blows Per Minute (variable speed)	950 - 1,900 BPM
Impact Energy	18.8 / 25.5 J
AMPS	14
Noise Level	95 dB
Vibration (m/s²)	15.5
Overall Length	22-3/4"
Net Weight	20.3 lbs.
Shipping Weight	36 lbs.
Bit Type	Accepts SDS-MAX



HM1211B

20 lb. DEMOLITION HAMMER
Air Cushion Design for Powerful Performance

- Powerful 10 AMP motor for fast and efficient operation
- Comfortable rubber D-shaped grip side handle absorbs vibration; secures in four positions for operator comfort
- One-touch latch bit retainer for quick bit changes
- Automatic brush cut-off protects commutator from damage for longer tool life
- Factory grease packed for reduced maintenance
- AC/DC switch for use with alternative power source

Model HM1211B Includes: Hex Wrench (783202-0), Tool Case

Blows Per Minute	2,000 BPM
Impact Energy	10.5 ft.lbs. / 14.2 J
AMPS	10
Overall Length	19-5/16"
Net Weight	20.7 lbs.
Shipping Weight	33 lbs.
Bit Type	3/4" Hex - 21/32" Round



HM1111C

17 lb. AVT® DEMOLITION HAMMER
Anti-Vibration Technology for
2X Less Vibration

- Powerful 14 AMP motor delivers 12.7 ft.lbs. of impact energy to handle the most demanding applications
- Anti-Vibration Technology is an internal counterbalance system that greatly reduces vibration for increased user comfort and greater productivity
- Detached rear handle is spring loaded to provide less vibration and more control
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs

Model HM1111C Includes: Side Handle (151769-0), Hammer Bit Grease (194683-7), CLOTH F/WIPING OIL (443122-7), 12" Bull Point, SDS-MAX (751423-A), Tool Case

Blows Per Minute (variable speed)	1,100 - 2,650 BPM
Impact Energy	12.7 ft.lbs. / 17.2 J
AMPS	14
Vibration (m/s ²)	8
Overall Length	20-3/4"
Net Weight	17.7 lbs.
Shipping Weight	28.6 lbs.
Bit Type	Accepts SDS-MAX



HM0870C

11 lb. DEMOLITION HAMMER
Compact Power with Less Weight

- Powerful 10 AMP motor delivers 8.4 ft.lbs. of impact energy to handle the most demanding applications
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- Soft start suppresses start-up reaction for better accuracy
- L.E.D. service light notifies the user approximately 8 hours before the brushes need to be replaced
- L.E.D. power light indicates switch failure or cord damage
- Variable speed control dial enables user to match the speed to the application for greater versatility

Model HM0870C Includes: Side Handle (135283-4), Hammer Bit Grease (194683-7), Tool Case

Blows Per Minute (variable speed)	1,100 - 2,650 BPM
Impact Energy	8.4 ft.lbs. / 11.4 J
AMPS	10
Vibration (m/s ²)	11
Overall Length	17-3/4"
Net Weight	11.1 lbs.
Shipping Weight	18.5 lbs.
Bit Type	Accepts SDS-MAX



HM0810B

11 lb. DEMOLITION HAMMER
Ideal for Light Chiseling, Chipping
and Scaling

- Compact with less weight for improved control
- Soft rubber grip side handle minimizes vibration and swivels 360° for operator convenience
- Innovative anti-vibration spring is positioned between tool body and rear handle for reduced operator fatigue
- One-touch tool retainer action for easy accessory installation and removal
- Makita Motor Advantage engineered for more power and longer tool life
- Extended life brushes are longer for more work between service intervals and less downtime

Model HM0810B Includes: Hex Wrench (783202-0), Tool Case

Blows Per Minute	2,900 BPM
Impact Energy	5.6 ft.lbs. / 7.6 J
AMPS	8.3
Vibration (m/s ²)	8
Overall Length	16-5/8"
Net Weight	12.8 lbs.
Shipping Weight	19.4 lbs.
Bit Type	3/4" Hex - 21/32" Round



HK1810

POWER SCRAPER
Versatile Tool for Scraping and
Tile Removal

- Air cushion hammering for longer tool life
- Quick change bit retainer for easy changes
- Automatic brush cut-off protects commutator from damage
- Factory grease packed for reduced maintenance
- All-ball bearing construction for longer tool life
- Accepts Makita Small bits

Model HK1810 Includes: 1-3/16" x 6" Scaling Chisel, Makita Small Shank (B-07331), 2" x 6" Scaling Chisel, Makita Small Shank (B-07347), 8-3/4" Bull Point, Makita Small Shank (B-06921), Dust Cover (423154-0), Tool Case

Blows Per Minute (variable speed)	0 - 3,200 BPM
Impact Energy	2.9 ft.lbs. / 3.9 J
AMPS	4.5
Vibration (m/s ²)	13.5
Overall Length	12-3/8"
Net Weight	7.1 lbs.
Shipping Weight	13.7 lbs.
Bit Type	Makita small

ROTARY HAMMERS



HR5212C

2" ADVANCED AVT® ROTARY HAMMER
Advanced Anti-Vibration Technology
for Significantly Less Vibration

- Powerful 15 AMP motor delivers 14 ft.lbs. / 19 J. of impact energy
- Advanced AVT® is an air actuated counterbalance, vibration absorbing housing and impact bolt damper spring that more effectively reduces vibration
- Electronic Controller is a feature package that provides constant speed control, soft start, soft no-load and variable speed

Model HR5212C Includes: Depth Rod, HR4013C (331955-1), Hammer Bit Grease (194683-7), Cloth F/Wiping Oil (443122-7), D-handle (417003-1), Straight Handle (454781-2) (454781-2), Straight Handle Assembly (135629-4) (135629-4), Accessory Case

AMPS	15
Capacities: Concrete Drilling	2"
Concrete Drilling w/ Core Bit	6-1/4"
Impact Energy	19 J / 14 ft.lbs.
Vibration (m/s ²)	9
Blows Per Minute (variable speed)	1,100 - 2,250 BPM
No Load Speed (variable speed)	130 - 260 RPM
Overall Length	23-1/2"
Cord Length (ft)	16.4'
Net Weight	26.2 lbs.
Shipping Weight	42 lbs.
Bit Type	Accepts SDS-MAX



HR4510C

1-3/4" AVT® ROTARY HAMMER
Anti-Vibration Technology for
2X Less Vibration

- Powerful 13.5 AMP motor delivers 9.2 ft.lbs. of impact energy to handle the most demanding applications
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- Soft start suppresses start-up reaction for increased accuracy
- L.E.D. service light notifies the user approximately 8 hours before the brushes need to be replaced
- L.E.D. power lights indicate switch failure or cord damage

Model HR4510C Includes: Side Handle (151769-0), D-handle (417003-1), Depth Gauge (321248-4), Hammer Bit Grease (194683-7), Tool Case

AMPS	13.5
Capacities: Concrete Drilling	1-3/4"
Concrete Drilling w/ Core Bit	5"
Impact Energy	12.5 J / 9.2 ft.lbs.
Vibration (m/s ²)	9.5
Blows Per Minute (variable speed)	1,250 - 2,750 BPM
No Load Speed (variable speed)	130 - 280 RPM
Overall Length	18"
Cord Length (ft)	16.4'
Net Weight	19.6 lbs.
Shipping Weight	35 lbs.
Bit Type	Accepts SDS-MAX



HR4013C

1-9/16" ADVANCED AVT® ROTARY HAMMER
Advanced Anti-Vibration Technology
for Significantly Less Vibration

- Powerful 11 AMP motor delivers 8.4 ft.lbs. / 11.4 J. of impact energy to handle the most demanding applications
- Advanced AVT® is an air actuated counterbalance, vibration absorbing housing and impact bolt damper spring that more effectively reduces vibration
- Electronic Controller is a feature package that provides constant speed control, soft start, soft no-load and variable speed

Model HR4013C Includes: D-Handle Assembly, HR4013C (196792-8), Depth Rod, HR4013C (331955-1), Side Handle Assembly (123138-5), Hammer Bit Grease (194683-7), Cloth F/Wiping Oil (443122-7), Accessory Case

AMPS	11
Capacities: Concrete Drilling	1-9/16"
Concrete Drilling w/ Core Bit	4-1/8"
Impact Energy	11.4 J / 8.4 ft.lbs.
Vibration (m/s ²)	5
Blows Per Minute (variable speed)	1,450 - 2,900 BPM
No Load Speed (variable speed)	250 - 500 RPM
Overall Length	18-11/16"
Cord Length (ft)	15.6'
Net Weight	15.1 lbs.
Shipping Weight	27.8 lbs.
Bit Type	Accepts SDS-MAX



HR4002

1-9/16" ROTARY HAMMER
Sequential Impact Timing for Up to
50% Faster Drilling

- Powerful 10 AMP motor delivers 4.6 ft.lbs. of impact energy
- 2-mode operation for "Hammering Only" or "Hammering with Rotation"
- Rubberized ergonomic soft grip provides more comfort
- "No hammering when idling" functions helps increase tool life
- One-touch sliding chuck for quick bit changes
- Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears if the bit binds

Model HR4002 Includes: Side Handle (158131-0), Depth Gauge (321248-4), Hammer Bit Grease (194683-7), Tool Case

AMPS	10
Capacities: Concrete Drilling	1-9/16"
Concrete Drilling w/ Core Bit	4-1/8"
Impact Energy	6.2 J / 4.6 ft.lbs.
Vibration (m/s ²)	17.5
Blows Per Minute	2,500 BPM
No Load Speed	680 RPM
Overall Length	18"
Cord Length (ft)	9.8'
Net Weight	14.6 lbs.
Shipping Weight	26.89 lbs.
Bit Type	Accepts SDS-MAX



HR5000



2" ROTARY HAMMER Air Cushion Design for Hard Hitting Action

- All ball-and-needle bearing construction for longer tool life
- Powerful 11 AMP motor for the most demanding applications
- Built-in clutch reduces gear damage by disengaging gears if the bit binds
- 2-mode operation for "Hammering Only" or "Hammering with Rotation" for multiple applications
- Sequential impact timing delivers timed hammering during rotation to minimize overlapping bit impacts resulting in up to 50% faster drilling

Model HR5000 Includes: Hex Wrench (783202-0), Hex Wrench (783203-8), Wrench (783204-6), Tool Case

HR4041C



1-9/16" ROTARY HAMMER Electronic Controller for Operator Convenience

- Powerful 12 AMP motor delivers 6.8 ft.lbs. of impact energy
- Constant speed control automatically applies additional power to the motor to maintain speed under load
- Soft start suppresses start-up reaction for increased accuracy
- Variable speed control dial enables user to match the speed to the application
- "No hammering while idling" helps increase tool life.
- Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears

Model HR4041C Includes: Depth Gauge (321248-4), Side Handle (416549-4), Tool Case



HR3210C



1-1/4" AVT® ROTARY HAMMER Anti-Vibration Technology for 2X Less Vibration

- Powerful 8.2 AMP motor delivers 4.7 ft.lbs. of impact energy
- Constant speed control automatically applies additional power to the motor to maintain speed under load
- Soft start suppresses start-up reaction for more precision and better accuracy
- L.E.D. service light notifies the user approximately 8 hours before the brushes need to be replaced
- L.E.D. power light indicates switch failure or cord damage

Model HR3210C Includes: Side Handle (151769-0), Depth Gauge (321248-4), Hammer Bit Grease (194683-7), Tool Case

HR2811F



1-1/8" ROTARY HAMMER Torque Limiting Clutch Engineered to Prevent Gear Damage

- Powerful 7.0 AMP motor delivers 2.1 ft.lbs. of impact energy
- L.E.D. light illuminates drilling surface for more productivity in low light applications
- 3-mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only"
- "No hammering when idling" function helps increase tool life
- Ergonomic "D-shaped" handle with rubberized soft grip for increased comfort

Model HR2811F Includes: Depth Gauge (324219-0), Side Handle (154842-5), Tool Case

AMPS	11
Capacities: Concrete Drilling	2"
Concrete Drilling w/ Core Bit	5-7/8"
Impact Energy	11.8 J / 8.7 ft.lbs.
Vibration (m/s ²)	25
Blows Per Minute	2,100 BPM
No Load Speed	260 RPM
Overall Length	18-3/4"
Cord Length (ft)	8.2'
Net Weight	21.8 lbs.
Shipping Weight	35 lbs.
Bit Type	Accepts Spline shank

AMPS	12
Capacities: Concrete Drilling	1-9/16"
Concrete Drilling w/ Core Bit	4-5/8"
Impact Energy	9.2 J / 6.8 ft.lbs.
Vibration (m/s ²)	15
Blows Per Minute (variable speed)	1,300 - 2,600 BPM
No Load Speed (variable speed)	230 - 460 RPM
Overall Length	16-7/8"
Cord Length (ft)	16.4'
Net Weight	14.8 lbs.
Shipping Weight	20.3 lbs.
Bit Type	Accepts Spline shank

AMPS	8.2
Capacities: Concrete Drilling	1-1/4"
Concrete Drilling w/ Core Bit	3-1/2"
Impact Energy	5.5 J / 4.1 ft.lbs.
Vibration (m/s ²)	10
Blows Per Minute (variable speed)	1,650 - 3,300 BPM
No Load Speed (variable speed)	315 - 630 RPM
Overall Length	15-5/8"
Cord Length (ft)	16.4'
Net Weight	11.4 lbs.
Shipping Weight	19.84 lbs.
Bit Type	Accepts SDS-PLUS

AMPS	7
Capacities: Concrete Drilling	1-1/8"
Concrete Drilling w/ Core Bit	3-1/8"
Impact Energy	2.9 J / 2.1
Vibration (m/s ²)	15
Blows Per Minute (variable speed)	0 - 4,500 BPM
No Load Speed (variable speed)	0 - 1,100 RPM
Overall Length	12-5/8"
Cord Length (ft)	8.2'
Net Weight	7.7 lbs.
Shipping Weight	11.8 lbs.
Bit Type	Accepts SDS-PLUS



HR2641



1" AVT® ROTARY HAMMER Anti-Vibration Technology for 2X Less Vibration

- Powerful 8 AMP motor delivers 2.1 ft.lbs./2.9 J. of impact energy
- Anti-Vibration Technology (AVT®) is an internal counterbalance system and impact bolt damper spring that greatly reduces vibration
- Torque limiting clutch engineered to prevent gear damage
- Recessed 3-mode function selector is located below gear housing for improved durability
- Retractable tool hook secures the tool when not in use

Model HR2641 Includes: Handle, LXF01CW (451749-9), Depth Gauge, HR2611F, HR2621 (331886-4), Tool Case

HR2475



1" ROTARY HAMMER Torque Limiting Clutch Engineered to Prevent Gear Damage

- Powerful 7.0 AMP motor delivers 2 ft.lbs. of impact energy
- 3-mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only"
- Variable speed trigger enables user to match the speed to the application for greater versatility
- Ergonomic "D-shaped" handle with rubberized soft grip for increased comfort
- One-touch sliding chuck for quick bit changes

Model HR2475 Includes: Side Handle (158057-6), Depth Gauge (324219-0), Tool Case

HR2611F



1" AVT® ROTARY HAMMER, ACCEPTS SDS-PLUS Anti-Vibration Technology for 2X Less Vibration

- Powerful 7 AMP motor delivers 2.1 ft.lbs. of impact energy to handle the most demanding applications
- Anti-Vibration Technology (AVT®) is an internal counterbalance system that greatly reduces vibration
- Integrated damper spring at the base of the impact bolt is engineered to absorb impact vibrations from the drill bit
- L.E.D. light illuminates drilling surface for more productivity in low light applications
- Recessed hammer function selector located below gear housing for improved durability

Model HR2611F Includes: Handle, LXF01CW (451749-9), Depth Gauge, HR2611F, HR2621 (331886-4), Tool Case

HR1830F



11/16" ROTARY HAMMER Compact with Less Weight (4.2 lbs.)

- Powerful 4.2 AMP motor delivers .9 ft.lbs. of impact energy
- L.E.D. light illuminates drilling surface for more productivity in low light applications
- Torque limiting clutch engineered to prevent gear damage
- 2-mode operation for "Rotation Only", "Hammering with Rotation"
- One-touch sliding chuck for quick bit changes

Model HR1830F Includes: Depth Gauge (415486-9), Side Handle (154842-5), Tool Case

AMPS	8
Capacities: Concrete Drilling	1"
Concrete Drilling w/ Core Bit	3-1/8"
Impact Energy	2.9 J / 2.1 ft.lbs.
Vibration (m/s ²)	11.5
Blows Per Minute (variable speed)	0 - 4,500 BPM
No Load Speed (variable speed)	0 - 1,100 RPM
Overall Length	16-5/8"
Cord Length (ft)	13.1'
Net Weight	7.1 lbs.
Shipping Weight	11.55 lbs.
Bit Type	Accepts SDS-PLUS

AMPS	7
Capacities: Concrete Drilling	1"
Concrete Drilling w/ Core Bit	3-1/8"
Impact Energy	2.7 J / 2
Vibration (m/s ²)	15.5
Blows Per Minute (variable speed)	0 - 4,500 BPM
No Load Speed (variable speed)	0 - 1,100 RPM
Overall Length	16-7/8"
Cord Length (ft)	13.1'
Net Weight	6.6 lbs.
Shipping Weight	11.9 lbs.
Bit Type	Accepts SDS-PLUS

AMPS	7
Capacities: Concrete Drilling	1"
Concrete Drilling w/ Core Bit	2-11/16"
Impact Energy	2.9 J / 2.1 ft.lbs.
Vibration (m/s ²)	11.5
Blows Per Minute (variable speed)	0 - 4,600 BPM
No Load Speed (variable speed)	0 - 1,200 RPM
Overall Length	15-1/8"
Cord Length (ft)	13.1'
Net Weight	6.6 lbs.
Shipping Weight	11.7 lbs.
Bit Type	Accepts SDS-PLUS

AMPS	4.2
Capacities: Concrete Drilling	11/16"
Concrete Drilling w/ Core Bit	
Impact Energy	1.2 J, .9 ft.lbs.
Vibration (m/s ²)	14
Blows Per Minute (variable speed)	0 - 5,000 BPM
No Load Speed (variable speed)	0 - 1,500 RPM
Overall Length	10-7/8"
Cord Length (ft)	8.2'
Net Weight	4.2 lbs.
Shipping Weight	11 lbs.
Bit Type	Accepts SDS-PLUS

1-1/8" Hex Shank Dust Extracting Attachment

MAXIMUM EXTRACTION

Durable Construction for use on the Most Demanding Jobsites

Applications



Attaches to 1-1/8" demo bit 1" to 4" from the surface being demolished for efficient dust extraction

Convenience



Convenient hose holders keep the hose out of the way during use



197172-1

1-1/8" HEX SHANK DUST EXTRACTING ATTACHMENT

- Large opening allows for maximum dust extraction
- Durable plastic construction for long life
- Includes hose and hose holders
- For use with demolition hammers that utilize 1-1/8" hex shank bits

Premium Hammer Cart

CONVENIENT TRANSPORTATION


Conveniently Transports Breaker Hammers and Bits on the Jobsite

Capacity



Bit retainers firmly hold up to (4) 1-1/8" demolition steel bits

Convenience



Stair climber rails for convenient lifting up stairs, curbs, truck beds, and other elevated surfaces

Durability



Rugged 9" semi-pneumatic wheels roll smoothly through rough jobsite terrain

Control



Adjustable strap keeps hammer securely fastened to the cart during transportation

T-02892

PREMIUM HAMMER CART

- For use with 1-1/8" hex shank Breaker and Demolition Hammers (HM1307CB, HM1317CB, HM1500B, HM1810, HM1812)
- Ball bearing hubs allow the wheels to rotate quickly and smoothly
- Corrosion resistant coating adds a layer of protection against harsh elements
- High-quality steel for long life



Hammer Bit Grease

Description	Size	Part #
For greasing the shanks of bits before installing them in the hammer	100ml	194683-7

Hammer Grease

Description	Model	Part #
30 cc used to lubricate grease reservoir	All Hammers	A-90582

Oil Supply

Description	Model	Part #
Oil Supply 100 cc	HM1301	181118-7

Blow-Out Bulb

Description	Model	Part #
Blows chips and dust from drilled holes before setting anchor fasteners	All Hammers	765009-6

*For use with all brands and types of bits for rotary and demolition hammers