




## TW0350

## 1/2" IMPACT WRENCH W/ DETENT PIN ANVIL

Max Torque of 258 ft.lbs.

- Powerful 3.5 AMP motor delivers 2,000 RPM/IPM for heavy duty applications
- · Efficient impact system with less vibration
- · Externally accessible brushes for easy replacement
- · Precision gearing with ball and needle bearing construction for efficient power transmission
- · Compact and lightweight (6.6 lbs.) for use in close quarters
- · Impact resistant aluminum gear housing with rubber boot for increased durability

Model TW0350 Includes: Belt Clip (324284-9),





#### 6906

## 3/4" IMPACT WRENCH W/ FRICTION RING ANVIL

Max Torque of 433 ft.lbs.

- Powerful 9.0 AMP motor delivers 1,700 RPM for heavy duty applications
- · Precision gearing with ball and needle bearing construction for smooth and efficient power transmission
- Rocker switch with forward/reverse operation for user
- Side handle rotates 360° for operator convenience
- · Externally accessible brushes for easy replacement

Model 6906 Includes: Side Handle (122464-9),



## TW1000

## 1" IMPACT WRENCH W/ FRICTION RING ANVIL

Large Hammer for Greater Impact Power

· Max torque of 738 ft.lbs.

Impacts Per Minute

Maximum Torque (ft.lbs./Nom)

No Load Speed

Overall Length

Shipping Weight

Net Weight

Square Drive (3/4") Capacity:

9 AMPS

1.600 IPM

1,700 RPM

12-7/8"

12.3 lbs.

22 lbs.

433 ft.lbs./588 N•m

- · Efficient impact system with less vibration
- · Externally accessible brushes for easy replacement, and ball bearings for longer tool life
- · Side handle rotates 360° for operator convenience
- · Impact resistant aluminum gear housing with rubber boot for protection and increased durability
- · Rocker switch with forward/reverse operation for user

19 lbs.

19.8 lbs

738 ft.lbs./1,000 N•m

Model TW1000 Includes: Side Handle (123018-5),



#### 6922NB

## 3/4" SHEAR WRENCH

Compact and Lightweight Yet Powerful

- · Delivers 593 ft.lbs. of max torque for the most demanding applications
- · Anti-slipping mechanism: tool won't start until inner
- sleeve engages with bolt tip Bolt tip ejecting lever located by power trigger for
- increased convenience
- · Light weight design at only 10.6 lbs.

Model 6922NB Includes: Outer Sleeve, 3/4" - M20 (764361-9), Outer Sleeve, 7/8" - M22 (153909-6), Screwdriver (783001-0), Inner Sleeve, 7/8" - M22 (764418-6), Steel Tool Case

Square Drive (1")	Capacity:	Bolt Drive (5/8", 3/4", 7/8")
1,500 IPM	No Load Speed	18 RPM
1,400 RPM	Maximum Torque (ft.lbs./N•m)	593 ft.lbs./804 N•m
ft.lbs./1,000 N•m	Overall Length	9-13/16"
12	Net Weight	10.6 lbs.
15"	Shipping Weight	20.12 lbs.
19 lbs.		

D-H-D-i--- (E/OII 0/4II 7/0II)





**Applications** 

socket changes

No Load Speed (3 speed)

Maximum Torque (ft.lbs.)

Net Weight (with battery)





1/2" IMPACT WRENCH KIT Perfect for High Torque Fastening

1,180 ft.lbs of breakaway torque

. BL™ Motor delivers 740 ft.lbs. of Max Torque and

3-speed (0-900/0-1.000/0-1.800 RPM & 0-1.800/

0-2,000/ 0-2,200 IPM) for precise fastening control

**Model XWT08M Includes:** (2) 18V LXT® Lithium-lon 4.0Ah Battery (BL1840B), 18V Lithium-lon Rapid Optimum Charger (DC18RC), Tool Bag

Model XWT08Z Includes: Tool Only; Battery and Charger not included

Impacts Per Minute (3 speed) 0 - 1,800 / 0 - 2,000 / 0 - 2,200 IPM

· Compact and ergonomic design at only 9" long

· 1/2" anvil with friction ring for quick and easy



# 4.0<sub>ab</sub>

## **18v LXT® BRUSHLESS HIGH TORQUE 3/4"** IMPACT WRENCH KIT

Perfect for High Torque Fastening **Applications** 

- BL<sup>™</sup> Motor delivers 780 ft.lbs. of Max Torque and 1,250 ft.lbs of breakaway torque
- · 3-speed power selection switch (0-900/0-1,000/ 0-1,800 RPM & 0-1,800/ 0-2,000/ 0-2,200 IPM) provides precise fastening control
- $\bullet$  3/4" anvil with friction ring and thru hole retention system for maximum productivity

**Model XWT07M Includes:** (2) 18V LXT® Lithium-Ion 4.0Ah Battery (BL1840B), 18V Lithium-Ion Rapid Optimum Charger (DC18RC), Tool Bag

Model XWT07Z Includes: Tool Only; Battery and Charger not included		
Square Drive	3/4"	
No Load Speed (3 speed)	0 - 900 / 0 - 1,000 / 0 - 1,800 RPM	
Impacts Per Minute (3 speed) 0 - 1,800 / 0 - 2,000 / 0 - 2,200 IPM		
Maximum Torque (ft.lbs.)	780 ft.lbs.	
Battery	18V LXT® Lithium-Ion	
Overall Length	9"	
Net Weight (with battery)	8.1 lbs.	
Shipping Weight	16.6 lbs.	



## **18v LXT® BRUSHLESS HIGH TORQUE 7/16" HEX** IMPACT DRILL KIT

Perfect for High Torque Drilling Applications

- BL<sup>™</sup> Motor delivers 590 ft.lbs. of Max Torque
- · 3-speed power selection switch (0-900/0-1,000/ 0-1,800 RPM & 0-1,800/ 0-2,000/ 0-2,200 IPM) provides the user with precise fastening control
- The BL™ Brushless Motor eliminates carbon brushes, enabling the BL Motor to run cooler and more efficiently for longer life
- Efficient BL<sup>™</sup> Brushless motor is electronically controlled to optimize battery energy use for up to 50% longer run time per charge

Model XWT09T Includes: 18V LXT® Lithium-Ion 5.0Ah Battery (BL1850B), 18V Lithium-Ion Rapid Optimum Charger (DC18RC), Tool Bag

Model XWT09Z Includes:	Tool Only; Battery and Charger not included
Hex Shank	7/16"
No Load Speed (3 speed)	0 - 900 / 0 - 1,000 / 0 - 1,800 RPM
Impacts Per Minute (3 spe	ed) 0 - 1,800 / 0 - 2,000 / 0 - 2,200 IPM
Maximum Torque (ft.lbs.)	590 ft.lbs.
Battery	18V LXT® Lithium-Ion
Overall Length	9"
Net Weight (with battery)	8.1 lbs.
Shipping Weight	16.7 lbs.



## 18v LXT® BRUSHLESS 3-SPEED 1/2" IMPACT WRENCH KIT

**Improved Fastening Control** 

- . BL™ Brushless Motor delivers 210 ft.lbs. of Max Torque . Compact and ergonomic design at only 5-3/4" long
- 3-speed power selection switch (0-1,600 / 0-2,100 / 0-2,800 RPM & 0-1,800 / 0-2,600 / 0-3,500 IPM) for precise fastening control
- Efficient BL™ Brushless Motor is electronically controlled to optimize battery energy use for up to 50% longer run time per charge

Model XWT02MB Includes: (2) 18V LXT® Lithium-Ion 4.0Ah Battery (BL1840B), 18V Lithium-Ion Rapid Optimum Charger (DC18RC), Tool Bag

Model XWT02Z Includes: Tool Only: Battery and Charger not included

Square Drive	1/2"		
No Load Speed (3 speed)	0 - 1,600 / 0 - 2,100 / 0 - 2,800 RPM		
Impacts Per Minute (3 speed) 0 - 1,800 / 0 - 2,600 / 0 - 3,500 IPM			
Maximum Torque (ft.lbs./N	•m) 210 ft.lbs./280 N•m		
Battery	18V LXT® Lithium-Ion		
Overall Length	5-3/4"		
Net Weight (with battery)	3.8 lbs.		
Shipping Weight	12 lbs.		



0 - 900 / 0 - 1,000 / 0 - 1,800 RPM









740 ft.lbs.

9"

7.9 lbs.

16.2 lbs

18V LXT® Lithium-Ion

Battery

Overall Length

Shipping Weight