







Handles 16 Ga. Mild Steel and 18 Ga.

• For clean and precise work in keystone plate, deck

· Slim and ergonomic body design for easy gripping

• Extremely light (weighs only 3.6 lbs.) for easier handling

Model JN1601 Includes: Spanner Wrench (781028-4),



XNJ01

18v LXT® 16 GAUGE NIBBLER KIT Powerful, Versatile and Cordless

- · Makita-built motor delivers 1,900 SPM for fast and smooth cutting
- Ideal for cutting roofing sheet metal at thicknesses up to 16 gauge
- Die holder rotates 360° to meet demands of cutting
- · Convenient chip disposal is below cutting material to minimize damage to cutting surface
- Cutting radius: inner edge 1-3/4"; outer edge 2"

Model XNJ01 Includes: (2) 18V LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18V Lithium-Ion Rapid Optimum Charger (DC18RC), Punch (A-83951), Spanner Wrench (271301), Table Page (DC1880), Punch (A-83951), Spanner Wrench (271301) (781028-4), Tool Bag

Model XNJ01Z Includes: Tool Only; Battery and Charger not included

|--|

JS8000

FIBER CEMENT SHEAR

Cuts Quickly While Producing Less Dust

- · Single-piece shear head is machined from precisely milled aluminum to ensure blades cut straight
- · Solid steel blades cut clean, straight lines with a
- maximum cutting capacity up to 5/16" • 1/2" protected spindle withstands heavy torque loads
- · Lightweight cast aluminum gear housing for durability
- · Retractable tool hook allows user to work in tight spaces

Model JS8000 Includes: Shear Blade, Center (725129-8) (2) Shear Blade, Side (725130-3), Hex Wrench (783221-6), Tool Case (824780-2)

П	16	2	n 1
U	N.G	14	UΙ

10 GAUGE NIBBLER

Powerful 6.2 AMP Motor; 1,300 SPM for the Most Demanding Applications

- · Less noise at 81 dB(A) for continuous operation
- · Well balanced with a rubberized soft grip handle for greater comfort
- · Built-in thickness gauge for added convenience
- · Refined design at only 7.4 lbs.
- · Lock-on switch for continuous operation

Model JN3201 Includes: Punch (792728-1), Die (792292-2), Hex Wrench (783201-2), Spanner Wrench (781019-5)

10 ga. (mm) 10 ga. (mm) 13 ga. (mm)	Capacities: Aluminum Mild Steel Stainless	10 ga. (mm) 16 ga. (mm) 18 ga. (mm)
1,300 SPM	Strokes Per Minute	2,200 SPM
4-3/4" 5-1/16"	Cutting Radius: Inner Edge Outer Edge	1-3/4" 2"
6.2	AMPS	5
8-1/2"	Overall Length	10-1/4"
7.5 lbs.	Net Weight	3.6 lbs.
8.8 lbs.	Shipping Weight	5.28 lbs.

JN1601

Stainless

16 GAUGE NIBBLER

plate and other sheet materials

• Die rotates 360°; large 1/4" stroke

· Lock-on sliding switch for continuous use

· Built-in thickness gauge for convenience

Сарасну	3/16
Strokes Per Minute (variable speed)	0 - 2,500 SPM
AMPS	6.5
Overall Length	13-5/8"
Net Weight	4.8 lbs.
Shipping Weight	8.5 lbs.

оарасниея:	Mild Steel Stainless	10 ga. (11111) 10 ga. (mm) 13 ga. (mm)	ľ
Strokes Per Min	ute	1,300 SPM	:
Cutting Radius:	Inner Edge Outer Edge	4-3/4" 5-1/16"	
AMPS		6.2	1
Overall Length		8-1/2"	1
Net Weight		7.5 lbs.	1
Shipping Weight		8.8 lbs.	:

Capacities:	Aluminum Mild Steel Stainless	10 ga. (mm) 16 ga. (mm) 18 ga. (mm)
Strokes Per Min	2,200 SPM	
Cutting Radius:	Inner Edge Outer Edge	1-3/4" 2"
AMPS		5
Overall Length		10-1/4"
Net Weight		3.6 lbs.
Shipping Weight		5.28 lbs.

Capacities: Aluminum Mild Steel Stainless	12 ga. (mm) 16 ga. (mm) 18 ga. (mm)
Strokes Per Minute (variable speed)	0 - 1,900 SPM
Cutting Radius: Inner Edge Outer Edge	1-3/4" 2"
Battery	18V LXT® Lithium-Ion
Overall Length	12-3/8"
Net Weight (with battery)	4.8 lbs.
Shipping Weight	13.3 lbs.





18 GAUGE STRAIGHT SHEAR

Powerful 6.5 AMP Motor for **Continuous Operation**

- · Cuts up to 18 gauge mild steel, 20 gauge stainless and 13 gauge aluminum
- · Pistol grip design for comfort and convenience
- · Shear head attachment rotates 360°
- · Large variable speed trigger switch for controlled cutting speed
- · Retractable belt clip allows operation in tight areas
- · Lock-on button for continuous operation

Model JS1300 Includes: Shear Blade, Right (725092-5), Shear Blade, Left (725093-3), Shear Blade, Center (725094-1), Shear Head Assembly (125112-9), Hex Wrench (783215-1)

Capacities:	Aluminum Mild Steel Stainless	13 ga. (mm) 18 ga. (mm) 20 ga. (mm)
Strokes Per Mi	nute (variable speed)	0 - 2,500 SPM
AMPS		6.5
Overall Length		11-7/8"
Net Weight		3.9 lbs.
Shipping Weigl	nt	5.28 lbs.











18v LXT® 18 GAUGE STRAIGHT SHEAR KIT

Swivel Shear Head Rotates 360°

- · Makita-built 4-pole motor delivers 3,000 strokes per minute for faster cutting
- · Cuts up to 18 gauge mild steel and 20 gauge stainless steel
- · Weighs only 5.3 lbs. with battery for reduced operator fatigue
- · Reversible belt-clip attaches to either side of the tool
- · Rubberized soft grip handle provides increased comfort on the job

Model XSJ01 Includes: (2) 18V LXT® Lithium-lon 3.0Ah Battery (BL1830), 18V Lithium-lon Rapid Optimum Charger (DC18RC), Tool Bag

Model XSJ01Z Includes: Tool Only; Battery and Charger not included

Capacities:	Mild Steel Stainless	18 ga. (mm) 20 ga. (mm)
Strokes Per	Minute	3,000 SPM
Battery		18V LXT® Lithium-Ion
Overall Leng	yth	13-3/4"
Net Weight (with battery)	5.3 lbs.
Shipping We	eight	14 lbs.



JS1602

16 GAUGE SHEAR

Cuts 16 Ga. Mild Steel and 18 Ga. Stainless

- Powerful 3.3 AMP motor delivers 4,000 SPM for the most demanding applications
- · Small circumference barrel grip (only 2-1/4") for added comfort
- · Refined design at only 3.4 lbs. for increased control
- · Lock-on slide switch for continuous operation
- · Built-in thickness gauge for added convenience · Large easily replaceable blades with 8 cutting edge

Model JS1602 Includes: Hex Wrench (783201-2), Shear Blade Set (191383-0)

Capacities:	Aluminum Mild Steel Stainless	1	3 ga. (mm) 6 ga. (mm) 8 ga. (mm)	С
Strokes Per Min	ute		4,000 SPM	S
Cutting Radius			1-3/16"	C
AMPS			3.3	Α
Overall Length			12-1/2"	0
Net Weight			3.4 lbs.	N
Shipping Weight	t		4.9 lbs.	S



JS3201

10 GAUGE SHEAR

Powerful 6.2 AMP Motor; 1,600 SPM for the Most Demanding Applications

- Less noise at 81 dB(A) for continuous operation
- · Tight 2" cutting radius for greater versatility
- · Lock-on switch for continuous operation
- · Built-in thickness gauge for convenience
- · Refined design at only 7.4 lbs. for increased control
- · Large, easily replaceable blades with 8 cutting edges each

Model JS3201 Includes: Hex Wrench (783202-0), Shear Blade Set, JS3201 (792287-5), Thickness Gauge

Capacities:	Aluminum Mild Steel Stainless	9 ga. (mm) 10 ga. (mm) 13 ga. (mm)
Strokes Per Min		1,600
Cutting Radius		2"
AMPS		6.2
Overall Length		8-3/8"
Net Weight		7.4 lbs.
Shipping Weigh	t	8.8 lbs.





		Abrasive	Cutting	y Wheels			
	Description	Diameter	Arbor	Material	Qty./Pkg.	Model	Part #
	Power Cutter Abrasive	12"	1"	Concrete, Stone, Masonry and Asphalt	10	4440U DD00440 DD07000	965-210-6
2000 A 100 A	Abrasive Cut-Off Wheels	12"	1"	Ferrous Metals	10	4112H, DPC6410, DPC7320	965-210-6
		14"	1"	Concrete, Stone, Masonry and Asphalt	10	4114, EK7651H, EK7301,	965-210-2
		14"	1"	Ferrous Metals	10	EK6101	965-210-2
		16"	20mm	Concrete, Stone, Masonry and Asphalt	1	EK8100	966-161-0
	Chop Saw Abrasive Cut-Off Wheels	12"	1"	Steel, Studs, Angle Iron, Channel and Steel Pipe	5	2412N	724504-
		14"	1"	Steel, Studs, Angle Iron,	5		A-93859-
		14"	1"	Channel, Steel Pipe	25	2414NB, 2414DB,	A-93859-2
		14"	1"	Steel, Studs, Angle Iron,	5	LW1400, LW1401	B-10849-
		14"	1"	Channel, Steel Pipe	25		B-10849-2
	16"	1"	Steel, Studs, Angle Iron, Channel, Steel Pipe	5	2416S	724701-3	

	libbler & Shear Acces	ssories	
	Description	Model	Part #
ear Blades	Right Blade		725092-5
	Center Blade	JS1300, XSJ01	725094-1
600	Left Blade		725093-3
	Left & Right Blade Set	JS1670 -	792536-0
	Center Blade	JS1670	792537-8
	Blade Set	JS1600	191383-0
	Blade Set	JS3201	792287-5
	Side Blade Set		725130-3
	Center Blade Set	JS8000	725129-8
	Shear Blade Kit		135168-4
	Side Blade Set	JS1600 -	792533-6
-	Center Blade Set	331000 -	792534-4

	Center Blade Set	331000 -	792534-4
	Side Blade Set	JS1600 —	792533-6
	Shear Blade Kit		135168-4
	Center Blade Set	JS8000	725129-8
and a	Side Blade Set		725130-3
	Blade Set	JS3201	792287-5
	Blade Set	JS1600	191383-0
	Center Blade	JS1670 _	792537-8
	Left & Right Blade Set	104.070	792536-0

Model	Part #	
JN1600	792265-5	
JN1601, XNJ01 JN3200, JN3201	A-83951 792728-1	
	JN1600 JN1601, XNJ01	JN1600 792265-5 JN1601, XNJ01 A-83951

		Model	Part #	
Die		JN1600	792264-7	
		JN1601, XNJ01	A-15051	
JN3200	JN1600	JN3200, JN3201	792292-2	

l	Band Saw Accessories				
		Workpiece Thickness	TPI	1/Pkg. Part #	5/Pkg. Part #
-	Bi-Metal Band Saw Blades	1/4"-1/2"	14		B-40543
	32-7/8" x 1/2" x 0.020"	NEW 1/8"-1/4"	18	A-97570	
-	Improved welding process for longer life	1/8"-1/4"	18		B-40559
-	Durable bi-metal construction	-1/8"	24		B-40565
-	Designed to cut non-ferrous metal, mild steel, cast steel, cast iron and stainless s	teel			

	Workpiece Thickness	TPI	1/Pkg. Part #
44-7/8" x 1/2" x .020"	1/2" +	10	792557-B
Bi-metal construction for up to 3x	1/4" - 1/2"	14	792557-A
longer life than carbon blades	1/8" - 1/4"	18	792556-A
 Ideal for cutting a wide variety of materials including, rebar, pipe, all thread, and channel 	- 1/8"	24	792555-A

	Model	Part #
Cutting Wax Extends blade life with easier cutting	2107F/K, XBP01, XBP02	191897-9