

# SPEED & EFFICIENCY



**14 INCLUDED**  
Accessories

**1-1/4" Plunge Blade**  
A-95255

**Adapter**  
313249-6

**Adapter**  
196271-6

**Sanding Pad**  
A-95423

**Sandpaper**  
10 Pc. Assortment

## TM3010CX1

### MULTI-TOOL KIT "Tool-less" Clamp System for Fast Accessory Installation

- Powerful 3.0 AMP motor with soft start feature for smooth start-ups and improved performance for fast cutting, sanding, scraping and grout removal
- Variable speed control dial (6,000-20,000 OPM) enables user to match the speed to the application
- Electronic speed control maintains constant speed under load for smoother, higher-quality work
- Precision engineered for reduced vibration (6.5m/s<sup>2</sup>) and low noise 80dB(A)
- 3.2° oscillation angle engineered for faster cutting and sanding

**Model TM3010CX1 Includes:** 1-1/4" Plunge Blade (BiM) (A-95255), Sanding Pad, Multi-Tool, TM3000C, LXMT (A-95423), (5) 120 Grit Sandpaper (A-9532-1), (5) 180 Grit Sandpaper (A-9548-1), Multi-Tool Adapter (313248-8), Multi-Tool Adapter (313249-6), Multi-Tool Adapter (313248-8), Multi-Tool Adapter (313249-6), Accessory Case, Tool Case

Oscillations Per Minute	6,000 - 20,000 OPM
Oscillation Angle	3.2°
AMPS	3
Overall Length	11-1/8"
Net Weight	3.5 lbs.
Shipping Weight	8.8 lbs.

## Additional Multi-Tool Accessories

### 2" Scraper

**A-95342**



### 3" Scraping Plate

**A-95401**



### 1-1/4" Plunge Blade

**A-95277**



### 3-1/4" Round Saw Blade

**A-95168**



### 3-1/4" Segmented Saw Blade

**A-95227**



### 3-1/4" Grout Removal Blade

**A-95386**



### (10 per/pkg)

### Sandpaper



Description	Part #
Assortment	A-95853
180 Grit	A-95548
150 Grit	A-95750
120 Grit	A-95532
100 Grit	A-95744
80 Grit	A-95526

Additional Multi-Tool Accessories See pg. 123



## XMT035

**3.0Ah BATTERY**

### 18v LXT® MULTI-TOOL KIT "Tool-less" Clamp System for Fast Accessory Installation

- 18V LXT® Lithium-Ion battery provides up to 20 minutes of continuous run time
- Variable speed control dial (6,000-20,000 OPM) enables user to match the speed to the application
- 3.2° oscillation angle engineered for faster, more aggressive cutting and sanding
- Large on/off slide switch with lock-on button for operator convenience

**Model XMT035 Includes:** (2) 18V LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18V Lithium-Ion Rapid Optimum Charger (DC18RC), 1-1/4" Plunge Blade (BiM) (A-95255), Multi-Tool Adapter (313249-6), Multi-Tool Adapter (313248-8), Tool Bag

**Model XMT03Z Includes:** Tool Only, Battery and Charger not included

Oscillations Per Minute	6,000 - 20,000 OPM
Oscillation Angle	3.2°
Battery	18V LXT® Lithium-Ion
Overall Length	13-3/8"
Net Weight (with battery)	4.9 lbs.
Shipping Weight	14.1 lbs.



## RP2301FC

### 3-1/4 HP\* PLUNGE ROUTER Delivers Power and Precision

- Powerful 15 AMP motor delivers 9,000 - 22,000 RPM for smooth routing
- Electronic speed control maintains constant speed under load
- Variable speed control dial enables user to match the speed to the application
- Soft start feature for smooth start-ups
- Electric brake for maximum productivity
- 0" - 2-3/4" plunge depth capacity for easy penetration in work piece

**Model RP2301FC Includes:** 1/2" Collet (763622-4), 1/4" Collet (763803-0), Extend Depth Adjustment Knob (158980-5), Spanner Wrench (781030-7)

Collet Capacity	1/2", 1/4"
Plunge Capacity	2-3/4"
No Load Speed (variable speed)	9,000 - 22,000 RPM
AMPS	15
Maximum Horsepower	3-1/4 HP
Overall Length	12-1/4"
Net Weight	13.4 lbs.
Shipping Weight	16.4 lbs.



## RP1800

### 3-1/4 HP\* PLUNGE ROUTER Deep 2-3/4" Depth Capacity Delivers Performance

- Powerful 15 AMP motor delivers up to 22,000 RPM for smooth routing
- 0" - 2-3/4" plunge depth capacity for easy penetration in work piece
- Linear ball bearings for smooth plunge action and superior performance
- Quick release plunge depth adjustment with micro control along with 3 preset depth stops for added precision
- Oversized ball bearing construction for longer tool life

**Model RP1800 Includes:** 1/2" Collet (763622-4), 1/4" Collet (763803-0), Extend Depth Adjustment Knob (158980-5), Spanner Wrench (781030-7)

Collet Capacity	1/2", 1/4"
Plunge Capacity	2-3/4"
No Load Speed	22,000 RPM
AMPS	15
Maximum Horsepower	3-1/4 HP
Overall Length	12-1/4"
Net Weight	13.4 lbs.
Shipping Weight	16.4 lbs.



## RP0900K

### 1-1/4 HP\* PLUNGE ROUTER Powerful 8 AMP Motor Delivers 27,000 RPM

- 0" - 1-3/8" plunge depth capacity for easy penetration into work piece
- Plunge depth adjustment lever with 3 preset depth stops for precision
- Oversized ball bearing construction for longer tool life
- Durable flat top design for added convenience when changing bits
- Rubberized contoured handles with built-in switch for better fit & control
- Easy-to-read depth scales

**Model RP0900K Includes:** 1/4" Collet (763637-1), Straight Guide (164834-6), Spanner Wrench (781006-4), Spanner Wrench (781011-1), Tool Case

Collet	1/4"
Plunge Capacity	1-3/8"
No Load Speed	27,000 RPM
AMPS	8
Maximum Horsepower	1-1/4 HP
Overall Length	8-1/2"
Net Weight	6 lbs.
Shipping Weight	5.52 lbs.



## RF1101KIT2

### 2-1/4 HP\* ROUTER KIT, WITH PLUNGE BASE Deluxe Kit Includes the Most Popular Accessories

- Powerful 11 AMP motor with variable speed control dial
- Electronic speed control with soft start feature
- Rugged aluminum motor housing with small 3-1/4" diameter
- Cam-lock for fast and easy depth adjustment and removal of motor
- Conveniently located plunge lock lever for efficient operation

**Model RF1101KIT2 Includes:** 2-1/4 HP\* Router (RF1101), Plunge Base (193457-3), 1/2" Collet (763643-6), 1/4" Collet with Nut (193214-9), 2-1/2" Clear Sub Base (193155-9), (2) Wrench 27 (193234-3), Spanner Wrench (781213-9), Hex Wrench (783202-0), Tool Case

Collet Capacity	1/2", 1/4"
Plunge Capacity	2-9/32"
No Load Speed (variable speed)	8,000 - 24,000 RPM
AMPS	11
Maximum Horsepower	2-1/4 HP
Overall Length	8-3/4"
Net Weight	7.2 lbs.
Shipping Weight	20 lbs.

\*Maximum horsepower