

# Electric Heat Guns

## Ecoheat® Heat Gun & Kit



Kit includes storage case and four specialized nozzle attachments

### Specifications

- **Air Volume:** 7 or 9 CFM
- **Air Velocity:** 720 or 1100 FPM
- **Motor:** Permanent Magnet
- **Nozzle Opening:** 1.2" I.D., 1.35" O.D.
- **Cordset:** 6 ft., 3-wire grounded
- **Dimensions:** 8.5" L x 3.2" W x 7.7" H
- **120V Models**
- **Tool Net Weight:** 2 lbs.
- **Shipping Weight Tool:** 3 lbs.
- **Shipping Weight Kit:** 5 lbs.

*NOTE: Users should independently evaluate the suitability of the product for their application.*

### Economical, Lightweight, Multi-use Heat Gun

- Two heat settings: 500°F or 1000°F (260°C or 540°C)
- Two fan speeds - Low or High (7 or 9 CFM)
- Lightweight - 1 lb. - Easy to hold at any angle for long periods of time, eliminates operator fatigue
- Built-in hand guard - Protects hand and fingers. Recessed switch guards against knocks and bumps
- 3-wire grounded cordset - Positive grounding system for user safety
- Thermoplastic housing - For high impact durability
- Built-in stand - Very stable, allows user to set heat gun down in an upright position for hands-free use
- Use to bend and form plastics, dry body fillers, remove decals, spot dry paint, shrink tubing, packaging and more

### Ecoheat Heat Gun & Kit

Model No.	Description
<b>EC-100</b>	500° or 1000°F 260° or 540°C 7 or 9 CFM 120V 60 Hz 10A 1200W
<b>EC-100K</b>	Kit includes EC-100 Heat Gun, 7/8" reducer attachment, 1-1/4" shrink tubing reflector, 1-15/16" and 3-1/8" spreader attachments packed in a durable storage/carrying case
<b>35225</b>	Attachment kit contains 7/8" reducer attachment, 1-1/4" shrink tubing reflector, 1-15/16" and 3-1/8" spreader attachments
<b>35215</b>	Durable storage/carrying case

## Masterflow® Heat Blower



### Professional Quality, Continuous-duty, Process Heat Blower

- 3 models produce 300°F, 500°F or 750°F. High temperatures accommodate many heating, drying & shrinking applications
- High air flow: 47 CFM at 2200 FPM gets job done fast
- Brushless induction type motor for quiet, continuous-duty operation
- Easily replaceable, reinforced, mica-insulated heating element
- Rubber-backed stand permits 90° non-slip adjustability
- Use in any position or mount on equipment
- Ergonomic handle for carrying or portable use
- Mount over conveyor line or on machinery
- Use to heat or dry materials, bend plastics, shrink wrap and more

### Ecoheat Heat Gun & Kit

Model No.	Description	Replacement Element
<b>AH-301**</b>	300°F 150°C 120V 60 Hz 10A 1200W	<b>815</b> (3.5"), <b>35485</b> (6")
<b>AH-501</b>	500°F 260°C 120V 60 Hz 14A 1680W	<b>30310</b>
<b>AH-751*</b>	750°F 400°C 120V 60 Hz 18A 2160W	<b>30312</b>
<b>AH-302**</b>	750°F 400°C 240V 60 Hz 5.2A 2160W	<b>816</b> (3.5"), <b>35486</b> (6")
<b>AH-502</b>	500°F 260°C 240V 60 Hz 7.3A 1680W	<b>30311</b>
<b>AH-752</b>	750°F 400°C 240V 60 Hz 9.4A 2160W	<b>30313</b>

\*\* 815 and 816 Element for 3.5" Nozzle, 35485 and 35486 Element for 6" Nozzle.

### Specifications

- **Air Volume:** 47 CFM
- **Air Velocity:** 2200 FPM
- **Motor:** Induction
- **Nozzle Opening:** 1.85" I.D., 2.25" O.D.
- **Cordset:** 6 ft., 3-wire grounded
- **Dimensions:** 12" L x 6" W x 9" H
- **All Models**
- **Base Size:** 6" x 6"
- **Net Weight:** 6 lbs.
- **Shipping Weight:** 8 lbs

*NOTE: Users should independently evaluate the suitability of the product for their application.*