

# Butane-Powered Torches

Microtorch MT-51, MT-51B & MT-51H



### MT Series Microtorch MT-51B

Included butane canister (10448) provides three fuel refills



### MT Series Microtorch MT-51

### MT Series Microtorch MT-51H

Includes Hot Air Tip (35387) & Heat Reflector (35394) for heat shrink applications



Heat Shrinking

### Microtorch MT-51

Model No.	Description
MT-51	Microtorch, table-top
MT-51B	Microtorch, table-top with 15/16 oz. butane (10448)
MT-51H	Microtorch, table-top includes hot air tip (35387) and 1" diameter heat shrink attachment (35394)

### Specifications

- **Approx. Flame Temp.** 2500°F
- **Fuel Tank:** Plastic, Built-in, Refillable
- **Approx. Run Time:** 2 hours
- **Dimensions:** 6.1" H x 3" W x 1.3" D
- **Tool Net Weight:** 5 oz.
- **Shipping Weight:** 1 lb.
- **Shipped Empty**
- 

**NOTE:** Users should independently evaluate the suitability of the product for their application.

## Hand-held or Table-top Butane-powered Microtorch

- Built-in self-igniting system with safety lock
- "Hands-free" slide lock for continuous use and instant off operation
- Durable self-contained, refillable plastic fuel tank
- Wide, stable base is perfect for hands-free use
- Temperatures up to 2500°F/1300°C
- 2 hour continuous burn time, perfect for continuous heat applications
- Adjustable broad or pinpoint flame
- Meets Consumer Products Safety Commission (CPSC) Child Safety Requirements
- MT-51B ships via ground transportation with no Hazmat charges
- Use to heat materials, ignite materials, pinpoint torch, shrink tubing, solder and desolder, terminate specialty connectors and more
- Refill with Master Ultratane Butane for best performance (page 31)