

COMPACT UV LEAK LOCATOR KITS

Leading the way in UV LEAK DETECTION, Mastercool offers a variety of compact UV leak locator kits. Each kit offers a powerful inspection lamp, a "Refillable" or "Cartridge Type" Dye Injector and accessories. All kits are packaged in a clamshell or custom molded carrying case.

KIT PART#	INJECTOR / LIGHT	CONTENTS OF EACH KIT	VOLTAGE/WATT
53451-110	53123/ 53518-UV	Rechargeable UV light, batteries, rechargeable batteries, battery holder, refillable 2 oz dye injector, 2 oz concentrated universal A/C fluorescent dye (25 application), 4 oz dye remover, 25 service information labels, UV enhancing safety glasses	LED
53451-C-110	53223/ 53518-UV	Same as 53451-110 but with replaceable 2 oz dye cartridge (25 applications)	LED
53583	53809/ 53513-UV	Mini UV Flashlight (53513-UV), "cartridge type" 1 oz dye injector with replaceable dye cartridge, low side hose, 1/4" FL adapter, UV safety glasses, service info. labels	LED
53587	53809/ 53517-UV	Compact UV flashlight (53517-UV), 1 oz dye injector with replaceable 1 oz dye cartridge (10 application), low side hose, 1/4" FL adapter, UV enhancing safety glasses, service information labels, packaged in a clam shell	LED
53580	53809/ 53515	MACH IV flexible LED UV light with 1 oz (30 ml) dye injector, w/replaceable 1 oz (30 ml) dye cartridge (10 application.), low-side hose with R134a coupler, 1/4" FL adapter, 10 service information labels & UV enhancing safety glasses	LED
53585	53809/ 53515	Same as above, but with 1 oz OIL/ATF/Gas (53610) & diesel fluorescent dye and 1oz (30ml) engine coolant fluorescent dye (53609)	LED
53100	53123/ 53012	High intensity swivel head light, with refillable 2 oz (60 ml) dye injector, 2 oz (60 ml) concentrated universal A/C fluorescent dye (25 application.), 4 oz (1200 ml) dye remover, 25 service information labels & UV enhancing safety glasses	12 V/100 WATT
53100-C	53223/ 53012	Same as 53100, but with replaceable 2 oz (60 ml) dye cartridge (25 application.)	12 V/100 WATT
53500	53123/ 53312	High intensity mini light w/refillable 2 oz (60 ml) dye injector, 2 oz (60 ml) concentrated universal A/C fluorescent dye (25 application.), 4 oz (120 ml) dye remover, 25 service information labels & UV enhancing safety glasses	12 V/50 WATT
53500-C	53223/ 53312	Same as 53500, but with replaceable 2 oz (60 ml) dye cartridge (25 Appl.)	12 V/50 WATT
53351	53809/ 53312	High intensity, 12V/50 watt, mini light (53312, replaceable 1 oz (10 application) dye cartridge (53809), A/C connection hose w/R134a coupler, 1/4" FL adapter, 1 oz OIL/ATF/Gas and diesel fluorescent dye, 1 oz engine coolant dye, 4 oz dye remover, 25 service information labels, UV enhancing safety glasses	12 V/50 WATT