EPDM RUBBER AIR HOSE



1628-1 1633 1630 1634 1631 1635 1632 1636 Deluxe heavy duty EPDM rubber is designed for tough service station and shop applications. Kink resistant and flexible in extreme temperatures, resists abrasion, weathering and ozone. Assembled with brass fittings, bulk hose comes without fittings in either a dispensing box or handy reel. Individually boxed. Limited oil resistance

Maximum working pressure: 250 PSI

• Burst pressure: 1000 PSI


• Working temperature: -40°F to 190°F (-40°C to 87°C)

 Material: EPDM rubber tube & cover spiral synthetic yarn reinforcement

· Color: red

	Assemblies				
Part No.	Hose ID	Length	Fittings, NPT		
1628-1	5/16"	50'	Male 1/4" x Female 1/4" Swivel Barb NPS		
1630	1/4"	25'	Male 1/4" Both Ends		
1631		50'			
1632	3/8"	25'	Male 3/8" Both Ends		
1633		50'			
1634		25'	Male 1/4" Both Ends		
1635		50'			
1636	1/2"	25'	Male 1/2" Both Ends		
1636-1		50'	ividie 1/2 Both Ends		

Bulk rubber hose only - fittings not included



1630-500BK

SWIVEL END SNUBBER HOSES

SEE PG. 27 FOR HOSE FITTINGS



s-680 s-680-3 s-680-1 681 s-680-2 681-1 Absorbs shock to air couplers from impact tools and/or air hammers. Snubber hoses are fitted with a full 360° steel swivel fitting for greater flexibility and easier use

• Burst pressure: 800 PSI

· Maximum working pressure: 200 PSI

Boxed Part No.	Retail Part No.	Per Card	Product Specs		360° Swivel Fitting NPT	Brass Fitting
Part No.	Part No.	Card	Hose ID	Length	FILLING NET	riuiig
	s-680	1	3/8"	30"	Male 1/4"	Female 1/4"
	s-680-1	1		5'		
	s-680-2	1		30"		
	s-680-3	1		5'		
681			1/2"	2'	Male 3/8" Non-Swivel	Male 3/8"
681-1					Male 1/2" Non-Swivel	Male 1/2"

JACK HAMMER HOSE



- Made of the highest quality EPDM rubber material, complete with universal couplers
- Great for jack hammers, plus other high-consumption pnuematic tools

Boxed	Product Specs					
Part No.	NPT (in)	Hose Length	Max Pressure			
1638	3/4"	50'	300 PSI			

