

COUPLERS PLUGS CAM/GROOVE
HOSE HOSE REELS FITTINGS
BLO-GUNS
FRLs
PUSH-TO-CONNECT
INFLATOR GAGES
PRESSURE & SERVICE GAGES
GREASE GUNS
MERCHANDISERS

Filter/Regulator & Lubrication Systems... A simple guide.

What are they? Where are they installed? Why would you spend the \$ to buy them?

First off, air leaving a compressor is hot, dirty and wet ... All elements that can damage and WILL shorten the life of expensive equipment and tools. That is why it is essential to protect your investments. Let's talk FILTERS first- Water vapor is the MORTAL enemy within a pneumatic system. The airline filter cleans this compressed air in two important stages:

First Stage - Air entering the filter is directed downward and with the resulting vortex action, liquids and particles are forced to the bowl wall and then extracted.

Second Stage - Air flows inward through the filter element where additional contaminants (as small as 4 microns) are removed with little pressure loss.



PRESSURE REGULATOR component. These reduce as well as control the air pressure in compressed air systems....maintaining an optimal and constant output pressure no matter the input pressure variations. Some of the applications include air tools, blow guns and aerosol lubrication systems.



Why is this important?

- 1) Allows for precise downstream pressure control.
- 2) Built-In safety piston diaphragm assembly automatically vents excess air in the event the downstream pressure exceeds the desired regulator setting.

This prevents excessive pressure from reaching your tools. Excessive pressure causes tools and seals to overwork which can cause over-speeding of the tools' internal mechanisms. Both will decrease the life of your tools.

LUBRICATION element. Truly a key factor in ensuring consistent operation of the tools. It adds a set quantity of oil into the compressed air system reducing moving component friction. How? Pressurized air is introduced and guided through the body where it turns into a smooth aerosol providing the needed lubrication to the working tools. This is critical to air tool life extension.



Additional Value-Add FRL Options

The Piggyback Regulator and Filter System

All in one. Modular design provides extra space while reducing the overall weight load and saving time.



Coalescing Filter System

Designed for applications that require air free of oil, water and foreign particles. It is best to locate these as close as possible to the actual tool. This is recommended for precision tools and actuators.

Desiccant Dryer System

Primarily for more heavy duty operations where any amount of moisture may cause an issue, or operations where extremely dry air is necessary.

More commonly found in a wide range of industrial and commercial facilities.

Desiccant dryers are placed after both Micro Filters and Coalescing Filters, in order to allow the desiccant pellets to absorb effectively.

Note - These cannot be used with a lubricating system. Perfect for spray painting applications, or applications where small amounts of moisture may cause issues.



COUPLERS
PLUGS
CAM/GROOVE

HOSE
HOSE REELS
FITTINGS

BLO-GUNS

FRLs

PUSH-TO-CONNECT

INFLATOR GAGES

PRESSURE &
SERVICE GAGES

GREASE GUNS

MERCHANDISERS

FRL Fun Facts

Air Compressor Compatibility: Big or small, our FRL systems will work with whatever pressure your air compressor provides.

Component Size

Mini - To be used closer to machinery or tool/application

Standard - For traditional use in home garage, small workshop or DIY application.

Heavy Duty - High flow system that is placed closer to compressor... for larger shop applications

SCFM - Standard Cubic Feet Per Minute

Regarding your FRL selection, SCFM only matters when it comes to the application. The SCFM rating of your air compressor is only the speed at which air enters a storage tank. Most pneumatic tools use air much faster than most air compressors can produce it.

EXAMPLE:

- Actual air tool usage is 4 to 5 times the “average SCFM rating” because you aren’t using a tool all the time. However, to get the most out of the tools, it’s best to have the air system capability CFM higher than the tools you plan to use. For example a ½” impact wrench can use as much as 35 SCFM, so make sure all the components upstream of that tool flow an amount of air greater than the tool. 2x if you plan to run two tools.

140 CFM (Auto shop, large workshop or an area that utilizes multiple locations)

247 CFM (Auto shop, large workshop or an area that utilizes multiple locations)

Applications

- Filter** - Critical for every application to ensure the elimination of water and particulates from your airline, machinery and tools
- Pressure Regulator** - The pressure regulator provides uniform controlled pressure to the system and ultimately the tools. The pressure in the air compressor tank rises and falls with usage and pump cycling. The air pressure regulator isolates the system from this and delivers air at a consistent pressure.
- Lubricator** - In-line lubrication takes the human element out of lubricating air tools. The tool is automatically lubricated to ensure long life from the tool. Lubricated air lines and hoses should be segregated to prevent cross contamination. General use air lines, for inflation, cleaning or painting should never have in-line lubrication.




COUPLERS PLUGS CAM/GROOVE
HOSE HOSE REELS HOSE FITTINGS
BLO-GUNS
FRLs
PUSH-TO-CONNECT
INFLATOR GAGES
PRESSURE & SERVICE GAGES
GREASE GUNS
MERCHANDISERS

TECH TIPS


Building An Efficient Air System

Compressed air powered equipment and machinery are critical elements in the productivity, efficiency, and economy of today's industry and quality air is the essential element. Water and dirt cause more problems in compressed air lines than anything else. High speed pneumatic production lines operate efficiently because of air dryers and filters that remove moisture and impurities from the air, which results in eliminating downtime. Regulators and lubricators can be added to control and lubricate downstream equipment. A good air system is the key to saving time, money and to operating at maximum efficiency.



5 Important Steps to an Air System Set-Up

- 1** Main line filter and regulator should be placed at least 20 feet from the compressor. The air will cool down, allowing much of the water vapor to condense naturally for removal by filtration.
- 2** Main line piping should slope down from point of origin by 1/8" per foot. Any water in the line will flow down to the lowest point for draining.
- 3** All line drops (work stations) should be taken from the top of the main line. This prevents water from flowing into branch lines.
- 4** Galvanized pipe is recommended when building an air system.
- 5** Follow illustration to the right when building a work station drop.



COUPLERS
PLUGS
CAM/GROOVE
HOSE REELS
FITTINGS
BLO-GUNS
FRLs
PUSH-TO-CONNECT
INFLATOR GAGES
PRESSURE & SERVICE GAGES
GREASE GUNS
MERCHANTISERS

COUPLERS
PLUGS
CAM/GROOVE

HOSE
HOSE REELS
HOSE FITTINGS

BLO-GUNS

FRLs

PUSH-TO-CONNECT

INFLATOR GAGES

PRESSURE &
SERVICE GAGES

GREASE GUNS

MERCHANDISERS

DESICCANT DRYER SYSTEMS

Replacement Desiccant Charge



- For use with all Milton® desiccant dryers
- Easy to monitor: when color changes in the sight glass from dark blue to pink, then it is time to change or dry the desiccant
- To dry desiccant, remove from unit, bake at 275° for 3 hours

Part No.	Description
1170-1	1 Quart
1170-8	1 Gallon

Mini Disposable Air Line Desiccant Filter/Dryer



- Removes all traces of dirt, dust, water vapor, oil vapor
- Lightweight: 2 oz
- See-through non-metallic chemical resistant material
- Replace cartridge when desiccant beads turn to pink in color
- Max pressure: 125 PSI
- Max flow capacity: 15 SCFM
- Working temperature: 32°F to 130°F (0°C to 54°C)
- Size: 3¾" x 1½"

Bulk Part No.	Retail Part No.	Per Card	Description
1173BK	s-1173	1	Replacement Desiccant Dryer Cartridges (2pk)
	s-1174	1	Mini Air Station w/ Desiccant Dryer Cartridge

Part No.	Description
1174-7	Replacement Air Station Dial Pressure Gage (0-160) PSI

COMPRESSOR OIL

High Performance Compressor Oil



- Provides exceptional wear, oxidation, and corrosion protection
- No-detergent formula minimizes foaming and separates from water easily
- For use in all oil-lubricated reciprocating air compressors
- Prevents formation of sludge and carbon deposits
- Works in cold down to -15°F (-26°C)

High Performance Conventional	
Part No.	Size (oz)
1002-32	32 (Qt)
1002	128 (Gal)

Premium Full Synthetic Compressor Oil



- All the performance of conventional compressor oil, plus...
- Even greater wear, oxidation, and corrosion protection
 - Maximum prevention of sludge and carbon deposit formation
 - Extreme all season low temperature performance down to -36°F (-38°C)

Premium Full Synthetic	
Part No.	Size (oz)
1002-32S	32 (Qt)
1002S	128 (Gal)