

AIR HOSE

Extreme Flex

Features: Specially formulated thermoplastic compounds provide extreme flexibility in severe cold and temperatures. Light weight of PVC and durability of rubber, without cold temperature stiffness, for easy handling. **Construction:** Coupled 1/4" MPT fittings with bend restrictors on each for longer service life. Highly abrasion resistant, non-marking cover. Stronger wall and tighter fabric reinforcement improve hose kink resistance and working/burst pressure without sacrificing flexibility.

Temp. range: -40°F to 150°F.

Apache P/N	I.D. x Length	W.P.	Fittings	Wt. Ea.	Source
10130348	3/8" x 25'	300	1/4" MPT	2.6#	Import
10130350	3/8" x 50'	300	1/4" MPT	5.3#	Import



Rubber

Assemblies: Coupled 1/4" solid brass MNPT fittings with PVC bend restrictors on each end for longer service life. 1/2" is coupled 1/2" MNPT. **Applications:** For air compressors, and other pneumatic tools in the shop or industrial use. **Construction:** Rubber air hose with synthetic yarn reinforcement. More flexible than PVC in extremely cold temperatures. Limited oil resistance.

Apache P/N	I.D. x Length	W.P.	Fittings	Wt. Ea.	Source
91009080	3/8" x 25'	300	1/4" MNPT	5#	Import
91009085	3/8" x 50'	300	1/4" MNPT	9#	Import
91009090	1/2" x 25'	300	1/2" MNPT	6#	Import
91009095	1/2" x 50'	300	1/2" MNPT	12#	Import



Premium Rubber

Assemblies: Coupled 1/4" solid brass MNPT fittings with PVC bend restrictors on each end for longer service life. 1/2" is coupled 1/2" MNPT. **Applications:** For air compressors, and other pneumatic tools in the shop or industrial use. **Construction:** Premium EPDM rubber air hose assembly features excellent operating temperature range, heat, weather (ozone), and abrasion resistance. More flexible than PVC in extremely cold temperatures. Limited oil resistance.

Apache P/N	I.D. x Length	W.P.	Fittings	Wt. Ea.	Source
91009280	3/8" x 25'	325	1/4" MNPT	5#	Domestic
91009285	3/8" x 50'	325	1/4" MNPT	9#	Domestic
91009290	1/2" x 25'	325	1/2" MNPT	6#	Domestic
91009295	1/2" x 50'	325	1/2" MNPT	12#	Domestic



Air Tool Lead-In/Whip-Hose

Assemblies: Red rubber hose coupled 1/4" male NPT 360° ball swivel x 1/4" female NPT.

Features: Absorbs shock and relieves strain on air couplers used with pneumatic impact tools. Improves operator comfort and extends coupler service life. Limited oil resistance. Domestic oil resistant assemblies available.

Apache P/N	I.D. x Length	W.P.	Wt. Ea.	Source
10130400	1/4" x 24"	300	0.25#	Import
10130401	1/4" x 60"	300	0.40#	Import
10130402	3/8" x 24"	300	0.30#	Import
10130403	3/8" x 60"	300	0.56#	Import

