

# AIR CONTROL PRODUCTS



## Compressed Air Components

- D-12** Mini Spray Gun Attaches directly to the spraygun and provides a lightweight sub-micronic filter to remove oil, water and particulate.
- DD-1008** Desiccant Dryer Lightweight disposable desiccant dryer attaches directly to tool. Color change indicator signals replacement.

Model No.	Description	Pipe Size	Nominal Air Flow	Maximum Pressure	Temperature Range	Filtration Rating
D-12	Spraygun Filter	1/4 NPT	30 CFM	100 PSI	32-120 F	.01 Micron
DD-1008	Mini Desiccant Filter	1/4 NPT	20 CFM	125 PSI	32-130 F	5 Micron

- RG-4049** Mini Spraygun Regulator A true diaphragm, precision regulator that weighs ounces. Attaches directly to tool or spraygun for ultimate control.

Model No.	Description	Pipe Size	Nominal Air Flow	Maximum Pressure	Temperature Range
RG-4049	Mini Spraygun Regulator	1/4 NPT	25 CFM	125 PSI	40-120 F



## Air Filters

- M-30** Sub-Micronic Compressed Air Filter M-30/-60 - The ultimate final filter. Removes moisture, particulate and oil aerosols to less than .01 microns in size. Protects refinishing equipment, air tools and plasma cutting equipment. Easily replaceable element.

- M-60** Sub-Micronic Compressed Air Filter

Model No.	Description	Pipe Size	Nominal Air Flow	Maximum Pressure	Temperature Range	Filtration Rating
M-30	Sub-Micronic Filter	1/4 NPT	45 CFM	125 PSI	32-175 F	.01 Micron
M-60	Sub-Micronic Filter	1/2 NPT	100 CFM	125 PSI	32-175 F	.01 Micron

- M-C100** Activated Carbon Filter Cartridge contains activated carbon media that traps oil and other molecules in microscopic pores through the absorption process.

Model No.	Description	Pipe Size	Nominal Air Flow	Maximum Pressure	Temperature Range	Filtration Rating
M-C100	Carbon-Max Filter	1/2 NPT	100 CFM	125 PSI	32-175 F	<.01 ppm



## Filter Elements

- M-723** Fibre-Pure for M30/60 Hydrophilic fiber for non-degrading, contaminant free and minimal pressure loss. For model M-30 and M-60 filters.

- M-785C** Carbon-Max Carbon-Max cartridge contains activated carbon media that traps oil and other molecules for air that is virtually free from oil vapor. For Model M-C100 filter.

## Filter Kits

- M-45-KIT** Clean Air Filter Kit, Sub-Micronic, 1/4 NPT Contains Motor Guard model M-30 filter, mounting bracket, hardware and 2 replacement elements.

- M-100-KIT** Clean Air Filter Kit, Sub-Micronic, 1/2 NPT Contains Motor Guard model M-60 filter and two replacement elements.

Model No.	Description	Pipe Size	Nominal Air Flow	Maximum Pressure	Temperature Range	Filtration Rating
M-45-KIT	Air Filter Kit	1/4 NPT	45 CFM	125 PSI	32-175 F	.01 Micron
M-100-KIT	Air Filter Kit	1/2 NPT	100 CFM	125 PSI	32-175 F	.01 Micron

