

APPLICATIONS

Buick: 1988 - 04 Regal
Cadillac: 2004 - 09 SRX
Chevrolet: 1990 - 01 Lumina Sedan
 1995 - 99 Monte Carlo
Oldsmobile: 1988 - 97 Cutlass/Supreme
Pontiac: 1995 - 96 Grand Prix

GM REAR TOE TOOL

83850

Tool allows quick, precise, and profitable adjustments of rear toe on both left and right sides of GM vehicles.



STEEL FILE SET 85125

Rotary Files

High quality carbide rotary files, ideal for elongating strut holes on many vehicles. Use when installing **82110**, **82120**, and **87350** adjusters. May be used with 1/4" or 3/8" drills at high speeds. Available individually. Use with **85774** Cool Tool cutting fluid (below).

INCLUDES: **85126** - 1/4" Rotary File (Max. Operating Speed 9,000 RPM)
85127 - 3/8" Rotary File (Max. Operating Speed 9,000 RPM)
85128 - 5/8" Rotary File (Max. Operating Speed 7,000 RPM)

3/8" ROTARY FILE SET 85130

This rotary file set is ideal for every technician. Be ready to elongate slots in aluminum and steel frames and brackets to accept larger offset cams. Includes one 85127 rotary file for steel, one 85137 rotary file for aluminum, and cutting fluid (85774) to extend your rotary file's life.

ALUMINUM FILE 85137

This 3/8" rotary file is specifically designed for Aluminum. Use it to quickly and cleanly expand cam slots in aluminum brackets and frames. It is an ideal tool to use when installing SPC Nissan and Infiniti Cams (pages 106, 110 and 111). Also is perfect when installing our Mustang Caster Bolts (page 111) and our Ford Crown Vic Front Cam Kit (page 132). Use with **85774** Cool Tool cutting fluid (below).



CAUTION: Always wear safety glasses when using cutting or grinding tools and equipment.



COOL TOOL FLUID 85774

This fluid lubricates the single rotary files and **85125** and **85130** rotary file sets (above), and the **68670** Rotor-Bor (page 168) to reduce stress on the cutting teeth. This product is **highly recommended** to prolong the life of all cutting bits used on steel.

Check out SPC's new Punch Tools to quickly elongate holes, page 170.

CAUTION: Not for use with impact wrenches (air tools).

3 IN-1 SPINDLE PULLER

85796 is a 3-in-1 puller that makes removing the spindle from four wheel drive vehicles much easier. This puller fits spindle sizes 1-1/2", 1-5/8" and 2" spindles that are OE on 4x4 trucks.



85796

APPLICATIONS

Dodge RWD: 1994 - 99 3500 Ram w/Mono
Dodge 4WD: 1994 - 99 2500HD, 3500 Ram
Ford RWD: 1990 - 90 Bronco II (Late 90)
 1992 & Up E150, E250, E350, E450
 2000 - 05 Excursion; 1987 - 96 F150
 1998 - 13 F250, F350 Twin I-Beam
 1987 - 98 F250, F350
Ford 4WD: 2000 - 05 Excursion
 1999 - 04 F250, F350 Solid Axles/Leaf Springs
 1992 - 98 F350 Crew Cab
Ford RWD/4WD: 1999 - 04 F450, F550
 1991 - 94 Explorer

TRUCK SLEEVE SOCKET

87175

This 1-1/2" socket is useful for adjusting both the OE and our popular **23130** and **23180** sleeve series (see page 75) for Ford and Mazda RWD and 4WD trucks with pinch bolt style suspension. For 1/2" drives.



APPLICATIONS

Ford: 1986 - 07 Taurus Sedans
Mercury: 1986 - 07 Sable Sedans

FORD/MERCURY REAR BUSHING ADJUSTING TOOL

87320

Many popular Taurus/Sable sedans utilize our **87330** Rear Camber/Toe Kit (page 132). The **87320** Bushing Adjustment Tool allows easy access to the head of the eccentric bushing to ease adjustment.

