

APPLICATIONS

Dodge/Ram RWD/4WD:
2008 & Up 4500, 5500

Sterling Bullet RWD/4WD:
2008 - 11 4500, 5500

DODGE/RAM PIN JOINT ADJUSTING WRENCH

88360

The 2-3/8" flat hex wrench is designed to make the installation of the **23850**, **23852** and **23854** (page 78) Dodge/Ram pin joints quicker and easier. Use a 1-1/2" socket to hold your adjustment and then tighten the jam nut with this tool.



CAUTION: Not for use with impact wrenches (air tools).

88830 is not recommended for use on Ford Motor Co. original equipment sleeves. Use 77880 (page 168 for OE Sleeves).

FORD/DODGE SLEEVE PULLER (AFTERMARKET)

88830

This puller is designed to work specifically with the **23100** (page 74) sleeves. It will allow the technician to pull the sleeves without normally breaking the ears off the sleeve.



Dual socket inner tie rod removal tool

Fits 1-3/16" or 1-5/16" hex. inner tie rod ends on Fords and Chryslers with TRW racks.

1-3/16" hex tool - for inner tie rod ends on Ford Escort, Tempo, Topaz, Lynx.

1-5/16" hex tool - designed for inner tie rod ends on 1986 - 07 Taurus/Sable.

1-7/16" hex tool - designed for GM Saginaw rack and pinions.

CAUTION: Not for use with impact wrenches (air tools).

INNER TIE ROD END WRENCH SET

89000

Set includes a Dual Socket Inner Tie Rod Removal Tool along with 1-3/16", 1-5/16" and 1-7/16" hex tools.

1-3/16" Hex **1-5/16" Hex** **1-7/16" Hex**



Dual Inner Tie Rod Removal Tool

SPC TAPE MEASURE

High quality 16' tape measure with SPC logo. Included in our Off-Road (91025) and Heavy Duty (91040) FasTrax™, this tape measure also works great for measuring toe with our standard (91000) and our Performance (91010) FasTrax™.



91045



APPLICATIONS

Ford: 1986 - 05 Taurus Station Wagon

Mercury: 1986 - 05 Sable Station Wagon

FORD STATION WAGON REAR TOE TOOL

97650

Taurus and Sable Station wagons have a sprocket type cam to adjust rear toe. This tool engages the sprockets and allows the technician to turn the cam.



APPLICATIONS

99361 extends 46-74 in. for light trucks & cars.

99374 extends 39-60 in. for standard and compact cars.

TOE MEASURING GAUGES

99361 99374

Spring-loaded gauges easily adapt to a variety of tread widths in order to give fast, accurate toe readings.



WHEEL SPREADER

Take the play out of front wheels during alignment! Place this spring-loaded pressure bar between the tires to assure a more accurate alignment. **A must for Mercedes vehicles.**



99918

