Self-Adhering SPRAY BOOTH WALL PROTECTIVE FILM

Clear, non-yellowing, see-through film applies directly over white booth walls and doors.

Easy to handle, lightweight reverse-wound 36" wide roll.

User-friendly Features:

- Strength of adhesive supports weight of roll preventing roll from running down the wall.
- Reverse-wound roll enables wrinklefree, bubble-free application against booth walls.



Eliminates repeated coats of

White booth coatinas!



Product Performance Benefits

- Durable puncture resistant plastic film with UV inhibitor.
- Self-adhering film leaves no adhesive transfer.
- Easy to apply. Easy to cut film with SNIPPET KNIFE or razor blade.
- Remove when desired and apply new film.
- Eliminates labor intensive removal of spray or roll-on peelable coatings!
- Eliminates repeated coats of white booth coating!
- Cuts booth maintenance time in half!
- No mess. No cleaning of spray gun.
- Film resists heat up to 200°F (93.3°C).
- Preserves booth lighting without distortion or deflection.

Average Material Use and Labor Time:

- Quick installation time.
- Booth Size 24' deep x 14' wide x 8' high walls.
- Booth Wall Protection Film required 2 to 2-1/2 rolls.
- Labor Time Required 1-1/2 hours with 2 personnel.

Product Information

Part No.	Description	Units/Case
438	Booth Wall Protective Film Clear 36″ x 100' Roll (.91m x 30.5m)	1 roll
443	Booth Wall Protective Film White 36" x 100' Roll (.91m x 30.5m)	1 roll
442	Booth Wall Protective Film White 48″ x 200' Roll (1.22m x 61m)	1 roll
555	SNIPPET KNIFE	25

Do NOT apply over Lite Box Glass. (Adhesive system is designed for walls only.) Use No. 435 Lite Box Glass Film.



Beginning at one end of the wall, tack down a 2"-3" starter edge at the ceiling break.



Roll down film against wall smoothing as you go to the top of lightbox.



Using a SNIPPET KNIFE or razor blade, cut across film at top edge of lightbox. (Do NOT cover lightbox*.)