### DIAPHRAGM AIR REGULATOR

- For precise air regulation at the spray gun.
- Delivers constant pressure.
- For use with all spray guns conventional and HVLP.
- Small, lightweight and compact.
- Inlet: 1/4" NPT Male; Outlet: 1/4" NPT Female with swivel connector.
- 22 CFM capacity.
- True diaphragm regulator to prevent surges not a cheater valve.
- Push/Pull lock to set pressure.
- Gage ranges: 0-160 PSI and 0-11 BAR.
- Glass lens.



## 99000

## IN-LINE WATER SEPARATOR AND **AIR FILTER**

99000 - Removes water and foreign particles from compressed air stream. Attaches directly to paint spray gun or air tool. Clear reservoir shows accumulated water taken out of air line. Button release valve allows for easy disposal. Filter can be removed and cleaned periodically. 1/4" NPT Male inlet x 1/4" NPT Female outlet.



# AIR ADJUSTMENT VALVE FOR PAINT **SPRAYING**

98300 - Allows for fine regulation of air entering spray gun. Approximately 2½ turns from fully opened to closed valve. Gage has dual scales - 160 PSI and 11 Kg/Cm<sup>2</sup>. Inlet is 1/4" NPT Male. Outlet is 1/4" NPT Female and swivels.



98300

94540

**CARDED** 

#### HOLDING PADS WITH FOUR SURFACE TREATMENT DISCS

· Use to clean and prep surfaces.

• Discs install and remove easily with a quick twisting action.

- Flexible, flanged rubber backer pad connects to 1/4" steel shaft.
- · For use with air and electric tools.

			INCLUDES		
CAT.	SIZE	MAX. RPM	HOLDING PAD	MEDIUM DISCS	COARSE
94540	2"	30,000	94520	2	2
94560	3″	20,000	94530	2	2

Always wear eye, respiratory and face protection when using these products.





**CARDED** 

HOLDING PADS FOR SURFACE TREATMENT DISCS

· Holds the discs used for prepping surfaces.

- Discs install and remove easily with a quick twisting action.
- Flexible, flanged rubber backer pad connects to 1/4" steel shaft.
- · For use with air and electric tools.
- Holding Pad can be used with most brands of surface treatment pads.

CAT. NO.	SIZE	MAX. RPM
94520	2″	30,000
94530	3″	20,000

Always wear eye, respiratory and face protection when using these products.

94520 94530

