

Proper preparation is the foundation to a quality repair. *SEM* prep products are specifically designed for each substrate to eliminate contaminants & maximize adhesion of top coats & repair materials.

SEM SOAP

Mild abrasive cleaner used as the first step in refinishing flexible substrates.

- Gravitates into surface & floats contaminants for easy removal
- Mild abrasive helps with adhesion
- Foaming action removes body oils & other water soluble contaminants

Suitable Substrates:

- Vinyl
- Leather
- Plastic

PART#	SIZE
39362	16 oz. Tube



VINYL PREP

Strong solvent blend critical to refinishing vinyl.

- Removes oil, wax & grease
- Temporarily softens substrate
- Works quickly

Suitable Substrates:

- Vinyl

PART#	SIZE
38343	16 oz. Aerosol
38344	Quart



PLASTIC & LEATHER PREP

A mild solvent blend to clean plastic & leather prior to refinishing.

- Removes mold release, fingerprints, grease & oil
- Will not soften or distort plastic parts
- Easy to use

Suitable Substrates:

- Plastic
- Leather
- Carpet & Velour

PART#	SIZE
38351	Gallon
38353	16 oz. Aerosol
38354	Quart



XXX UNIVERSAL GUN CLEANER

Quickly removes solvent-based & waterborne coatings from spray equipment.

- Removes waterborne or solvent-based paint & overspray
- 100% virgin solvent formula
- 2-in-1 cleaner reduces products needed in collision center

PART#	SIZE
77763	20 oz. Aerosol



SCUFF & CLEAN

An abrasive paste that cleans & prepares panels for repair or refinish. Improved formula provides better sudsing, easier rinsing & no settling.

- Perfect for bumper covers
- Removes wax, grease, & road grime
- Uniform scratch improves top coat adhesion
- Easier rinsing
- No shaking or stirring necessary

Suitable Substrates:

- Primed or painted surfaces
- Raw plastic

PART#	SIZE
38391	Gallon Pump
38398	16 oz. Tube



SEM SOLVE

A virgin solvent blend to clean panels prior to refinish or repair.

- Removes wax, grease, road tar, oil, silicone, paint overspray & bug remnants
- Easy to use
- Leaves no residue

Suitable Substrates:

- Bare metal
- Primed or painted surfaces
- SMC & plastic – limit exposure

PART#	SIZE
38371	Gallon
38373	20 oz. Aerosol
38374	Quart
38375	5 Gallon



SPRAYABLE SEAM SEALER GUN CLEANER

Blend of solvents to help clean one-component sprayable seam sealer applicators.

- High strength virgin solvent blend
- Does not contain chlorinated solvents
- Perfect when changing sealer colors
- Attached straw for tight areas

PART#	SIZE
29433	20 oz. Aerosol



XXX UNIVERSAL SURFACE CLEANER

Compliant, waterborne cleaner that removes solvent & water soluble contaminants prior to refinishing.

- 2-in-1 cleaner reduces products needed in collision center
- Helps eliminate static for improved metallic orientation & reduced dust contamination
- Solvent strong in waterborne formula
- Exceptional grease-cutting power

Suitable Substrates:

- Primed or painted surfaces
- Vinyl
- Aluminum
- Leather
- Plastic
- Bare Steel

PART#	SIZE
77771	Gallon
77774	Quart



XXX UNIVERSAL ADHESIVE REMOVER

Mild solvent blend used to remove adhesive residue left by tapes, decals & body molding as well as dirt, road tar, sap, wax, silicone, grease, oil & bugs from interior or exterior surfaces.

- Quick acting formula dissolves adhesive residue, tar & more
- Will not damage thoroughly cured paint when used as directed
- Will not soften, discolor, or distort plastic, vinyl, or fabric when used as directed

Suitable Substrates:

- Plastic
- OEM & refinished panels
- Bare aluminum & steel
- Vinyl
- Leather
- Glass

PART#	SIZE
77783	16 oz. Aerosol
77784	Quart



Plastic Refinishing

STANDARD OPERATING PROCEDURE

1 CLEAN



Clean with **SEM Soap** & a gray scuff pad. Scrub thoroughly, paying close attention to textured or recessed areas. Wipe with a clean, damp, lint-free cloth to remove all residue.

2 PREP



Apply **Plastic & Leather Prep**, **SEM Solve** or **XXX Universal Surface Cleaner**.

Wipe clean in one direction using a clean, lint-free cloth.

- ❗ **Wiping in one direction** will remove contaminants from the surface rather than smearing contaminants over the surface.
- ❗ If contamination still exists, water will bead on the surface when dry. Repeat steps 1 & 2 until beading no longer occurs.

3 DETERMINE THE CORRECT ADHESION PROMOTER

A **Sure-Coat** waterborne coating is not compatible with **Sand Free Adhesion Promoter**.

If applying **Sure-Coat** waterborne coating on ABS, do not use an adhesion promoter.

B When using **Bumper Coater** flexible coating, an adhesion promoter is not required, with the exception of **Low VOC Bumper Coater** flexible coating.

Place a drop of acetone on the back of the plastic. Rub with your gloved finger.

If the plastic smears & melts, it is ABS. Use **Sand Free Adhesion Promoter**.

Apply a medium wet coat of **Sand Free Adhesion Promoter**. See note **A**.

While still wet, apply a light coat of **Color Coat**. Avoid applying the first coat too heavily as sagging may occur.

As the **Sand Free Adhesion Promoter** evaporates, **Color Coat** flexible coating is drawn into the surface resulting in excellent adhesion.

If the acetone does not have an effect on the plastic, use **XXX Adhesion Promoter** or **Plastic Adhesion Promoter**. See note **B**.

Apply one medium wet coat of **XXX Adhesion Promoter** or **Plastic Adhesion Promoter**. Allow to flash 3 – 5 minutes before topcoating.

4 PAINT



Apply **Bumper Coater** flexible coating, **Color Coat** flexible coating, **Sure-Coat** flexible coating, **Trim Black**, or **Trim Black Ultra** trim paint.

PRODUCT LIST

CLEAN & PREP

PART#	PRODUCT	SIZE
38351	Plastic & Leather Prep	Gallon
38353	Plastic & Leather Prep	16 oz. Aerosol
38354	Plastic & Leather Prep	Quart
38371	SEM Solve	Gallon
38373	SEM Solve	20 oz. aerosol
38374	SEM Solve	Quart
39362	SEM Soap	16 oz. Tube
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart

Clean & Prep products - See page 2.

ADHESION PROMOTERS

PART#	PRODUCT	SIZE
38363	Sand Free Adhesion Promoter	16 oz. Aerosol
38364	Sand Free Adhesion Promoter	Quart
39861	Plastic Adhesion Promoter	Gallon
39863	Plastic Adhesion Promoter	16 oz. Aerosol
39861	Plastic Adhesion Promoter	Quart
77721	XXX Adhesion Promoter	Gallon
77723	XXX Adhesion Promoter	16 oz. Aerosol
77724	XXX Adhesion Promoter	Quart

Adhesion Promoter products - See page 19.


PAINT

Bumper Coater products - See page 20.

Color Coat products - See page 22 – 24.

Sure-Coat products - See page 24 – 25.

Trim Black products - See page 31



Order a copy of the Interior & Exterior Refinishing booklet at semproducts.com

CHECK LOCAL VOC REGULATIONS TO ENSURE COMPLIANCE OF ALL PRODUCTS IN YOUR AREA. ALWAYS WEAR OSHA REQUIRED (PPE) PERSONAL PROTECTION EQUIPMENT TO ENSURE YOUR SAFETY.

Leather Refinishing

STANDARD OPERATING PROCEDURE



1 CLEAN


Clean with **SEM Soap** & a gray scuff pad. Scrub thoroughly, paying close attention to textured or recessed areas. Wipe with a clean, damp cloth to remove all residue.



2 PREP


Apply **Plastic & Leather Prep** or **XXX Universal Surface Cleaner**. Wipe clean in one direction using a damp, lint-free cloth.

- ❗ Wiping in one direction will remove contaminants from the surface rather than smearing contaminants over the surface.
- ❗ If contamination still exists, water will bead on the surface when dry. Repeat steps 1 & 2 until beading no longer occurs.



3 FINAL PREP

Scuff the leather with a clean, gray scuff pad or P400 – P600 grit sandpaper. Blow off dust & clean again with **Plastic & Leather Prep**.



4 PAINT

Apply **Sure-Coat** flexible coating or **Classic Coat** flexible coating.

PRODUCT LIST

CLEAN & PREP


PART#	PRODUCT	SIZE
38351	Plastic & Leather Prep	Gallon
38353	Plastic & Leather Prep	16 oz. Aerosol
38354	Plastic & Leather Prep	Quart
39362	SEM Soap	16 oz. Tube
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart

Clean & Prep products - See page 2.

PAINT

Classic Coat products - See page 22.

Color Coat products - See page 22 – 24.



Order a copy of the Interior & Exterior Refinishing booklet at semproducts.com

CHECK LOCAL VOC REGULATIONS TO ENSURE COMPLIANCE OF ALL PRODUCTS IN YOUR AREA. ALWAYS WEAR OSHA REQUIRED (PPE) PERSONAL PROTECTION EQUIPMENT TO ENSURE YOUR SAFETY.