

Rust Preventer Cavity Wax

STANDARD OPERATING PROCEDURE

RESTORES OEM CORROSION PROTECTION

Rust Preventer Cavity Wax is easily applied with a 360° spray pattern when using the Premium Undercoat Gun & Spray Wand or the Rust Preventer Aero Wand.

- ! Do not spray without tip being inserted into inner panel access point.

PREP & APPLY AEROSOL



Clean surface with **SEM Solve** or **XXX Universal Surface Cleaner** where applicable. Remove cap from **Rust Preventer Cavity Wax**, attach straw or **Rust Preventer Aero Wand**. Apply 1 – 2 coats.

- ! Change angle & depth of the tip inside panel to ensure coverage.

PREP & APPLY QUART



Clean surface with **SEM Solve** or **XXX Universal Surface Cleaner** where applicable. Shake bottle of **Rust Preventer Cavity Wax** for 1 minute. Spray 1 – 2 coats at 35 – 45 psi.

- ! Change angle & depth of the tip inside panel to ensure coverage.

CLEAN WAND



Clean **Rust Preventer Aero Wand** by attaching the tip & wand to **XXX Universal Gun Cleaner**.

Clean **Premium Undercoat Gun & Spray Wand** with **XXX Universal Gun Cleaner**.

CHECK LOCAL VOC REGULATIONS TO ENSURE COMPLIANCE OF ALL PRODUCTS IN YOUR AREA. ALWAYS WEAR OSHA REQUIRED (PPE) PERSONAL PROTECTION EQUIPMENT TO ENSURE YOUR SAFETY.



SEM undercoatings eliminate headaches caused by poor performance of low quality products. Our rubberized products offer exceptional color & texture without bleed through. Our asphalt-based products give fantastic coverage & dry times at an economic price.

RUBBERIZED UNDERCOATING

Premium, single component, paintable, textured coating for sound dampening, chip resistance, rust protection & corrosion protection.

- OEM recommended
- Uniform final appearance
- Quality asphalt-free formula
- Paintable without bleed through
- Sound-dampening properties
- Aerosol includes straw for tight spots
- Fast-drying
- Chip & corrosion resistant



PART#	COLOR	SIZE
39513	White (EU only)	24 oz. Aerosol
39523	Black	24 oz. Aerosol

UNDERCOATING

Non-paintable, asphalt-based aerosol coating for corrosion protection, chip resistance & sound dampening on automotive frames, wheel wells & undercarriage areas.

- Uniform appearance
- Excellent adhesion
- Economical



PART#	COLOR	SIZE
39463	Black	24 oz. Aerosol

LOW VOC UNDERCOATING

VOC Compliant

Asphalt-based, aerosol coating for corrosion protection, chip resistance & sound dampening on frames, wheel wells & undercarriage areas.

- Uniform appearance
- Excellent adhesion
- Economical



PART#	COLOR	SIZE
40463	Black	24 oz. Aerosol

LOW VOC RUBBERIZED UNDERCOATING

VOC Compliant

Premium, easy to apply, paintable, asphalt-free coating for sound dampening, chip resistance, rust & corrosion protection.

- OEM recommended
- Paintable without bleed-through
- Pinhole free
- 100% asphalt free
- Sound-dampening properties
- Chip & corrosion resistant
- Aerosol includes straw for tight spots



PART#	COLOR	SIZE
40523	Black	24 oz. Aerosol



BUILT BETTER™

Every day.

Collision centers, restoration shops & DIYers trust **SEM's** OEM recommended products to reduce repair time, steps & waste in every application.

Every day.

We relentlessly pursue excellence. We innovate and we improve.

We are American manufacturing.

