

Check local VOC regulations to ensure compliance of all products in your area.

DESCRIPTION

2-IN-1 Seam Sealer is a beadable and sprayable, high performance, one-component MSP seam sealer for interior or exterior seams and OEM sprayed sound-dampening pads.

FEATURES

- OEM recommended
- Optimized viscosity for beading, spraying or brushing
- Direct to metal
- Paintable immediately with most solvent-based coatings
- Permanently flexible without shrinking, cracking or peeling
- Colors matched to OEM seam sealers
- Weather and corrosion resistant
- Resistance weldable (STRSW)
- · UV stable, non-yellowing formula
- · Contains no solvents or isocyanates
- · Excellent adhesion to many substrates

SUITABLE SUBSTRATES - PROPERLY PREPPED

• Primed or painted surfaces

Glass

• Aluminum

Concrete

Steel

Wood

Fiberglass

Plastic

• SMC

TYPICAL PROPERTIES

| Part: | Product Name: | Color: | Container: | |
|--------------------------|--------------------|-----------------------------------|--------------|--|
| 29462 | 2-IN-1 Seam Sealer | White | 9.5 oz. Tube | |
| 29472 | 2-IN-1 Seam Sealer | Gray | 9.5 oz. Tube | |
| 29482 | 2-IN-1 Seam Sealer | Beige | 9.5 oz. Tube | |
| 29492 | 2-IN-1 Seam Sealer | Black | 9.5 oz. Tube | |
| Working Time: | | 20 – 40 minutes @ 70°F (21°C) | | |
| Set Time: | | 1 hour @ 70°F (21°C) | | |
| Paint Time (Solvent): | | 0 – 24 hours @ 70°F (21°C) | | |
| Paint time (waterborne): | | 1 hour @ 70°F (21°C) | | |
| Cure time: | | 4mm/24 hours @ 70°F (21°C)/50% HR | | |

Check local VOC regulations to ensure compliance of all products in your area.

2-IN-1 Seam Sealer should be stored in a cool, dry place with adequate ventilation, away from heat, sparks and flames. The shelf life for **2-IN-1 Seam Sealer** is 18 months when stored under normal conditions.

RELATED PRODUCTS:

| Part: | Product Name: | Size: |
|-------|-------------------------------------|----------------|
| 29312 | 1K Doorskin Nozzles | 6 Pack |
| 29322 | 1K Extrusion Nozzels | 6 Pack |
| 29342 | 1K Pneumatic Applicator | Each |
| 29442 | 1K Sprayable Seam Sealer Applicator | Each |
| 38351 | Plastic & Leather Prep | Gallon |
| 38353 | Plastic & Leather Prep | 16 oz. Aerosol |
| 38354 | Plastic & Leather Prep | Quart |
| 38371 | SEM Solve | Gallon |
| 38373 | SEM Solve | 20 oz. Aerosol |
| 38374 | SEM Solve | Quart |
| 38375 | SEM Solve | 5 Gallons |
| 77771 | XXX Universal Surface Cleaner | Gallon |
| 77774 | XXX Universal Surface Cleaner | Quart |

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate. Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.