

SEM[®] **1K SEAM SEALING** STANDARD OPERATING PROCEDURE

PREP	Clean with SEM Solve or XXX Universal Surface	PRODUCT LIST
	Cleaner . Wipe clean in one direction with a dry, lint-free cloth.	
2 SAND	Sand bare metal with P180 grit or use red scuff pad on OEM or e-coat finish. Blow off and re-clean with SEM Solve or XXX Universal Surface Cleaner . Tack clean. Mask off area to create clean lines.	PartProductSize38371SEM SolveGallon38373SEM Solve20 oz. Aerosol38374SEM SolveSquare Quart77771XXX Universal Surface CleanerGallon77774XXX Universal Surface CleanerQuart
3 APPLY	Apply 1K Seam Sealer using 1K Pneumatic Applicator or a manual applicator. Finish with a gloved finger, acid brush, putty knife, or spreader. While product is wet, remove excess by wiping with a small amount of SEM Solve .	Image: State of the state
4 PAINTABLE IMMEDIATELY	 Remove masking tape immediately after clean up. Paint immediately with Factory Pack[™] or most solvent-based coatings. (i) Can be painted for up to 24 hours without scuffing. If in doubt, scuff with gray pad prior to painting. 	29362 White 10.1 oz. Tube 29372 Gray 10.1 oz. Tube 29382 Beige 10.1 oz. Tube 29392 Black 10.1 oz. Tube
	 1K Seam Sealers are paintable immediately with most solvent-based coatings, however, always test for compatibility. 1 Do not apply 1K Seam Sealer directly over acid-based self-etching primers or vice versa. Cracking and blistering may occur. 	EQUIPMENT Part Product Size 29342 1K Pneumatic Applicator 1 Applicator 29352 1K Seam Sealer Nozzle 15 Pack
<section-header></section-header>	WATCH THE VIDEO AT: semproducts.com/sop-1k-seam- sealer	PAINTProductSizeFactory Pack - 40 Colors16 oz. AerosolSee back side for available Factory Pack colors.SEM Products, Inc.Rock Hill, SC 29730Tech Support: 1-800-831-1122Customer Care: 1-866-327-7829semproducts.com

CHECK LOCAL VOC REGULATIONS TO ENSURE COMPLIANCE OF ALL PRODUCTS IN YOUR AREA. ALWAYS WEAR OSHA REQUIRED (PPE) PERSONAL PROTECTION EQUIPMENT TO ENSURE YOUR SAFETY. (**i**)



SEM[®] **1K SEAM SEALER STANDARD OPERATING PROCEDURE I** PRODUCT LIST CONTINUED

PRODUCT LIST



FACTORY PACK[™]

16 OZ AEROSOLS		
Part	Color	
19013	Ford TS Silver Frost	
19023	Ford YZ White	
19033	Ford CX Dk Shadow Grey	
19043	Ford G2 Redfire Pearl	
19053	Ford FL Torreador Red Metallic	
19063	Ford G3 Pueblo Gold	
19073	Ford E4 Vermillion	
19083	Ford DX Dk Blue Pearl	
19093	Ford YN Silver Metallic	
19103	Ford UA Black	
19133	Honda B537M Atomic Blue	
19143	Honda B92P Black Pearl	
19163	Honda NH700M Alabaster Silver	
19173	Honda YR538M Desert Mist Metallic	
19183	Honda B536P Royal Blue Pearl	
19193	Honda NH737M Polished Gray Metallic	
19203	Honda R81 Milano Red	
19213	Honda R525P Tango Red	
19223	Honda NH578 Taffeta White	
19233	Honda YR573M Mocha Metallic	
19253	Toyota 1C0 Millenium Silver	
19263	Toyota 1C8 Lunar Mist Metallic	
19273	Toyota 1E3 Phantom Gray	
19283	Toyota 040 Super White	
19293	Toyota 202 Black	
19303	Toyota 1D4 Titanium	
19313	Toyota 4Q2 Desert Sand Pearl	
19323	Toyota 056 Natural White	
19353	Toyota 3R3 Red Pearl	
19363	Toyota 1G3 Magnetic Gray Pearl	
19373	GM WA8554 White	
19393	GM WA9260 Victory Red	
19403	GM WA8624 Olympic White	
19423	GM WA8555 Black	
19433	GM WA994L Lt Tarnished Silver	
19443	GM WA519F Galaxy Silver Metallic	
19453	GM WA929L Cashmere	
19463	GM WA722J Dk Blue Metallic	
19473	GM WA382E Pewter Metallic	
19483	GM WA316N Gold Mist Metallic	



For a crossover list of Factory Pack colors, refer to **OEM Refinishing System™** literature at:

semproducts.com/factory-pack