

Model	Application	Hose Capacity			Max. Working Pressure Bare Reel, psi	Inlet/Outlet (f)
		Rating	Type	Max. Length		

BARE REEL SPECIFICATIONS

94100	Air, A-F, Water, WW	RMA	Class A	60'	1000*	1/2" NPTF
94300	Oil	SAE100R3	73	60'	2500*	1/2" NPTF
94500	Grease	SAE100R2	75, 76	50'	8000*	3/8" NPTF

* Note: Actual working pressure of the reel should not exceed pressure rating of the installed hose. 60' hose should be used on installations allowing for a 10' to 12' hose hand down.

Model	Description	Included with Reel Assemblies				
		Bare Reel Model	Delivery Hose	Connecting Hose	Ball Stop	Control Valve or Meter

HIGH PRESSURE REELS & ASSEMBLIES

GREASE REEL AND HOSE ASSEMBLIES

94532	1/4" x 30'	94500	75360	75024	85515	NA
94552	1/4" x 50'	94500	75600	75024	85515	NA
94553	3/8" x 50'	94500	76600B	75024	85516	NA

GREASE ASSEMBLIES with Universal Swivel & Control Valve

94532G	1/4" x 30'	94500	75360	75024	85515	81387 & 740
94552G	1/4" x 50'	94500	75600	75024	85515	81387 & 740
94553H	3/8" x 50'	94500	76600B	75024	85516	81729 & 3050

MEDIUM PRESSURE REELS & ASSEMBLIES

OIL REEL AND HOSE ASSEMBLIES

94334	1/2" x 30'	94300	73360	73024	85517	NA
94354	1/2" x 50'	94300	73600	73024	85517	NA
94364	1/2" x 60'	94300	73720	73024	85517	NA

LOW PRESSURE REELS & ASSEMBLIES

AIR, WATER REEL AND HOSE ASSEMBLIES

94132	1/4" x 30'	94100	72360	74024	85515	NA
94133	3/8" x 30'	94100	72360A	74024	85516	NA
94152	1/4" x 50'	94100	72600	74024	85515	NA
94153	3/8" x 50'	94100	72600A	74024	85516	NA
94154	1/2" x 50'	94100	74600	74024	85515	NA
94163	3/8" x 60'	94100	74720	74024	85516	NA

AIR ASSEMBLIES with Air Coupler & Tire Chuck

94132A	1/4" x 30'	94100	72360	74024	85515	815/11659/66951
94133A	3/8" x 30'	94100	72360A	74024	85516	815/11659/66951
94152A	1/4" x 50'	94100	72600	74024	85515	815/11659/66951
94153A	3/8" x 50'	94100	72600A	74024	85516	815/11659/66951
94154A	1/2" x 50'	94100	74600	74024	85517	815/11659/66951

WATER ASSEMBLIES with Water/Antifreeze Bibb Cock

94132W	1/4" x 30'	94100	72360	74024	85515	846 Bibb Cock
94133W	3/8" x 30'	94100	72360A	74024	85516	846 Bibb Cock
94152W	1/4" x 50'	94100	72600	74024	85515	846 Bibb Cock
94153W	3/8" x 50'	94100	72600A	74024	85516	846 Bibb Cock
94154W	1/2" x 50'	94100	74600	74024	85517	846 Bibb Cock

Pressure Application	Hose Diameter	Max. Working Pressure psi (bar)
High	1/4"	5,000 (340)
	3/8" & 1/2"	4,000 (272)
Medium	1/2"	1,500 (102)
Low	1/4" & 3/8"	250 (17)
	1/2"	200 (13.6)

I-Beam Clamp Model 85654

The I-beam clamp accessory allows users to easily mount the 94000 series reels to existing I-beams.

