
Lubrication Fittings & Accessories

Remote Lube Fitting Systems





Tube Connectors

Part No.	Style	Α	В	Туре
66200	1	1⁄4" O.D.	⅓" NPT	STGT
66201	1	1⁄4" O.D.	⅓" NPT	90°
66414	2	1∕8" O.D.	⅓" NPT	90°
66415	2	1/8" O.D.	⅓" NPT	STGT
66714	2	1/8" O.D.	1/4"-28 thd.	STGT
66716	2	1/8" O.D.	1/4"-28 thd.	90°



Compression Nut

No. 66260 for use with Style 2 Tube Connectors and 66717 Swivel. For $\frac{1}{8}$ " O.D. Tubing. Thread size is $\frac{5}{16}$ "-24.




Sleeve

No. 68462 for use with Style 1 Tube Connectors. For $\frac{1}{4}$ " O.D. Tubing.



Nut


No. 68464 for use with Style 1 Tube Connectors. For ¼" O.D. Tubing.



Zerk-Lock® Grease Fitting Adapter

Connects any 1/8" NPTF male tube adapter directly to a standard grease fitting. Aluminum, carbon steel construction; fluorocarbons elastomer seal. Useful for connecting to drive-type fittings or metric fittings. Once installed, the Zerk-Lock cannot be removed from the fitting.

Part	Threads in. / mm	A	B	C
No.		in./mm	in./mm	in./mm
270784	1/8" NPSL Female	.625 / 15.9	.500 / 12.7	.500 / 12.7



Installation Accessories



No. 247615 Staking Tool