



Divider Valve Outlet Closure Plug

Model No.	Description
303-17499-3	Valve outlet closure plug (gasket not required)
303-19346-2	Stainless steel outlet closure plug (gasket not required)

1/8" Supply and Feed Line Hose

Min. Burst	Lube Working Pressure	Nominal Size		Minimum Bending Radius	Construction	Temp.
		ID	OD			
10,000 psig 690 bar	4000 psig 276 bar	1/8"	5/16"	3 1/2"	Nylon Tube Dacron Braid Polyurethane Cover	-40°F to +212°F

Model No.	Description (1/8" ID hose)
241286	26 ft. (7.92 m) coil grease filled
241287	35 ft. (10.66 m) coil grease filled
241288	40 ft. (12.19 m) coil grease filled
252717	200 ft (60.96 m) coil non-grease filled
277226	2250 ft. (685.8 m) spool non-grease filled
276395	40 ft. (12.19 m) grease filled with quick wrap protection installed on hose

Hose Ends for Use with Quickline Fittings for 1/8" ID Hose

Model No.	Description
272394	Hose stud, 90° (to be used with 272427)
272401	Hose stud, straight (to be used with 272427)
272427	Threaded sleeve
274238	Stainless steel hose stud sleeve
274239	Stainless steel straight hose

Hose Ends for 1/8" I.D. Hose

Model No.	Description
241289	1/8" NPT swedge on hose stud (Requires swedging tool)
246002	1/8" NPT field installable hose coupling (swedging tool not required)
276954	1/8" NPT swedge on hose fitting with swivel (requires swedging tool)

Hose End Connecting Tools

Model No.	Description
241238	Hose Swedging Tool
274062	Hand vise for quick connect and reusable hose ends

Feed Line Nylon Tubing

Model No.	Description	O.D. In.	Wall Thickness in. / mm	Working Pressure		Minimum Bending Radius	Temp.
				psig	bar		
242025	25 ft./7.6 m coil grease filled	1/4" black	.050 / 1.27	625	42.5	.875 / 22.2	-65°F to +150°F
242050	50 ft./15.2 m coil grease filled						
62357	100 ft./30.5 m coil non-grease filled						
247022	500 ft./152.40 m coil non-grease filled						
274047	25 ft./7.6 m coil grease filled	1/4" grey	.062 / 1.575	500	34.5	0.5 / 12.7	-65°F to +200°F
274048	50 ft./15.2 m coil grease filled						
274049	100 ft./30.5 m coil non-grease filled						
274050	500 ft./152.4 m coil non-grease filled						

NOTE: Burst pressure 2500 psi (172 bar)

