

### PS2000

### **Power Steering Hose Repair Kit**

S.U.R.&R. EXCLUSIVE



## Double Braided Hose Pressure: Rated up to 6,000 PSI



- Working Pressure 1,500 PSI, Burst Pressure 6,000 PSI
- Temperature Range ( $-40^{\circ}$  F to  $+250^{\circ}$  F,  $-40^{\circ}$  C to  $+121^{\circ}$  C)
- Exceeds SAE J188 Type 1 Specifications

# Repair High And Low Pressure Power Steering Lines

- Use to make 5/16" and 3/8" line repairs
- On-the-car repairs made easy
- 95% coverage (domestic and foreign)
- Universal can be used to repair hundreds of different line types
- Use for power steering lines, clutch, industrial and heavy duty applications
- Includes 6", 12", 18", 24" and 30" lines –
   Oty 1 of each



Heavy-duty compression connections that feature "double-seal" technology with o-ring and interchangeable ferrule

#### Repair Leaking Hoses In Minutes



Leaking hose at collar

PROBLEM SOLVED: With new Power Steering Hose

# 5 Hoses & 2 Ferrules

### **Easy Installation**



**Cut Tubing** 

Push hose onto line

Tighten with wrenches

1.800.390.3996 • phone: 330.745.3300 • fax: 330.745.3488 • www.surrauto.com

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

### **KITS CONTENTS**

#### **Power Steering Hose**

IMAGE	PART#	KITS/ QTY	LINE SIZE	DESCRIPTION	REORDER QTY
	PS16	1	3/8" or 5/16"*	3/8" x 6" Power Steering Hose	1/pkg
	PS112	1	3/8" or 5/16"*	3/8" x 12" Power Steering Hose	1/pkg
	PS118	1	3/8" or 5/16"*	3/8" x 18" Power Steering Hose	1/pkg
	PS124	1	3/8" or 5/16"*	3/8" x 24" Power Steering Hose	1/pkg
	PS130	1	3/8" or 5/16"*	3/8" x 30" Power Steering Hose	1/pkg

<sup>\*</sup> Lines include 3/8" ferrules which can be replaced with interchangeable 5/16" ferrules (sold separately)

#### **Compression Union Ferrule**

IMAGE	PART#	KITS/ QTY	LINE SIZE	DESCRIPTION	REORDER QTY
	PS810	2	5/16"	5/16" Compression Union Ferrule	2/pkg