


15800 TOYOTA SERPENTINE BELT WRENCH Double-ended wrench design accesses the serpentine belt tensioner without having to lift the car and remove the wheel and splash shield. A 19mm 12-point deep socket, 14mm 12-point shallow clearance socket and the bend angles of the wrench handle allow for precise access to the fasteners.

Applications: TOYOTA & SCION 2GR-FE, 2AZ-FE, 2AR-FE, 1AR-FE, & other engines



60100A HONDA AND ACURA 4" OFFSET HARMONIC DAMPER PULLEY HOLDING TOOL (50mm) Aids in the removal and installation of the crank bolt on most Honda and Acura engines. In operation with the use of a 1/2" breaker bar or ratchet this tool holds the harmonic damper pulley from rotating when removing the pulley bolt. There is an opening in the center of the tool to allow the use of a socket and extension to break loose or tighten the pulley bolt.

Applications:

HONDA

Accord	2.2L 4 cyl.	90-97
	2.7L V6	96-97
	2.3L 4 cyl.	98-02
	2.4L 4 cyl.	03&later
	3.0L V6	98-07
	3.5L V6	08&later
Accord Hybrid	3.0L V6	05-07
Civic	1.6L 4 cyl.	92-00
	1.7L 4 cyl.	01-05
	1.8L 4 cyl.	06&later
	2.0L 4 cyl.	03&later
Civic Hybrid	1.3L 4 cyl.	03&later
CRV	2.0L 4 cyl.	97-01
	2.4L 4 cyl.	02&later

HONDA

Del Sol	1.6L 4 cyl.
Element	2.4L 4 cyl.
Fit	1.5L 4 cyl.
Insight	1.0L 3 cyl.
Odyssey	2.2L 4 cyl.
	2.3L 4 cyl.
	3.5L V6
Pilot	3.5L V6
Prelude	2.2L 4 cyl.
	2.3L 4 cyl.
Ridgeline	3.5L V6
S2000	2.0L 4 cyl.
	2.2L 4 cyl.

93-97

CL

03&later

07&later

00&later

95-97

Integra

98

99&later

03&later

92-01

Legend

92-96

MDX

06&later

RDX

00-03

RL

04&later

RSX

TL

TSX

ACURA

2.2L 4 cyl.

97

3.0L V6

97-99

2.3L 4 cyl.

98-99

3.2L V6

00-03

1.6L 4 cyl.

90-92

1.7L 4 cyl.

92-93

1.8L 4 cyl.

93-01

3.2L V6

91-95

3.5L V6

01-06

3.7L V6

07 & later

2.3L 4 cyl. turbo

07 & later

3.5L V6

96 & later

2.0L 4 cyl.

02-07

3.2L V6

97 & later

3.5L V6

07 & later

2.4L 4 cyl.

04 & later



61200 2-PIECE FAN CLUTCH WRENCH KIT Specially designed contoured water pump holder for easy use on vehicles using bolt-on water pump pulleys, to remove and replace the viscous fan clutch. The new water pump holding tool replaces all designs of water pump holding tools for "bolt on type pulleys". Simple one hand use, hook on the pulley bolt and hold to remove the viscous fan clutch. Reverse the 61600 to install the fan clutch.

Applications: Chrysler, GM, Ford, Land Rover and Mazda (Not including the 4.9L 6 cylinder Ford).



61600 see page 16

95210 see page 28

Same as discontinued 62020 without rack

61260 3-PIECE FAN CLUTCH WRENCH KIT U.S. PATENT 6,912,936

This three-piece kit (includes 61600, 95210 & 95260) gives the professional technician the ability to service all fan clutches that have bolt-on pulleys on the water pump.

Applications: Chrysler, GM, Ford, Land Rover and Mazda applications. (Includes the 4.9L 6 cylinder Ford).



61600 see page 16

95210 see page 28

95260 see page 29

*61500B FAN CLUTCH WRENCH

The four strengthened chromolly billet bulkhead pins in this tool give the professional technician greater durability than tools presently available on the market. These pressed on pulleys have holes instead of bolt heads for use in securing the pulley from rotating while removing or installing the fan clutch assembly. With the use of a 48mm open-end wrench (part 95210) the technician can loosen and tighten the fan clutch on many 2000 and later GM trucks.

Applications:



GM	6.5L diesel	2000-2001
Isuzu Duramax	6.6L diesel	2001-2005
Isuzu Duramax with new pin straight slot fan		

*Available In A Kit See Page 31 6.6L diesel 2006 & later

*61600 FAN CLUTCH WRENCH U.S. PATENT 6,912,936

Universal fan clutch wrench works with all "BOLT ON" water pumps that have bolts holding the pulley on the pump. 95260 40mm use with 61600 for 1992-1996 Econoline Vans, 1993-1996 F Series Pickup trucks, with 4.9L engines.



*Available In A Kit See Page 31

62100 AUDI, BMW & VW FAN CLUTCH WRENCH

U.S. PATENT 6,912,936 The 62100 is used to loosen and tighten the fan clutch. Can be used with the 61600 for all water pumps that have bolts holding the pulley on the pump.

Applications: 62100 32mm works with 61600 Fan Clutch

Audi

*Except press on pulleys 1996 & later

BMW

3, 5, 6-8, X & Z series *Except 4.0L & 4.4L V8 engines
4.0L & 4.4L V8 with bolt on water pump pulleys

VW

Works with 11250 Fan Clutch 1998 & later

*Except pressed on pulleys



62800 GM HARMONIC DAMPER HOLDING TOOL

Aids in the removal and installation of the crank bolt. The bolts holding these pulleys are extremely tight and removal is extremely difficult at best. In replacing the center bolt after installation of the pulley, factory specifications require up to 240 lbs. of torque to seat the pulley properly. This tool allow the factory torque to be attained. (Refer to factory specifications for specific requirements.)

Applications:

GM LS One Gen. III	5.7L V8	1997 & 2004
---------------------------	----------------	------------------------



63100 BMW "A" ARM THRUST BUSHING WRENCH

This narrow access wrench allows the technician to hold the not with 12-point positioning. Having the box-end feature allows a strong hold for quick removal of the bushing bolt.

Applications:

22mm 5-7 Series 1988-1996

21mm 5-7 Series 1996-2001



*63800 CAM SEAL INSTALLER Replace and install the cam seals in 4 & 6 cylinder engines. Place threaded rod screws into the cam end, slides over the rod against the seal then the seal is pressed in using the nut provided.

Applications:

Mazda, Nissan, Toyota & Lexus 4 & 6 cylinder engines with 10mm & 12mm X 1.25 cam bolts



*See Replacement Parts Page 43-44

93260 FAN CLUTCH WRENCH 36mm

Works with most gas and diesel viscous fan clutches, with a 36mm hex holding the viscous fan clutch to the water pump.



Applications: Chrysler, Ford, GM, Jeep, Land Rover and Mazda, with 36mm Hex

93750B OFFSET 2-1/8" SUPER DUTY 12- AND 6-POINT OXYGEN SENSOR WRENCH

Completely updated 12 point and 6 point SP Spline Grip Drive giving the technician the ultimate tool to remove oxygen sensors in confined areas.

Applications: 22mm non-shielded oxygen sensor wire/connectors

Corvette	LT1 Gen II 5.7L HO MPFI V8	1992 & later
Camaro		1993 & later
Firebird/Trans Am		1993 & later
Corvette ZR1	LT5 5.7L DOHC SFI V8	1989 & later
All Harley Davidson Motorcycles		2007 & later




93480 GM TRANSMISSION SEAL REMOVAL AND INSTALLATION TOOL

Removes and replaces the shift selector shaft seal on GM transmissions. Disconnect linkage from the shaft end, slide remover over the shaft until the threads engage with the seal. Rotate the remover clockwise using pressure. Insert remover bolt into the center of the remover, tighten the bolt to extract the seal. Slide the new seal over the selector shaft up to the transmission. Place the installer tube over the selector shaft and using a soft face hammer, tap in the new seal.



94170A BELT IT "SERPENTINE, V-BELT AND TIMING BELT INSTALLATION ASSIST"

This time saving tool gives the technician the control and reach when installing serpentine belts in all applications. Also helps install V-belts and timing belts that tend to be placed in areas that are difficult to reach. The three pin design gives the technician convenient belt push/pull capability and the handle gives the twisting control to install belts in difficult areas.



*95210 FAN CLUTCH WRENCH 36mm & 48mm

Works with most gas and diesel viscous fan clutches, with either a 36mm or 48mm hex holding the viscous fan clutch to the water pump. Two wrenches are needed to perform removal and replacement of the viscous fan clutch. One wrench to hold the water pump stationary (depending on the application a 99800A, 61600, 61500B, 10800 or 10900) and the other wrench a 95210 to remove and replace the viscous fan clutch.

Applications:

61600 + 95210

Chrysler, Ford, GM, Land Rover, Mazda (except Ford 4.9L 6 cylinder engines, "Bolted on" water pump pulleys.

99800A + 95210 Chrysler, GM Late Model Gas Engines "Pressed on" water pump pulleys.

61500B + 95210 GM Late Model Diesel Engines GM 6.5L Diesels 2000-2001, GM / Isuzu Duramax 6.6L 2001-2005 and new straight pin slot fan hub 2006 and later. "Pressed on" water pump pulleys.

10800 + 95210 Chrysler, Dodge, Jeep 5.7L Hemi Truck Engines 2009 and later "Pressed on" water pump pulleys.



***Available In A Kit See Page 31**

*95260 FAN CLUTCH WRENCH 40mm

This specially designed 40mm thin wrench is used with 61600 to remove and tighten the fan clutch. The wrench was developed and heat treated from alloy steel. It also has larger head size to maintain dimensional stability due to its thin profile design.

Applications:

Econoline Vans
F-Series Pickup Trucks 4.9L

1992 and later
1993 and later



*Available In A Kit See Page 31

95650A CUMMINS ENGINE ROTATING TOOL - VARIABLE DEPTH 3/8" drive barring tool is used for valve adjustments or pump settings and is made with a two-piece sleeve. Allows proper contact with the flywheel when the flywheel is at different depths from where the tool is inserted.

Applications:

Cummins
J.I. Case

B, C & L series engines 1987-current
3.9L, 5.9L, 6.7L and 8.3L diesel engine



96280 VW & AUDI POWER STEERING AND WATER PUMP PULLEY REMOVAL AND REPLACEMENT AID

The double triangular head configuration on this tool is designed to be used on pulleys that utilize socket head bolts. The tool holds the power steering or water pump pulley stationary while removing or replacing the three socket head bolts that attach the pulley to the shaft.

Applications: Volkswagen water cooled 4 cyl. V6

Volkswagen

5 cyl. engines with socket head bolts holding the pulley to the power steering pump

Audi water cooled
Power Steering Pump

4 cyl. V6
V8 engines

V6 engines

5 cyl. engines with socket head bolts holding the pulley to the power steering pump

1975 & later
1992 & later
1983-1988

1975 & later
1990 & later

1992 & later
1981-1985



96480 GM TRANSMISSION SEAL REMOVAL AND INSTALLATION TOOL

Works with transmissions that have the neutral safety switch around the transmission shift selector which requires a longer tool to remove and replace the seal.

Applications:

GM

Astro/Sierra Vans
Trucks

1996 and later
1998 and later

Denali, Envoy & Escalade with transmissions 4L60E and 4L80E




96600 UNIVERSAL HOSE PLIERS FITS 1/2" TO 3/4" U.S. Patent # 5,991,997

These pliers can be rotated 90° to easily pull the stuck hose from the fitting due to corrosion. The specially designed tips of these pliers grip a large surface area and different diameters of the hose to reduce damage during hose removal. Made from quality steel and come with soft grip handles.



1997

Popular Mechanics
EDITOR'S CHOICE AWARD 1998



POSITION CHANGE
FOR REMOVAL
OR INSTALLATION

BREAK LOOSE POWER
ROTATE POSITION

FAN CLUTCH KITS

61200 TWO PIECE KIT U.S. PATENT 6,912,936

This kit (61600 & 95210) has a specially designed contoured water pump holder that is exceptionally easy to use on vehicles using bolt-on water pump pulleys to remove and replace the viscous fan clutch. There are many sizes and patterns of the bolts holding the pulley on the water pump. The new water pump holding tool replaces all designs of water pump holding tools for "bolt-on type pulleys". Simply with only one hand, hook on the pulley bolt and hold to remove the viscous fan clutch. Reverse the 61600 to install the fan clutch.

Applications: Chrysler, GM, Ford, Land Rover and Mazda (Not including the 4.9L 6 cylinder Ford).



61600 see page 16

95210 see page 28

61260 THREE PIECE KIT U.S. PATENT 6,912,936

This three piece kit (includes 61600, 95210 & 95260) gives the professional technician the ability to service all fan clutches that have bolt-on pulleys on the water pump.

Applications: Chrysler, GM, Ford, Land Rover and Mazda applications. (Includes the 4.9L 6 cylinder Ford). Used on water pump pulleys that are bolted-on



61600 see page 16

95210 see page 28

95260 see page 29

UPDATE KITS

13351 Updates the 64900 or 64900A to 13350. Update kit includes three legs and 6 spring washers



13350 CAMARO 3.6L HARMONIC DAMPER PULLEY PULLER

See Page 11

13451 Updates the 64900 or 64900A to 13450. Update kit includes three legs and 6 spring washers



13450 DODGE HARMONIC DAMPER PULLEY PULLER

See Page 11

64910A Updates the 64900 to 64900A. Update kit includes three legs and 6 spring washers



64900A UPGRADED HARMONIC DAMPER PULLEY PULLER KIT

See Page 17

65120 PATENT PENDING HONDA / ACURA BUSHING X-TRACTOR™ "REMOVAL AND INSTALLATION TOOL"
Update for 65100, 65130



65100 HONDA / ACURA BUSHING X-TRACTOR™

See Page 18

91410B UPDATED UNIVERSAL OHC VALVE SPRING COMPRESSOR

Includes: Hex bar, two hex slider blocks, three detent clevis pins and a short lever bar.

Updates 91400A to 91400B













91400B UPDATED UNIVERSAL OHC VALVE SPRING COMPRESSOR

See Page 27

FAN CLUTCH WRENCH QUICK REFERENCE GUIDE

Must Select One Holding Tool from Section A (●) and One Wrench from Section B (○). Both are needed for each application

 <p>If "Bolted-on" use 61600 to hold the pulley</p> <p>If "Pressed-on" Domestic use 99800A, 61500B or 10900</p>	 <p>U.S. PATENT 6,912,936</p> <p>Universal 61600</p>	 <p>Five pin 99800A Domestic gas engines</p>	 <p>Four pin 61500B Domestic diesel engines</p>	 <p>Three pin 10800 5.7L Hemi truck engines</p>	 <p>Four pin 10900 Ford diesel engines</p>	 <p>11250 BMW & Sprinter Van</p>	 <p>36mm & 48mm 95210</p>	 <p>40mm "thin" 95260</p>	 <p>32mm 62100</p>
<p>Chrysler • Ford • GM Land Rover • Mazda (except Ford 4.9L 6 cyl. engines, see Ford below) "Bolted-on" water pump pulleys.</p>	●						○		
<p>Chrysler • GM Late Model Gas Engines "Pressed-on" water pump pulleys.</p>		●					○		
<p>GM Late Model Diesel Engines GM 6.5L diesels 2000-2001, GM / Isuzu Duramax 6.6L 2001-2005 and new straight pin slot fan hub 2006 and later. "Pressed-on" water pump pulleys.</p>			●				○		
<p>Dodge•Chrysler•Jeep 2009 and later 5.7L Hemi Truck Engines "Pressed-on" water pump pulleys</p>				●			○		
<p>Ford Diesel 2011 and later 6.7L Power Stroke Engines "Pressed-on" water pump pulleys</p>					●		○		
<p>Ford 4.9L 6 Cyl. Used on Ford 4.9L 6 cylinder F Series pickup trucks 93-96 and Econoline van 92-96.</p>	●							○	
<p>AUDI•BMW•VW AUDI 1996 and later (except pressed on pulley see below) BMW 3, 5, 6, 7, 8, X & Z series. (61600 works on all BMW's except the 4.0L & 4.4L V8 See 11250) VW's 1998 and later "Bolted on" water pump pulleys.</p>	●								○
<p>BMW & SPRINTER VANS BMW 4.0L & 4.4L V8 Sprinter Vans 2.7L, Dodge 03-06 "Bolted on" water pump pulleys.</p>						●			○

UNIVERSAL TOOLS

**89250 MASTER CYLINDER
PRESSURE CAP**
See Page 25



See Page 26

**90450 UNIVERSAL VALVE
ADJUSTMENT TOOL 9/16"**
See Page 25



See Page 26

**91400B UPDATED
UNIVERSAL OHC VALVE
SPRING COMPRESSOR**



See Page 27

**91400B-LDT VALVE
SPRING LOCK DOWN TOOL**



See Page 27

**91900 RADIATOR DRAIN
PLUG SOCKET**



See Page 27

**92350 NARROW ACCESS
VALVE STEM SEAL
REMOVAL
PLIERS**



See Page 27

**93750B OFFSET 2 1/8"
SUPER DUTY 12 & 6 POINT
OXYGEN SENSOR WRENCH**



See Page 28

**94170A BELT IT
SERPENTINE, V-BELT
AND TIMING BELT
INSTALLATION ASSIST**



See Page 28

**96600 UNIVERSAL HOSE
PLIERS 1/2" TO 3/4"**



See Page 29

**98110 RELAY AND
FUSIBLE LINK SLIP
JOINT PLIERS**



See Page 30

GM

**11700 DURAMAX LB7
INJECTOR PULLER KIT**



See Page 8

**12150 DURAMAX FUEL RAIL
PRESSURE WRENCH**



See Page 8

**12400 DURAMAX TURBO
VANE POSITION SENSOR
SOCKET**



See Page 9

**12900 21mm and 24mm
ALIGNMENT WRENCH**



See Page 9

**13100 GM DURAMAX
WATER IN FUEL SENSOR
WRENCH**



See Page 10

**13300 DURAMAX LLY,
LBZ, LMM INJECTOR
PULLER KIT**



See Page 10

**13350 CAMARO 3.6L
HARMONIC DAMPER
PULLEY PULLER**



See Page 11

**14300 DURAMAX FAN
PULLEY HOLDER**



See Page 13

**15500, 15510, 15520 NOX
AND SOOT SENSORS**



See Page 14

**61500B FAN CLUTCH
WRENCH**



See Page 16, 28, 32

**61600 FAN CLUTCH
WRENCH**



See Page 15, 16, 28, 29, 31, 32

**62800 GM HARMONIC
DAMPER HOLDING TOOL**



See Page 16

**64900A UPGRADED
HARMONIC DAMPER
PULLEY PULLER**



See Page 11, 17, 31

**66200 GM DOOR BUSHING
INSTALLATION TOOL**



See Page 19

**69200 GM DURAMAX
CRANKSHAFT AND
FLYWHEEL KIT**



See Page 22

69250 GM DURAMAX FLYWHEEL LOCK



See Page 22

93260 FAN CLUTCH WRENCH 36mm



See Page 28, 30

93480 GM TRANSMISSION SEAL REMOVAL AND INSTALLATION TOOL



See Page 28

96480 GM TRANSMISSION SEAL REMOVAL AND INSTALLATION TOOL



See Page 29

99800A FAN CLUTCH PULLEY HOLDER



See Page 28, 30, 32

CHRYSLER • DODGE • FIAT • JEEP

10800 FAN CLUTCH WRENCH



See Page 5, 28, 32

13450 DODGE HARMONIC DAMPER PULLEY PULLER



See Page 11, 31

14200 PNEUMATIC U-JOINT C-CLIP REMOVER



See Page 13

15200 DIESEL DEF TUBE RELEASE FORKS



See Page 14

15500, 15510, 15520 NOx AND SOOT SENSORS



See Page 14

15700 FIAT AND DODGE TIMING BELT WRENCH



See Page 14

61600 FAN CLUTCH WRENCH



See Page 15, 16, 28, 29, 31, 32

66150 FLARE NUT WRENCH FOR CUMMINS DIESEL ENGINE COMMON RAIL INJECTION



See Page 19

68450 SPARK PLUG BOOT REMOVER



See Page 21

88550 HEAVY DUTY 36mm FAN CLUTCH WRENCH



See Page 5, 25, 30

89100 CUMMINS SPECIAL OFFSET WRENCH 13mm



See Page 26

89150 CUMMINS SPECIAL OFFSET WRENCH 10mm



See Page 26

93260 FAN CLUTCH WRENCH 36mm



See Page 28, 30

95210 FAN CLUTCH WRENCH 36mm & 48mm



See Page 5, 15, 16, 28, 30-32

95650A CUMMINS ENGINE ROTATING TOOL



See Page 29

99100 FUEL INJECTION 6 POINT FLARE NUT SOCKET



See Page 30

99800A FAN CLUTCH PULLEY HOLDER



See Page 28, 30, 32

FORD

**11400 FORD POWER
STROKE 6.7L DIESEL
INJECTOR SOCKETS**



See Page 7

**12250 FORD 6.4L TURBO
ARM PULLER**



See Page 9

**13800 FORD 6.0L
TENSIONER WRENCH**



See Page 12

**14200 PNEUMATIC
U-JOINT C-CLIP REMOVER**



See Page 13

**15200 DIESEL DEF TUBE
RELEASE FORKS**



See Page 14

**61600 FAN CLUTCH
WRENCH**



See Page 15, 16, 28, 29, 31, 32

**68450 SPARK PLUG BOOT
REMOVER**



See Page 21

**93260 FAN CLUTCH
WRENCH 36mm**



See Page 28, 30

**95210 FAN CLUTCH
WRENCH 36mm & 48mm**



See Page 5, 15, 16, 28, 30-32

**95260 FAN CLUTCH
WRENCH 40mm**



See Page 15, 16, 29, 31, 32

LARGE TRUCKS • DIESEL

**13250 FUEL LINE
DISCONNECT TOOL SET
FOR 3/8" VOSS TYPE
CONNECTORS**



See Page 10

**13260 FUEL LINE
DISCONNECT TOOL SET
FOR CUMMINS ISB AND
ISX ENGINES**



See Page 10

**13270 FUEL LINE
DISCONNECT TOOL SET
FOR 1/2" VOSS TYPE
CONNECTORS**



See Page 10

**13900 (13910, 13920)
FUEL LINE SOCKETS 6
POINT FOR CUMMINS
ENGINES**



See Page 12

**14200 PNEUMATIC
U-JOINT C-CLIP REMOVER**



See Page 13

**15300 EGT SENSOR
SOCKETS**



See Page 14

**15500, 15510, 15520 NOx
AND SOOT SENSORS**



See Page 14

**61600 FAN CLUTCH
WRENCH**



See Page 15, 16, 28, 29, 31, 32

**66150 FLARE NUT
WRENCH FOR CUMMINS
DIESEL ENGINE COMMON
RAIL INJECTION**



See Page 19

**88550 HEAVY DUTY 36mm
FAN CLUTCH WRENCH**



See Page 5, 25, 30

**89100 CUMMINS SPECIAL
OFFSET WRENCH 13mm**



See Page 26

**89150 CUMMINS SPECIAL
OFFSET WRENCH 10mm**



See Page 26

**95650A CUMMINS ENGINE
ROTATING TOOL**



See Page 29

**99100 FUEL INJECTION 6
POINT FLARE NUT SOCKET**



See Page 30

ACURA • HONDA

10950 HONDA / ACURA
SERPENTINE BELT
TENSIONER



See Page 5

60100A HONDA / ACURA
4" OFFSET HARMONIC
DAMPER PULLEY HOLDING
TOOL 50mm



See Page 15

65100, 65130 HONDA
/ ACURA BUSHING
X-TRACTOR™ REMOVAL
AND INSTALLATION KIT



See Page 18, 31

66750B SHIELDED OXYGEN
& AIR FUEL SENSOR
SOCKET



See Page 19

68100 HONDA /
ACURA FRONT LOWER
COMPLIANCE BUSHING
R&R TOOL



See Page 20

88800 UNIVERSAL VALVE
ADJUSTMENT TOOL 12mm



See Page 26

88800, 88950 UNIVERSAL
VALVE ADJUSTMENT TOOL



See Page 26

96800 CAMSHAFT PULLEY
HOLDING TOOL



See Page 7, 30


LEXUS • TOYOTA

10200 TOYOTA "TOP
ACCESS" SERPENTINE
BELT TENSIONER WRENCH



See Page 5

10950 HONDA / ACURA
SERPENTINE BELT
TENSIONER



See Page 5

11500 CAMSHAFT PULLEY
HOLDING TOOL



See Page 7

13500 TOYOTA WATER
PUMP PULLEY WRENCH



See Page 12

14150 TOYOTA PARKING
BRAKE TOOL



See Page 13

15800 TOYOTA SERPENTINE
BELT WRENCH



See Page 5, 15

63800 CAM SEAL INSTALLER



See Page 16

64300 LEXUS & TOYOTA
HARMONIC DAMPER
PULLEY HOLDING TOOL



See Page 17

64400 TOYOTA HARMONIC
DAMPER HOLDING TOOL



See Page 17

65400 LEXUS & TOYOTA
FRONT AXLE LOCK NUT
REMOVER KIT



See Page 18

65510 TOYOTA / LEXUS V6
CAM SEAL R&R TOOL



See Page 18

66750B SHIELDED OXYGEN
& AIR FUEL SENSOR
SOCKET



See Page 19

68960 TOYOTA / LEXUS
39mm 12 POINT SOCKET
AXLE NUT



See Page 21

88250 TOYOTA / LEXUS
VALVE ADJUSTMENT
TOOLS



See Page 25

88800 UNIVERSAL VALVE
ADJUSTMENT TOOL 12mm



See Page 26

LEXUS • TOYOTA

**88950 UNIVERSAL VALVE
ADJUSTMENT TOOL 10mm**



See Page 26

**96800 CAMSHAFT PULLEY
HOLDING TOOL**



See Page 7, 30

**97300 TIMING BELT
TENSIONER**



See Page 30

NISSAN • HYUNDAI • SUBARU

**11500 CAMSHAFT PULLEY
HOLDING TOOL**



See Page 7

**63800 CAM SEAL
INSTALLER**



See Page 16

**64900A UPGRADED
HARMONIC DAMPER
PULLEY PULLER**



See Page 11, 17, 31

**66750B SHIELDED OXYGEN
& AIR FUEL SENSOR
SOCKET**



See Page 19

**88800 UNIVERSAL VALVE
ADJUSTMENT TOOL 12mm**



See Page 26

**88950 UNIVERSAL VALVE
ADJUSTMENT TOOL 10mm**



See Page 26

**96800 CAMSHAFT
PULLEY HOLDING TOOL**



See Page 7, 30

**98700 TENSION PULLEY
SPANNER WRENCH**



See Page 30

MAZDA • MITSUBISHI

**61600 FAN CLUTCH
WRENCH**



See Page 15, 16, 28, 29, 31, 32

**63800 CAM SEAL
INSTALLER**



See Page 16

**66750B SHIELDED OXYGEN
& AIR FUEL SENSOR
SOCKET**



See Page 19

**93260 FAN CLUTCH
WRENCH 36mm**



See Page 28, 30

**95210 FAN CLUTCH
WRENCH 36mm & 48mm**



See Page 5, 15, 16, 28, 30-32

**98700 TENSION PULLEY
SPANNER WRENCH**



See Page 30

**99700 DOHC VALVE
LIFTER REMOVAL TOOL**



See Page 30

AUDI

**12200 VW / AUDI DIESEL
INJECTOR PULLER**



See Page 8

**12700 & 12730 AUDI,
BMW, VW BRAKE BLEEDER
WRENCHES 11mm**



See Page 9

**12900 AUDI, BMW, VW,
PORSCHE ALIGNMENT
WRENCH**



See Page 9

**61600 FAN CLUTCH
WRENCH**



See Page 15, 16, 28, 28, 31, 32

**62100 AUDI, BMW, VW FAN
CLUTCH WRENCH**



See Page 16, 32

**67600 AUDI & VW TIMING
BELT PULLEY HOLDER**



See Page 20

**67650 AUDI & VW
TIMING BELT TENSIONER
RELEASE TOOL**



See Page 20

**68950 AUDI, BMW & VW
32mm 12 POINT DEEP
SOCKET AXLE NUT**



See Page 21

**83400 CIS FUEL INJECTOR
PULLER**



See Page 24

**86400 AUDI & VW TENSION
PULLEY SPANNER
WRENCH**



See Page 25

**87300 VW & AUDI STRUT
SHOCK NUT SOCKET**



See Page 25

**89250 MASTER
CYLINDER PRESSURE
CAP**



See Page 26

**96280 AUDI & VW POWER
STEERING & WATER PUMP
PULLEY REMOVAL &
REPLACEMENT AID**



See Page 29

BMW

**11800 BMW INJECTOR
PULLER**



See Page 8

**12500 BMW T-60 TORX
SERPENTINE BELT
TENSIONER TOOL**



See Page 9

**12700 & 12710 AUDI,
BMW, VW BRAKE BLEEDER
WRENCHES 11mm**



See Page 9

**12900 AUDI, BMW, VW,
PORSCHE ALIGNMENT
WRENCH**



See Page 9

**13400, 13410, 13420
BMW INJECTOR LINE
SOCKETS 14mm & 17mm
12 POINT 3/8" DRIVE**



See Page 11

**61600 FAN CLUTCH
WRENCH**



See Page 15, 16, 28, 29, 30, 31

**62100 AUDI, BMW, VW
FAN CLUTCH WRENCH**



See Page 16, 32

**63100 BMW "A" ARM
THRUST BUSHING
WRENCH**



See Page 16

**68950 AUDI, BMW & VW
32mm 12 POINT DEEP
SOCKET AXLE NUT**



See Page 21