88750B COMPACT SUPER DUTY 22mm 12- AND 6-POINT OXYGEN SENSOR WRENCH Completely

updated 12 point and 6 point SP Spline Grip Drive giving the technician the ultimate tool to remove oxygen sensors in confined areas.

Applications: W 4 cyl. 1996 & later, Foreign and Domestic cars with all 22mm non-shielded oxygen sensor wire/connectors



88800 12mm, **88900** 13mm, **88950** 10mm UNIVERSAL VALVE ADJUSTMENT TOOLS

Designed for a wide variety of cars with 10mm, 12mm & 13mm jam nut valve adjustment screws. This two-in-one tool features a window in its socket so the technician can see the position of the screwdriver blade holding the adjustment screw as the jam nut is tightened. The unique handle pivots from one side to the other, so the window is always visible.

Applications: All vehicles with 10mm, 12mm and 13mm jam nut valve adjustment screws, Honda, Toyota, Nissan (Includes the VTEC engine), & VW



89100 CUMMINS SPECIAL OFFSET WRENCH

13mm For Cummins Injection Pump & Idle Lock Nuts.

Designed to remove and install the 13mm injection pump mounting bolts and idle lock nuts. These tools have also been found to be useful in many other applications where these size fasteners are in a confined area.

Applications: Cummins injection pump and idle lock nuts Dodge Cummins B series 5.9L diesel engines



89100 13mm Wrench

89150 CUMMINS SPECIAL OFFSET WRENCHES

10mm For Cummins Injection Pump & Idle Lock Nuts. Designed to remove and install the 10mm injection pump mounting bolts and idle lock nuts. These tools have also been found to be useful in many other applications where these size fasteners are in a confined area.

Applications: Cummins injection pump and idle lock nuts Dodge Cummins B series 5.9L diesel engines



89250 MASTER CYLINDER PRESSURE CAP

Designed with a 1/4"-18" NPT threaded opening for use with pressure bleeders on most master cylinders or clutch slave cylinders.

Applications: Audi, BMW, Mazda, Mercedes Benz, Porsche, Saab, Volkswagen and Volvo.





90450 9/16" UNIVERSAL VALVE ADJUSTMENT

TOOL Designed for a wide variety of cars with 9/16" jam nut valve adjustment screws. This two-in-one tool features a window in its socket so the technician can see the position of the screwdriver blade holding the adjustment screw as the jam nut is tightened. The unique handle pivots from one side to the other, so the window is always visible.

UNIVERSAL TOOLS



See Page 5



See Page 7





See Page 8



See Page 10





See Page 12



See Page 14



See Page 14



66100, 66110, 66120 HEAD HANDLER 6mm, 1/4", 8mm set of 3 sizes



See Page 18

67300 UNIVERSAL BRAKE CALIPER TOOL AND 1/2" DRIVE ADAPTER



See Page 19

67380 3/8" DRIVE BRAKE **CALIPER ADAPTER**



See Page 19





67900 OrganizeAIR™



68800 LOW-PROFILE PITMAN ARM POPPER



See Page 21



See Page 22



86100B UNIVERSAL

86100B-7 1/2" DRIVE **BRAKE CALIPER ADAPTER**





See Page 25

88150 BENCH HEAD STAND



See Page 25

88750B COMPACT SUPER DUTY 12-AND 6-POINT OXYGEN SENSOR WRENCH



See Page 26



88800 UNIVERSAL VALVE

See Page 26





SP TOOLS / SCHLEY PRODUCTS INC.