

2017 NEW PRODUCTS

13250 FUEL LINE DISCONNECT TOOL SET FOR 3/8" VOSS TYPE CONNECTORS

NEW



SEE PAGE 10

13260 FUEL LINE DISCONNECT TOOL SET FOR CUMMINS ISB AND ISX ENGINES

NEW



SEE PAGE 10

13270 FUEL LINE DISCONNECT TOOL SET FOR 1/2" VOSS TYPE CONNECTORS

NEW



SEE PAGE 10

14150 TOYOTA PARKING BRAKE TOOL

NEW



SEE PAGE 13

14200 PNEUMATIC U-JOINT C-CLIP REMOVER

NEW



SEE PAGE 13

14500 HARLEY DAVIDSON CLUTCH ADJUSTMENT WRENCH

NEW



SEE PAGE 13

15200 DIESEL DEF TUBE RELEASE FORKS

NEW



See Page 14

15300 EGT SENSOR SOCKETS

NEW



See Page 14

15600 BATTERY CABLE CRIMPER

NEW



See Page 14

15200 DIESEL DEF TUBE RELEASE FORKS This set of forks is designed to depress the locks that retain the DEF lines allowing removal. Three sizes to fit most DEF fill and breather lines on Ford and Dodge trucks, two angles straight and 90° to access most locations saving time trying to access hard to reach clips.



15300 EGT SENSOR SOCKETS Remove exhaust temperature sensors with ease, without damage. This set of sockets is designed to drive all 6 sides of the hex equally to reduce the chance of damage. The 3 different sizes and 2 different styles will remove most, if not all, EGT sensors used on cars, light, medium, and heavy-duty trucks on the road today.



15500 NOx AND SOOT SENSOR SOCKETS

15510 24mm 15520 30mm: This set of 12-point and 6-point 24mm and 30mm sockets is designed to remove NOx, and Particulate Matter (SOOT) sensors on cars and trucks on the road today.

Applications: Chrysler 3.0L V6, Jeep Grand Cherokee and Dodge Ram and other diesel motors with modern exhaust particulate filter systems.



15500 SEPARATE PIECES

15510 24mm NOx AND SOOT SENSOR SOCKET




15520 30mm NOx AND SOOT SENSOR SOCKET



15600 BATTERY CABLE CRIMPER

Convenient 14mm bolt head and 16mm casting hex size is compact and heat treated for durability. Crimps up to 0 AWG cable terminal ends. Designed to service battery cables while still attached to the vehicle, using a common wrench and ratchet—no hammer required.




15700 FIAT AND DODGE TIMING BELT WRENCH

Allows for the easy adjustment of the camshaft spur belts that have idler pulleys with pin holes. In operation, this spanner wrench with its protruding pins, grips the center of the idler pulley and rotates it around its off-center retaining bolt. This rotation then allows for camshaft spur belt tension adjustment. Comes with a black finish and a soft grip handle. **Applications:**

CHRYSLER

Dodge	1.4L 4 cyl.	2013-2016
Fiat	1.4L 4 cyl.	2012-2016



UNIVERSAL TOOLS

**10500 PARKING BRAKE
CABLE COUPLER TOOL**



See Page 5

**11100 MANUAL BUSHING
R&R TOOL SET**



See Page 7

**11600 EXTRA LONG AIR
HAMMER PNEUMATIC
DRIFTS**



See Page 7

**11880 HEAVY-DUTY
PITMAN ARM POPPER**



See Page 8

**13000 STAKED AXLE
NUT PUNCHES**



See Page 10

**13700 ALL-IN-ONE
FLUID STOPPER**



See Page 12

**14000 BOSCH DIRECT
INJECTION INJECTOR
PULLER KIT**



See Page 12

15300 EGT SENSOR SOCKETS



See Page 14

**15600 BATTERY CABLE
CRIMPER**



See Page 14

**65350 UNIVERSAL LONG
REACH SPARK PLUG BOOT
PULLER**



See Page 18

**66100, 66110, 66120 HEAD
HANDLER 6mm, 1/4",
8mm set of 3 sizes**



See Page 18

**67300 UNIVERSAL BRAKE
CALIPER TOOL AND 1/2"
DRIVE ADAPTER**



See Page 19

**67380 3/8" DRIVE BRAKE
CALIPER ADAPTER**



See Page 19

**67700 MAGNETIC WASHER
REMOVER**



See Page 20

**67750A SUPER DUTY 12 &
6 POINT OXYGEN SENSOR
WRENCH WITH HANDLE**



See Page 20

67900 OrganizeAIR™



See Page 20

**68800 LOW-PROFILE
PITMAN ARM POPPER**



See Page 21

**69610, 69630 HUB BEARING
REMOVER 12mm, 14mm**



See Page 22

**86100B UNIVERSAL
BRAKE CALIPER TOOL**



See Page 24

**86100B-7 1/2" DRIVE
BRAKE CALIPER ADAPTER**



See Page 25

88150 BENCH HEAD STAND



See Page 25

**88750B COMPACT SUPER
DUTY 12-AND 6-POINT
OXYGEN SENSOR WRENCH**



See Page 26

**88800 UNIVERSAL VALVE
ADJUSTMENT TOOL 13mm**



See Page 26

**88900 UNIVERSAL VALVE
ADJUSTMENT TOOL 12mm**



See Page 26

**88950 UNIVERSAL VALVE
ADJUSTMENT TOOL 10mm**



See Page 26