



TREE & INDUSTRIAL MARKER

A highly visible marking paint that produces a narrow, concentrated spray for marking trees and lumber at longer distances. Adheres to wet wood and leaves a permanent mark. Color selection is approved by the logging and lumber industry.

Suggested Uses:

Marking trees
Grading steel
Identifying lumber
Mine marking
Pipe coding
Grading logs

Packaging:

Cans per case	12
Shipping weight per case	14 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 250 linear feet
Cleanup	Paint or lacquer thinner
Flammability	Flammable
Flash point	-4 F
Specific Gravity	0.80
Solids Content	27%
MIR value	0.61, cannot exceed 0.85
HAPs content	0
Storage Temperature	40-100F
Application Temperature	50-90F
Heat Resistance	250° F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch 15 minutes

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code
16-604	White	043281000734
16-616	Red	043281000758
16-618	Blue	043281000765
16-620	Green	043281000772
16-622	Yellow	043281000789
16-624	Orange	043281000796

12-5-2019