Seymour of Sycamore

www.seymourpaint.com

3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

1 Identification of the substance and manufacturer

| Trade | nam | e: |
|-------|-----|----|
| | | |

Product code: **Recommended use:** Uses advised against: Manufacturer/Supplier:

GREEN ZINC PHOSPHATE

0000160899 Paint and coatings application. Any that differs from the recommended use. Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com 1-800-255-3924

Emergency telephone number:

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



| Signal word | Danger |
|--------------------------|---|
| Hazard statements | Extremely flammable aerosol. |
| | Contains gas under pressure; may explode if heated. |
| | Causes serious eye irritation. |
| | May cause drowsiness or dizziness. |
| | May cause damage to organs through prolonged or repeated exposure. |
| Precautionary statements | Keep away from heat/sparks/open flames/hot surfaces No smoking. |
| | Do not spray on an open flame or other ignition source. |
| | Pressurized container: Do not pierce or burn, even after use. |
| | Do not breathe dust/fume/gas/mist/vapors/spray. |
| | Wash hands thoroughly after handling. |
| | Use only outdoors or in a well-ventilated area. |
| | Wear protective gloves/protective clothing/eye protection/face protection. |
| | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and |
| | easy to do. Continue rinsing. |
| | Call a poison center/doctor if you feel unwell. |
| | If eye irritation persists: Get medical advice/attention. |
| | Store in a well-ventilated place. |
| | Store locked up. |
| | Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| | Dispose of contents/container in accordance with local/regional/national/international regulations. |

3 Composition/information on ingredients **Chemical characterization: Mixtures**

This product is a mixture of the substances listed below with nonhazardous additions. **Chemical Description:** Dangerous components: 79-20-9 methyl acetate 74-98-6 propane

| propane | 15-25% |
|----------|--------|
| n-butane | 5-10% |
| | 1-5% |
| | 1-5% |
| | 1-5% |
| | 1-5% |
| | 1-5% |
| | 1-5% |
| methanol | 0.17% |
| | |

| 4 First-aid measures | |
|---|---|
| After inhalation: After skin contact: After eye contact: After swallowing: | Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting. |
| Most important symptoms and effects: | Dizziness (Contri en para 2) |

(Contd. on page 2)

25-50%

Printing date 01/10/2020

F

Page 2/5

| Printing date 01/10/2020 | Revised On 01/10/2020 |
|---|--|
| Trade name: GREEN ZINC PHOSPHATE | |
| | |
| Indication of any immediate media | (Contd. of page 1) |
| Indication of any immediate medica attention needed: | No further relevant information available. |
| | |
| E Fire fighting measures | |
| 5 Fire-fighting measures | 202 extinguishing neurolegies water envey. Fight lever fires with water envey |
| Extinguishing agents: Special hazards: | CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures. |
| Protective equipment for | Carronn explosive gas-air mixtures. |
| firefighters: | A respiratory protective device may be necessary. |
| | |
| 6 Accidental release measures | |
| Personal precautions, protective | |
| equipment and emergency | |
| procedures: | Wear protective equipment. Keep unprotected persons away. |
| Matheada and material fan | Use respiratory protective device against the effects of fumes/dust/aerosol. |
| Methods and material for containment and cleaning up: | Ensure adequate ventilation. |
| containment and cleaning up. | |
| 7 Llevelling and stars as | |
| 7 Handling and storage | |
| Precautions for safe handling | Use only in well ventilated areas. |
| Storage requirements: | Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up. |
| | |
| 9 Evenesure controls/nerroundling | testion |
| 8 Exposure controls/personal pro | |
| | require monitoring at the workplace: |
| 79-20-9 methyl acetate | |
| PEL (USA) Long-term value: 610 mg | |
| REL (USA) Short-term value: 760 mg Long-term value: 610 mg | /m³, 250 ppm |
| TLV (USA) Short-term value: 757 mg | |
| Long-term value: 606 mg | /m², 250 ppm /m³ 200 ppm |
| 74-98-6 propane | , 200 pp.m |
| PEL (USA) Long-term value: 1800 m | g/m ³ , 1000 ppm |
| REL (USA) Long-term value: 1800 m | |
| TLV (USA) refer to Appendix F inTLV | |
| 106-97-8 n-butane | |
| REL (USA) Long-term value: 1900 m | g/m ³ , 800 ppm |
| TLV (USA) Short-term value: 2370 m | |
| (EX) | |
| 110-19-0 Isobutyl Acetate | |
| PEL (USA) Long-term value: 700 mg | |
| REL (USA) Long-term value: 700 mg | |
| TLV (USA) Short-term value: 712 mg | /m ³ , 150 ppm |
| Long-term value: 238 mg | יווי², סט ppm |
| 1330-20-7 xylene (mix) | /m³ 100 nnm |
| PEL (USA) Long-term value: 435 mg. | |
| REL (USA) Short-term value: 655 mg Long-term value: 435 mg | /m , 150 ppm /m ³ 100 ppm |
| TLV (USA) Short-term value: 651 mg | |
| Long-term value: 434 mg | /m³, 100 ppm |
| BEI | |
| 64-17-5 ethyl alcohol | |
| PEL (USA) Long-term value: 1900 m | |
| REL (USA) Long-term value: 1900 m | |
| TLV (USA) Short-term value: 1880 m | g/m³, 1000 ppm |
| 67-64-1 Acetone | |
| PEL (USA) Long-term value: 2400 m | |
| REL (USA) Long-term value: 590 mg | |
| TLV (USA) Short-term value: 1187 m | g/m³, 500 ppm |
| Long-term value: 594 mg BEI | /m°, 250 ppm |
| | (Contd. on page 3) |
| | (Cond. of page 3) |

Revised On 01/10/2020

Page 3/5

| Trade name: GREEN ZINC PHOSPHATE | |
|---|---|
| Trade name. Skeln zing Phosphare | |
| | (Contd. of page 2) |
| 67-56-1 methanol PEL (USA) Long-term value: 260 mg/n | n ³ 200 nnm |
| REL (USA) Cong-term value: 200 mg/n REL (USA) Short-term value: 325 mg/r Long-term value: 260 mg/n Skin | n ³ , 250 ppm |
| TLV (USA) Short-term value: 328 mg/r Long-term value: 262 mg/n Skin; BEI | n³, 250 ppm 1³, 200 ppm |
| Ingredients with biological limit valu | es: |
| 1330-20-7 xylene (mix) | |
| BEI (USA) 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric a | acids |
| 67-64-1 Acetone | |
| BEI (USA) 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonsp | ecific) |
| 67-56-1 methanol | |
| BEI (USA) 15 mg/L Medium: urine Time: end of shift Parameter: Methanol (backg | ground, nonspecific) |
| | Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working. |
| Breathing equipment: | A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine. |
| Hand protection: | Nitrile gloves. The glove material must be impermeable and resistant to the substance. |
| Eye protection: | Tightly sealed goggles |
| 9 Physical and chemical properties | |
| Appearance: | Aerosol. |
| Odor: Odor threshold: | Aromatic Not determined. |
| pH-value: Melting point/Melting range Boiling point: | Not determined. Undetermined. -110 °C (-230 °F) |
| Flash point: Flammability (solid, gas): | -19 °C (-66.2 °F) Extremely flammable. |
| Decomposition temperature: | Not determined. |
| Auto igniting: | Product is not self-igniting. |
| Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: | In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 16 Vol % |
| Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octonal/water | Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. : Not determined. |
| Solubility: Viscosity: VOC content (less exempt solvents): Water: | Not determined. Not determined. 80.6 % 0.0 % |
| 10 Stability and reactivity | |
| Reactivity: Conditions to avoid: Chemical stability: | Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. Not fully evaluated. |
| Possibility of hazardous reactions: | No dangerous reactions known. No further relevant information available. |
| Incompatible materials: | NO TURTNER RELEVANT INFORMATION AVAILABLE. (Contd. on page 4) |

Trade name: GREEN ZINC PHOSPHATE

Revised On 01/10/2020

| Trade name: GREEN ZINC PHOSPHATE | |
|--|--|
| Hazardous decomposition: | No dangerous decomposition products known. (Contd. of page 3) |
| 11 Toxicological information | |
| LD/LC50 values that are relevant fo | r classification: |
| 79-20-9 methyl acetate | |
| Oral LD50 6,970 mg/kg (rat |) |
| 106-97-8 n-butane | , |
| Inhalative LC50/4 h 658 mg/l (rat) | |
| 110-19-0 Isobutyl Acetate | |
| Oral LD50 4,763 mg/kg (rbt |) |
| 1330-20-7 xylene (mix) Oral LD50 8,700 mg/kg (rat | |
| Oral LD50 8,700 mg/kg (rat Dermal LD50 2,000 mg/kg (rbt | |
| Inhalative LC50/4 h 6,350 mg/l (rat) | |
| 64-17-5 ethyl alcohol | |
| Oral LD50 7,060 mg/kg (rat | |
| Inhalative LC50/4 h 20,000 mg/l (rat) | |
| 67-56-1 methanol | |
| Oral LD50 5,628 mg/kg (rat | |
| Dermal LD50 15,800 mg/kg (rl | |
| Information on toxicological effects Skin effects: | : No data available. No irritant effect. |
| Eye effects: | Irritating effect. |
| Sensitization: | No sensitizing effects known. |
| | |
| 12 Ecological information | |
| Aquatic toxicity: | Hazardous for water, do not empty into drains. |
| Persistence and degradability: Other information: | The product is degradable after prolonged exposure to natural weathering processes. |
| Other mormation: | This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated |
| | solvents. |
| Bioaccumulative potential: | No further relevant information available. |
| Mobility in soil: Other adverse effects: | No further relevant information available. No further relevant information available. |
| | |
| 13 Disposal considerations | |
| Dispose of in accordance with local, s | tate, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be |
| disposed of responsibly. Do not heat of | or cut empty containers with electric or gas torches. |
| Recommendation: | Completely empty cans should be recycled. |
| | |
| 14 Transport information | |
| UN-Number DOT | UN1950 N/A |
| Bol | UN1950 |
| DOT | Consumer Commodity ORM-D |
| ADR | Aerosols, flammable 1950 Aerosols |
| Transport hazard class(es): | |
| Class Marine pollutent | 2.1 No |
| Marine pollutant: | No Symbol (fish and tree) |
| Special precautions for user: | Warning: Gases |
| EMS Number: | F-D,S-Ŭ |
| Packaging Group: UN "Model Regulation": | UN1950, Aerosols, 2.1 |
| | |
| 15 Regulatory information | |
| SARA Section 355 (extremely hazar | dous substances). |
| None of the ingredients in this product | |
| SARA Section 313 (Specific toxic cl | |
| 1330-20-7 xylene (mix) | iennear narniya). |
| 7779-90-0 zinc phosphate | |
| 1314-13-2 zinc oxide | |
| · · · · | (Contd. on page 5) |
| | |

Revised On 01/10/2020

| Trade name: GREEN ZINC PHOSPHATE | | |
|--|--|------------------|
| | (Co | ontd. of page 4) |
| Toxic Substances Control Act (TSCA): | All hazardous ingredients are found on the inventory list of substances. | |
| Canadian Domestic Substances List (DSL): | t All ingredients are listed or exempted. | |
| Consumer Product Safety Comission (CPSC): | This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead | J. |
| California Proposition 65 chemicals | | |
| 100-41-4 ethyl benzene | | |
| 1333-86-4 Carbon black | | |
| 108-10-1 methyl isobutyl ketone | | |
| Prop 65 chemicals known to cause I | birth defects or reproductive harm: | |
| 67-56-1 methanol | | |
| 108-10-1 methyl isobutyl ketone | | |
| EPA: | | |
| 110-19-0 Isobutyl Acetate | | D |
| 1330-20-7 xylene (mix) | | 1 |
| 7779-90-0 zinc phosphate | | D, I, II |
| 67-64-1 Acetone | | 1 |
| 1314-13-2 zinc oxide | | D, I, II |
| | | |
| 16 Other information | | |
| Contact: | Regulatory Affairs | |