Printing date 01/10/2020 Revised On 01/10/2020

1 Identification of the substance and manufacturer

Trade name: **PBE 1K CLEAR** Product code: 0000201690

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Manufacturer/Supplier: Seymour of Sycamore

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation. Eye Irrit. 2A Skin Sens. 1 H317 May cause an allergic skin reaction.

H350 May cause cancer. Carc. 1B

H336 May cause drowsiness or dizziness. STOT SE 3

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

Precautionary statements





GHS02 GHS04 GHS07 GHS08

Signal word

Extremely flammable aerosol. **Hazard statements**

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause an allergic skin reaction. May cause cancer.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. **Chemical Description:**

Dangero	Dangerous components:			
115-10-6	dimethyl ether	25-50%		
67-64-1	Acetone	15-25%		
123-86-4	butyl acetate	10-15%		
108-65-6	PM acetate	5-10%		
78-93-3	methyl ethyl ketone	≥5-<10%		
628-63-7	pentyl acetate	1-5%		

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After eye contact: After swallowing: Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 01/10/2020 Revised On 01/10/2020

Trade name: PBE 1K CLEAR

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.

Protective equipment for

firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:		
115-10-6 dimethyl ether		
WFFL (USA) Long-term value: 1000 ppm		

67-64-1 Acetone PEL (USA)

Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m³, 250 ppm Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm TLV (USA)

BFI

123-86-4 butyl acetate

PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA)

Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

78-93-3 methyl ethyl ketone

PEL (USA) Long-term value: 590 mg/m³, 200 ppm REL (USA) Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm TLV (USA)

BEI

628-63-7 pentyl acetate

PEL (USA) Long-term value: 525 mg/m³, 100 ppm REL (USA) Long-term value: 525 mg/m³, 100 ppm Short-term value: 532 mg/m³, 100 ppm TLV (USA) Long-term value: 266 mg/m³, 50 ppm

80-62-6 methyl methacrylate

PEL (USA) Long-term value: 410 mg/m³, 100 ppm REL (USA) Long-term value: 410 mg/m³, 100 ppm TLV (USA) Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm DSĔN

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Printing date 01/10/2020 Revised On 01/10/2020

Trade name: PBE 1K CLEAR

78-93-3 methyl ethyl ketone

BEI (USA) 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In **Breathing equipment:** cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn.

If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Not determined. Odor threshold: Not determined. pH-value: Melting point/Melting range Undetermined. **Boiling point:** -24 °C (-75.2 °F) -19 °C (-66.2 °F) Flash point: Flammability (solid, gas): Extremely flammable. Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

In use, may form flammable/explosive vapour-air mixture. Danger of explosion:

3 Vol % Lower Explosion Limit: Upper Explosion Limit: 18.6 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined.

VOC content (less exempt solvents): 69.0 %

10 Stability and reactivity

Reactivity: Conditions to avoid: Stable at normal temperatures.

No decomposition if used according to specifications.

Chemical stability: Not fully evaluated.

No dangerous reactions known. Possibility of hazardous reactions:

Incompatible materials: No further relevant information available. No dangerous decomposition products known. Hazardous decomposition:

11 Toxicological information

LD/LC50 values that are relevant for classification:				
115-10-6 dimethyl ether				
Inhalative LC50/4 h 308 mg/l (rat)				
123-86-4 butyl acetate				
		14,000 mg/kg (rat)		
Inhalative	LC50/4 h	>21 mg/l (rat)		
108-65-6 PM acetate				
-		8,500 mg/kg (rat)		
Inhalative	LC50/4 h	35.7 mg/l (rat)		
78-93-3 methyl ethyl ketone				
Oral	LD50	3,300 mg/kg (rat)		
Dermal	LD50	5,000 mg/kg (rbt)		

628-63-7 pentyl acetate

LD50 6,500 mg/kg (rat) Oral

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

I

Safety Data Sheet

Printing date 01/10/2020 Revised On 01/10/2020

Trade name: PBE 1K CLEAR

Sensitization: No sensitizing effects known. (Contd. of page 3)

12 Ecological information

Aquatic toxicity:

Hazardous for water, do not empty into drains.

Persistence and degradability:

The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential: Mobility in soil:

No further relevant information available. No further relevant information available. No further relevant information available.

13 Disposal considerations

Other adverse effects:

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950

DOT N/A

DOT Consumer Commodity ORM-D

Aerosols, flammable

1950 Aerosols

Transport hazard class(es):

Class

Warning: Gases Special precautions for user:

F-D,S-Ŭ EMS Number:

Packaging Group: UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

Toxic Substances Control Act

All hazardous ingredients are found on the inventory list of substances.

(TSCA): Canadian Domestic Substances List (DSL):

Consumer Product Safety

All ingredients are listed or exempted.

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

EPA:

67-64-1 Acetone

78-93-3 methyl ethyl ketone

16 Other information

Contact: Regulatory Affairs