Seymour of Sycamore

3041 Dougall Avenue, Suite 503

Printing date 01/10/2020 Revised On 01/02/2020

1 Identification of the substance and manufacturer

Trade name: **SAFETY RED** Product code: 0006201423

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Manufacturer/Supplier: Seymour of Sycamore

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com www.seymourpaint.com

1-800-255-3924

Emergency telephone number:

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

Precautionary statements







GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. Chemical Description:

| Dangerous components: | | |
|-----------------------|----------------------|---------|
| | Acetone | 15-25% |
| | propane | 15-25% |
| | n-butane | 5-10% |
| | barium sulfate | 5-10% |
| | Isobutyl Acetate | 5-10% |
| | Glycol Ether EP | ≥5-<10% |
| | PM acetate | 1-5% |
| | butyl acetate | 1-5% |
| 107-87-9 | Methyl Propyl Ketone | 1-5% |

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After eye contact:

Rinse out mouth and then drink plenty of water. After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Dizziness

(Contd. on page 2)

Printing date 01/10/2020 Revised On 01/02/2020

Trade name: SAFETY RED

Indication of any immediate medical

No further relevant information available. attention needed:

(Contd. of page 1)

5 Fire-fighting measures

Extinguishing agents: Special hazards:

Protective equipment for firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Storage requirements:

Store locked up.

8 Exposure controls/personal protection

| Components with limit values that require monitoring at the workplace: 67-64-1 Acctone | 8 Exposure controls/personal protection | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
| PEL (USA) Long-term value: 2400 mg/m³, 1500 ppm Long-term value: 590 mg/m³, 250 ppm Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI 74-98-6 propane | Components with limit values that require monitoring at the workplace: | | | |
| REL (USA) Long-term value: 590 mg/m³, 250 ppm | ** * * * * * * * * * * * * * * * * * * * | | | |
| TLV (USA) Short-term value: 1187 mg/m³, 500 ppm | PEL (USA) | Long-term value: 2400 mg/m³, 1000 ppm | | |
| Long-term value: 594 mg/m³, 250 ppm | REL (USA) | Long-term value: 590 mg/m³, 250 ppm | | |
| BEI | TLV (USA) | Short-term value: 1187 mg/m³, 500 ppm | | |
| 74-98-6 propane PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX 106-97-8 n-butane REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm (EX) 7727-43-7 barium sulfate PEL (USA) Long-term value: 15* 5** mg/m³ | | | | |
| PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX | 74-98-6 prop | | | |
| REL (USA) | | | | |
| TLV (USA) | | | | |
| 106-97-8 n-butane | ` , | | | |
| REL (USA) | | | | |
| TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm (EX) 7727-43-7 barium sulfate PEL (USA) Long-term value: 15* 5** mg/m³ *total dust **respirable fraction REL (USA) Long-term value: 10* 5** mg/m³ *fintal dust **respirable fraction TLV (USA) Long-term value: 5* mg/m³ *fintal able fraction; E 110-19-0 Isobutyl Acetate PEL (USA) REL (USA) Long-term value: 700 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 5* ppm 123-86-4 butyl acetate PEL (USA) REL (USA) Short-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 710 mg/m³, 150 ppm Short-term value: 238 mg/m³, 50 ppm TLV (USA) Long-term value: 710 mg/m³, 150 ppm Short-term value: 238 mg/m³, 50 ppm TLV (USA) Long-term value: 712 mg/m³, 150 ppm TLV (USA) Long-term value: 712 mg/m³, 150 ppm TLV (USA) Long-term value: 712 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 738 mg/m³, 50 ppm Long-term value: 738 mg/m³, 50 ppm Long-term value: 738 mg/m³, 50 ppm Long-term value: 700 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm | | | | |
| (EX) 7727-43-7 barium sulfate PEL (USA) | ` , | | | |
| PEL (USA) Long-term value: 15* 5** mg/m³ *total dust **respirable fraction REL (USA) Long-term value: 10* 5** mg/m³ *total dust **respirable fraction TLV (USA) Long-term value: 5* mg/m³ *inhalable fraction; E 110-19-0 Isobutyl Acetate PEL (USA) Long-term value: 700 mg/m³, 150 ppm REL (USA) Long-term value: 700 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm 123-86-4 butyl acetate PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm Long-term value: 238 mg/m³, 50 ppm Long-term value: 238 mg/m³, 50 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | 127 (00/1) | (EX) | | |
| *total dust **respirable fraction REL (USA) Long-term value: 10* 5** mg/m³ *total dust **respirable fraction TLV (USA) Long-term value: 5* mg/m³ *inhalable fraction; E 110-19-0 Isobutyl Acetate PEL (USA) Long-term value: 700 mg/m³, 150 ppm REL (USA) Long-term value: 700 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm 123-86-4 butyl acetate PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm TLV (USA) Long-term value: 710 mg/m³, 50 ppm Long-term value: 238 mg/m³, 50 ppm Long-term value: 700 mg/m³, 50 ppm | | 7727-43-7 barium sulfate | | |
| REL (USA) Long-term value: 10* 5** mg/m³ *total dust **respirable fraction TLV (USA) Long-term value: 5* mg/m³ *inhalable fraction; E 110-19-0 Isobutyl Acetate PEL (USA) Long-term value: 700 mg/m³, 150 ppm REL (USA) Long-term value: 700 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm 123-86-4 butyl acetate PEL (USA) Short-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 710 mg/m³, 150 ppm TLV (USA) Long-term value: 710 mg/m³, 50 ppm TLV (USA) Long-term value: 710 mg/m³, 50 ppm Long-term value: 238 mg/m³, 50 ppm Long-term value: 712 mg/m³, 50 ppm | PEL (USA) | Long-term value: 15* 5** mg/m³ | | |
| *total dust **respirable fraction Long-term value: 5* mg/m³ *inhalable fraction; E 110-19-0 Isobutyl Acetate PEL (USA) | DEL (1104) | ^total dust ^^respirable fraction | | |
| *inhålable fraction; E 110-19-0 Isobutyl Acetate PEL (USA) Long-term value: 700 mg/m³, 150 ppm REL (USA) Long-term value: 700 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm 123-86-4 butyl acetate PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 950 mg/m³, 200 ppm Long-term value: 712 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | REL (USA) | *total dust **respirable fraction | | |
| 110-19-0 Isobutyl Acetate | TLV (USA) | | | |
| PEL (USA) Long-term value: 700 mg/m³, 150 ppm REL (USA) Long-term value: 700 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm 123-86-4 butyl acetate PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 300 ppm Long-term value: 700 mg/m³, 200 ppm | | · | | |
| REL (USA) Long-term value: 700 mg/m³, 150 ppm Short-term value: 238 mg/m³, 50 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm 123-86-4 butyl acetate PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 710 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | | | | |
| TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm 123-86-4 butyl acetate PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | | | | |
| Long-term value: 238 mg/m³, 50 ppm 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm 123-86-4 butyl acetate PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 712 mg/m³, 50 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | | | | |
| 108-65-6 PM acetate WEEL (USA) Long-term value: 50 ppm 123-86-4 butyl acetate PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | TLV (USA) | Short-term value: /12 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm | | |
| 123-86-4 butyl acetate PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | 108-65-6 PM | The state of the s | | |
| PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | WEEL (USA) | Long-term value: 50 ppm | | |
| REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | 123-86-4 butyl acetate | | | |
| Long-term value: 710 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | PEL (USA) | | | |
| TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | REL (USA) | Short-term value: 950 mg/m³, 200 ppm | | |
| Long-term value: 238 mg/m³, 50 ppm 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm | | | | |
| PEL (USA) Long-term value: 700 mg/m³, 200 ppm | TLV (USA) | Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm | | |
| | | | | |
| | | | | |
| | REL (USA) | Long-term value: 530 mg/m³, 150 ppm | | |
| TLV (USA) Short-term value: 529 mg/m³, 150 ppm | TLV (USA) | | | |

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Printing date 01/10/2020 Revised On 01/02/2020

Trade name: SAFETY RED

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

Keep away from foodstuffs and animal feed. Wash hands after use. **Hygienic protection:**

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In **Breathing equipment:**

cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Appearance: Aerosol. Aromatic Odor: Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. -44 °C (-111.2 °F) Boiling point: -19 °C (-66.2 °F) Flash point: Extremely flammable.

Flammability (solid, gas): Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture. Lower Explosion Limit: 1.7 Vol %

10.9 Vol % **Upper Explosion Limit:** Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Viscosity: Not determined.

VOC content (less exempt solvents): 48.7 % 0.0 % Water:

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. No dangerous decomposition products known. Hazardous decomposition:

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

110-19-0 Isobutyl Acetate

LD50 Oral 4,763 mg/kg (rbt)

108-65-6 PM acetate

LD50 8,500 mg/kg (rat) Oral Inhalative LC50/4 h 35.7 mg/l (rat)

123-86-4 butyl acetate

LD50 14,000 mg/kg (rat) Inhalative LC50/4 h >21 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect.

(Contd. on page 4)

(Contd. of page 3)

Printing date 01/10/2020 Revised On 01/02/2020

Trade name: SAFETY RED

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity:

Hazardous for water, do not empty into drains.

Persistence and degradability: Other information:

The product is degradable after prolonged exposure to natural weathering processes

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential: Mobility in soil:

No further relevant information available. No further relevant information available. No further relevant information available.

13 Disposal considerations

Other adverse effects:

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Completely empty cans should be recycled. Recommendation:

14 Transport information

UN-Number UN1950 N/A

DOT Consumer Commodity ORM-D

Aerosols, flammable

ADR 1950 Aerosols

Transport hazard class(es):

Class 2.1 No

Marine pollutant: Special precautions for user:

Warning: Gases

EMS Number: F-D,S-Ŭ

Packaging Group: UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer: 108-10-1 methyl isobutyl ketone

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

67-64-1 Acetone 7727-43-7 barium sulfate D, CBD(inh), NL(oral)

110-19-0 Isobutyl Acetate **USDA (United States Department of**

Agriculture):

Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product

may be used where there is a possibility of incidental food contact.

16 Other information

Contact: Regulatory Affairs