

## History of Quality and Dependability

For over 100 years, IRWIN HANSON has been providing the highest quality threading tools in the industry. The IRWIN HANSON name signifies dependability with professionals who use our tools each and every day. By working with various tradesmen, we are able to create solutions for endless fastening challenges. Whether creating new threads or repairing damaged and worn threads, achieving a precise fit is essential. IRWIN HANSON sets the standard for delivering quality every step of the way for your threading applications.

## Tap & Die Overview

Although there are hundreds of different types of fasteners, most of them have the same basic design: a spiral groove inside a hole matches the threads on the outside diameter of a screw or bolt. IRWIN HANSON taps and dies are the tools used by professionals to create threads to solve the most challenging fastener applications.

### Material Types

- **High Carbon Steel (HCS)** for hand tapping applications
- **High Speed Steel (HSS)** for machine tapping where critical dimensions are required

### Point Styles

- Taper, plug, and bottoming styles are available



### Laser Etched

- Tap size and recommended drill bit size are laser etched on each tool for easy identification

### Precision Ground Flutes



## Tap Point Styles

### Taper Taps



8-10 threads

- Easiest to start
- 8 to 10 threads chamfered
- Ideal for tough starting applications
- Preferred use with deep or through hole applications

### Plug Taps



3-5 threads

- 3 to 5 threads chamfered
- Most common chamfer
- Ideal for for all general purpose threading

### Bottom Taps



1-2 threads

- 1 to 2 threads chamfered
- Shortest and least efficient standard chamfer
- Ideal for threading close to the bottom of blind holes

**Die Styles**

**Hexagon Dies**



**5/8", 1", 1-7/16" & 1-13/16" Across Hex Flats**

- Best suited to maintenance and repair work
- Recommended for use with hexagonal die stock handles
- In area with limited space, die can be used with a wrench or socket

**Adjustable Round Dies**



**1", 1-1/2", 2" & 3" Overall Diameter**

- Adjustable dies allow the user to under or over cut their threads
- Ideal for a precision threading with the adjustment of die made by set screw
- Fits into adjustable guide or plain die stock handles
- Meets Federal Specifications GGG-D-296

**Solid Round Dies**



**1" & 1-1/2" Overall Diameter**

- Ideal for general purpose threading
- Fits into adjustable guide or plain die stock handles

**Tap & Die Description Guide**

**10-24 NC**

**Fastener Diameter**

10 - Machine screw size  
5/8" - Fractional  
8 mm - Metric

**Thread Pitch**

Threads per inch (machine & fractional)  
Distance between threads (metric)

**Thread Type**

NC = National Coarse (USS)  
  
NF = National Fine (SAE)  
  
NS = National Special  
  
NEF = National Extra Fine  
NPT = National Pipe Taper  
BSP = British Standard Pipe

**Applications**

General purpose machines and appliances  
  
Automotive parts requiring extreme pressures  
  
Special threads – either diameter or threads per inch  
  
For optical or thin wall parts  
  
For all pipe threads  
  
For all pipe threads

(no thread symbol required for metric fasteners)

**Machine Screw Reference Guide**

Before cutting a thread you must know the rod diameter.

Use the chart to determine the appropriate machine screw size:

Machine Screw	Rod Diameter
#0	.060"
#1	.073"
#2	.086"
#3	.099"
#4	.112"
#5	.125"
#6	.138"

Machine Screw	Rod Diameter
#7	.151"
#8	.164"
#9	.179"
#10	.190"
#12	.216"
#14	.242"

# TAPS & DIES

## TAP & DRILL SELECTION CHART

TAPS & DIES

Diam/Type	Decimal Equiv.	Fractional Tap	Machine Screw Tap	Metric Tap	Screw Ext.
1/64"	.0516				
1/32"	.0312				
1.0 mm	.0394				
60	.0400				
59	.0410				
58	.0420				
57	.0430				
56	.0465				
3/64"	.0469		0 - 80 NF		
55	.0520				
54	.0550				
1.5 mm	.0591				
53	.0595		1 - 64 NC 1 - 72NF		
1/16"	.0625				
52	.0635				
51	.0670				
50	.0700		2 - 56 NC 2 - 64 NF		
49	.0730				
48	.0760				
5/64"	.0781		3 - 48 NC		EX-1
47	.0785				
2.0 mm	.0787				
46	.0810				
45	.0820		3 - 56 NF		
44	.0860		4 - 36 NS		
43	.0890		4 - 40 NC		
42	.0935				
3/32"	.0938		4 - 48 NF		
41	.0960			3 mm - 0.60	
40	.0980				
2.5 mm	.0984			3 mm - 0.50	
39	.0995			3 mm - 0.50	
38	.1015	1/8" - 40 NS	5 - 40 NC		
37	.1040		5 - 44 NF		
36	.1065		6 - 32 NC		
7/64"	.1094				EX-2
35	.1100				
34	.1110		6 - 36 NS		
33	.1130		6 - 40 NF		
32	.1160		6 - 48 NS		
3.0 mm	.1181				
31	.1200				
1/8"	.1250				
30	.1285			4 mm - 0.70 4 mm - 0.75	
29	.1360		8 - 32 NC 8 - 36 NF		
3.5 mm	.1378				
28	.1405				

Diam/Type	Decimal Equiv.	Fractional Tap	Machine Screw Tap	Metric Tap	Screw Ext.
9/64"	.1406	8 - 40 NS			ST-1
27	.1440				
26	.1470	3/16"-24 NS			
25	.1495		10 - 24 NC		
24	.1520				
23	.1540				
5/32"	.1562	3/16"-32 NS			EX-3
22	.1570				
4.0 mm	.1575				
21	.1590		10 - 32 NF		
20	.1600			5 mm - 0.90	
19	.1660			5 mm - 0.80	
18	.1695				
11/64"	.1719				
17	.1730				
16	.1770		12 - 24 NC		
4.5 mm	.1772				
15	.1800				
14	.1820		12 - 28 NEF		
13	.1850				
3/16"	.1875				ST-2
12	.1890				
11	.1910				
10	.1935		14 - 20 NS		
9	.1960				
5.0 mm	.1969			6 mm - 1.00	
8	.1990			6 mm - 1.00	
7	.2010	1/4" - 20 NC			
13/64"	.2031		14 - 24 NS		
6	.2040				
5	.2055				
4	.2090	1/4" - 24 NS			
3	.2130	1/4" - 28 NF			
5.5 mm	.2165				
7/32"	.2188	1/4" - 32 NEF			
2	.2210				
1	.2280	1/4" - 40 NS			
A	.2340				
15/64"	.2344			7 mm - 1.00	ST-3
6.0 mm	.2362			7 mm - 1.00	
B	.2380				
C	.2420				
D	.2460				
E	.2500				
1/4"	.2500				EX-4
6.5 mm	.2559				
F	.2570	5/16" - 18 NC			

Diam/Type	Decimal Equiv.	Fractional Tap	Pipe Tap	Metric Tap	Screw Ext.
G	.2610				
17/64"	.2656			8 mm - 1.25	
H	.2660				
I	.2720	5/16"-24 NF			
7.0 mm	.2756			8 mm - 1.00	
J	.2770			8 mm - 1.00	
K	.2810				
9/32"	.2812	5/16"-32 NEF			
L	.2900				
M	.2950				
7.5 mm	.2953				
19/64"	.2969				EX-5
N	.3020			9 mm - 1.25	
5/16"	.3125	3/8"- 16 NC			ST-4
8.0 mm	.3150			9 mm - 1.00	
O	.3160			9 mm - 1.00	
P	.3230			9 mm - 0.75	
21/64"	.3281		1/8" - 28 BSP		
Q	.3320	3/8"- 24 NF	1/8" - 27 NPT		
8.5 mm	.3346			10 mm - 1.50	
R	.3390			10 mm - 1.50	
11/32"	.3438			10 mm - 1.25	
S	.3480				
9.0 mm	.3543			10 mm - 1.00	
T	.3580			10 mm - 1.00	
23/64"	.3594				
U	.3680	7/16"- 14 NC			
9.5 mm	.3740			11 mm - 1.50	
3/8"	.3750			11 mm - 1.50	ST-5
V	.3770				
W	.3806				
25/64"	.3906	7/16"- 20 NF			
10.0 mm	.3937				
X	.3970				
Y	.4040				
13/32"	.4062			12 mm - 1.75	EX-6
Z	.4130			12 mm - 1.50	
10.5 mm	.4134			12 mm - 1.50	
27/64"	.4219	1/2"- 13 NC		12 mm - 1.25	
11.0 mm	.4331				
7/16"	.4375		1/4" - 18 NPT		
11.5 mm	.4528				
29/64"	.4531	1/2"-20 NF 1/2"-24 NS	1/4" - 19 BSP		
15/32"	.4688			14 mm - 2.00	ST-6
12.0 mm	.4724			14 mm - 2.00	
31/64"	.4844	9/16" - 12 NC			
12.5 mm	.4921			14 mm - 1.50	

Diam/Type	Decimal Equiv.	Fractional Tap	Pipe Tap	Metric Tap	Screw Ext.
1/2"	.5000			14 mm - 1.25 14 mm - 1.50	
13.0 mm	.5118			14 mm - 1.25	
33/64"	.5156	9/16"- 18 NF			
17/32"	.5313	5/8" - 11 NC			EX-7
35/64"	.5469			16 mm - 2.00	
9/16"	.5625		3/8" - 18 NPT		ST-7
37/64"	.5781	5/8" - 18 NF		16 mm - 1.50	
19/32"	.5938	11/16"-11 NS			
39/64"	.6094			18 mm - 2.50	
5/8"	.6250	11/16"-16 NS			
41/64"	.6406				
21/32"	.6562	3/4" - 10 NC		18 mm - 1.50	
43/64"	.6719				
11/16"	.6875	3/4" - 16 NF		20 mm - 2.50	
45/64"	.7031		1/2" - 14 NPT		
23/32"	.7188				
47/64"	.7344				
3/4"	.7500				
49/64"	.7656				
25/32"	.7812	7/8" - 9 NC			
51/64"	.7969				
13/16"	.8125	7/8" - 14 NF		22 mm - 1.50	EX-8
53/64"	.8281			24 mm - 3.00	
27/32"	.8438				
55/64"	.8594				
7/8"	.8750	1" - 8 NC		24 mm - 2.00	
57/64"	.8906				
29/32"	.9062				
59/64"	.9219	1" - 12 NF	3/4" - 14 NPT		
15/16"	.9375	1" - 14 NS			
61/64"	.9531				
31/32"	.9688				
63/64"	.9844	1-1/8" - 7 NC			
1"	1.0000				
1-1/64"	1.0156				
1-1/32"	1.0312				
1-1/16"	1.0625				EX-9
1-3/32"	1.0938				
1-1/8"	1.1250				
1-5/32"	1.1562		1" - 11-1/2" NPT		
1-3/16"	1.1875				
1-1/4"	1.2500				
1-5/16"	1.3125				
1-3/8"	1.3750				
1-7/16"	1.4375				
1-1/2"	1.5000		1-1/4" - 11-1/2" NPT		

NC = National Coarse (USS)  
NS = National Special  
NF = National Fine (SAE)

NEF = National Extra Fine  
NPT = National Pipe Taper  
BSP = British Standard Pipe

**HANSON® Metric Taps (HCS)**



1859

- Ideal for auto repair and machinery where metric threads are specified

**HANSON Tap Sets with Taper, Bottoming & Plug Point Styles**



2652

- Set contains all three chamfer styles for various uses

Description	No. of Flutes	Plug Carded Stock #	Plug Bulk Stock #	Bottom Bulk Stock #
3 mm - 0.50	3	8312	1712	1812
3 mm - 0.60	3	—	1713	—
4 mm - 0.70	4	8317	1717	1817
4 mm - 0.75	4	8318	1718	1818
5 mm - 0.80	4	8322	1722	1822
5 mm - 0.90	4	8323	1723	1823
6 mm - 1.00	4	8327	1727	1827
6.3 mm - 1.00	4	—	1729	1829
7 mm - 1.00	4	8331	1731	1831
8 mm - 1.00	4	8333	1733	1833
8 mm - 1.25	4	8334	1734	1834
9 mm - 0.75	4	8335	—	—
9 mm - 1.00	4	8336	—	—
9 mm - 1.25	4	8337	1737	1837
10 mm - 1.00	4	8338	1738	1838
10 mm - 1.25	4	8339	1739	1839
10 mm - 1.50	4	8340	1740	1840
11 mm - 1.50	4	8341	1741	—
12 mm - 1.25	4	8342	1742	1842
12 mm - 1.50	4	8343	1743	—
12 mm - 1.75	4	8344	1744	1844
14 mm - 1.25	4	—	1749	1849
14 mm - 1.50	4	—	1750	—
14 mm - 2.00	4	—	1752	1852
16 mm - 1.00	4	—	1754	—
16 mm - 1.50	4	—	1755	1855
16 mm - 2.00	4	—	1756	1856
18 mm - 1.50	4	—	1759	1859
18 mm - 2.50	4	—	1761	1861
20 mm - 2.50	4	—	1764	1864
22 mm - 1.50	4	—	1765	1865
24 mm - 2.00	4	—	1768	1868
24 mm - 3.00	4	—	1769	1869

Description	No. of Flutes	Stock #
6 - 32 NC	3	2518
8 - 32 NC	4	2524
10 - 24 NC	4	2528
10 - 32 NF	4	2531
1/8" - 40 NS	3	2606
5/32" - 32 NS	4	2610
5/32" - 36 NS	4	2611
1/4" - 20 NC	4	2620
1/4" - 28 NF	4	2623
5/16" - 18 NC	4	2627
5/16" - 24 NF	4	2629
3/8" - 16 NC	4	2634
3/8" - 24 NF	4	2636
7/16" - 14 NC	4	2639
7/16" - 20 NF	4	2640
1/2" - 13 NC	4	2644
9/16" - 12 NC	4	2648
5/8" - 11 NC	4	2652
5/8" - 18 NF	4	2654
3/4" - 10 NC	4	2658
7/8" - 9 NC	4	2661
1" - 8 NC	4	2665
3 mm - 0.50	3	2712
5 mm - 0.80	4	2722
6 mm - 1.00	4	2727
7 mm - 1.00	4	2731
8 mm - 1.00	4	2733
8 mm - 1.25	4	2734
10 mm - 1.00	4	2738
10 mm - 1.25	4	2739
10 mm - 1.50	4	2740
12 mm - 1.25	4	2742
12 mm - 1.75	4	2744
14 mm - 2.00	4	2752
16 mm - 2.00	4	2756