FACOM® INSULATED RATCHETS

- > Sockets and accessories secured by spring -ball.
- 2 Color warning handle insulation color changes from orange to yellow if Insulation integrity compromised.
- For manual use.
- Insulated to 1000V AC or 1500 DC.

| | | Overall | | |
|-----------|-----------------|-------------|--------------|--|
| Product # | Drive Size (in) | Length (in) | Weight (lbs) | |
| R.151AVSE | 1/4 | 4-7/8 | 0.28 | |
| J.151AVSE | 3/8 | 7 | 0.53 | |
| S.151AVSE | 1/2 | 10-3/8 | 1.24 | |
| | | | | |





SPUD HANDLE RATCHET

- > Tapered handle for aligning bolt holes.
- Spring loaded pellet in male drive plug.
- Black oxide finish.



| Produc | t # | Drive Size (in) | Finish | Style | Uverali Length (in) | Weight (lbs) |
|---------|-----|-----------------|-------------|-----------|------------------------|---------------|
| J5449-1 | 4BL | 1/2 | Black Oxide | Pear Head | 14 | 2.03 |
| | | | | | | 40ME D407 F00 |

ASME B107.500



SCAFFOLDING RATCHET

- > The scaffold ratchet is designed for working with scaffolding and other construction applications.
- Socket retained with through hole and pin for safety.
- ▶ Hammer tip reduces vibration and protects fasteners against distortion.
- > Hole in ratchet handle to be used with tether strap.



| | | | Uverali | | |
|-----------|-----------------|-------------|-------------|-------------|--------------|
| Product # | Drive Size (in) | Finish | Style | Length (in) | Weight (lbs) |
| J5449SC | 1/2 | Full Polish | Scaffolding | 10 | 2.01 |
| · | | | | | |



SPINNER RATCHET

- Made from alloy steel.
- Heat-treated for strength and durability.
- ▶ Fits on the drive end of the ratchet for quickly running down the fastener before final tightening with the ratchet.

| Product # | Drive Size (in) | Finish | Overall Length (in) | Weight (lbs) |
|-----------|-----------------|-------------|------------------------|--------------|
| J5251 | 3/8 | Full Polish | 1-1/2 | 0.56 |
| | | | | |



