



## 3/8" DRIVE DRAG LINK SOCKET

- › Made of heat-treated alloy steel.
- › Ball detent.

INCH	Product #	Tip Width (in)	Overall Length (in)	Weight (lbs)
11/16	<b>J5244</b>	1/8	1-1/8	0.06



## 3/8" DRIVE BIT SOCKETS

	Size	Product #	Tip Width (in)	Bit Length (in)	Overall Length (in)	Weight (lbs)
Slotted	1/4"	➤ <b>J5246</b>	1/32	-	1-13/16	0.01
	5/16"	➤ <b>J5240A*</b>	3/64	-	3	0.13
Phillips	#2	➤ <b>J5241</b>	-	-	1-31/32	0.11
	#3	➤ <b>J5242</b>	-	-	1-31/32	0.12
	#4	➤ <b>J5243</b>	-	-	1-31/32	0.12
Torx®	T10	➤ <b>J5239-10W</b>	-	5/8	1-23/32	0.10
	T15	➤ <b>J5239-15W</b>	-	5/8	1-23/32	0.10
	T20	➤ <b>J5239-20W</b>	-	5/8	1-23/32	0.10
	T25	➤ <b>J5239-25W</b>	-	5/8	1-23/32	0.10
	T27	➤ <b>J5239-27W</b>	-	5/8	1-23/32	0.10
	T30	➤ <b>J5239-30W</b>	-	7/8	1-23/32	0.12
	T40	➤ <b>J5239-40W</b>	-	7/8	1-23/32	0.11
	T45	➤ <b>J5239-45W</b>	-	7/8	1-23/32	0.12
	T50	➤ <b>J5239-50W</b>	-	7/8	1-23/32	0.12
T55	➤ <b>J5239-55W</b>	-	7/8	1-23/32	0.13	

\*One-piece design

