




## SATIN SERVICE WRENCHES


- › Satin finish provides corrosion resistance and a slip resistant grip.
- › 30° angle head allows access to difficult to reach fasteners.
- › Thin pattern for use on jam nuts, check nuts or lock nuts.
- › Short shank allows for use in confined spaces.



SERVICE WRENCHES

INCH		Throat Depth 1 (in)	Outside Head Width 1 (in)	Head Thickness 1 (in)	Overall Length (in)	Weight (lbs)
3/4	<b>J3524</b>	7/32	1-11/16	1/4	6-1/4	0.22
13/16	<b>J3526</b>	7/32	1-11/16	1/4	6-1/4	0.22
7/8	<b>J3528</b>	7/32	1-11/16	1/4	6-1/4	0.22
15/16	<b>J3530</b>	1/4	1-7/8	1/4	6-7/8	0.25
1	<b>J3532</b>	1/4	1-7/8	1/4	6-7/8	0.25
1-1/16	<b>J3534</b>	1/4	1-7/8	1/4	6-7/8	0.25
1-1/8	<b>J3536</b>	5/16	2-1/16	1/4	7	0.31
1-3/16	<b>J3538</b>	5/16	2-1/16	1/4	7	0.31
1-1/4	<b>J3540</b>	19/64	2-1/16	1/4	7	0.45
1-5/16	<b>J3542</b>	29/64	2-1/2	9/32	7-5/8	0.44
1-3/8	<b>J3544</b>	7/16	2-1/2	9/32	7-5/8	0.43
1-7/16	<b>J3546</b>	7/16	2-1/2	9/32	7-5/8	0.42
1-1/2	<b>J3548</b>	27/64	2-1/2	9/32	7-5/8	0.43
1-9/16	<b>J3550</b>	7/16	2-5/8	9/32	7-5/8	0.43
1-5/8	<b>J3552</b>	7/16	2-5/8	9/32	7-5/8	0.42
1-11/16	<b>J3554</b>	27/64	2-5/8	9/32	7-5/8	0.7
1-3/4	<b>J3556</b>	45/64	3-1/8	5/16	8-1/2	0.69
1-13/16	<b>J3558</b>	11/16	3-1/8	5/16	8-1/2	0.69
1-7/8	<b>J3560</b>	11/16	3-1/8	5/16	8-1/2	0.68
1-15/16	<b>J3562</b>	11/16	3-1/8	5/16	8-1/2	0.68
2	<b>J3564</b>	21/32	3-1/2	5/16	8-1/2	0.66
2-1/8	<b>J3568</b>	21/32	3-1/2	5/16	8-1/2	0.65
2-1/4	<b>J3572</b>	39/64	3-1/2	5/16	8-1/2	0.61
2-3/8	<b>J3576</b>	39/64	3-1/2	5/16	8-1/2	0.61
2-1/2	<b>J3580</b>	19/32	3-1/2	5/16	8-1/2	0.59
2-9/16	<b>J3582</b>	9/16	3-1/2	5/16	8-1/2	0.57



MM		Outside Head Width 1 (in)	Head Thickness 1 (in)	Overall Length (in)	Weight (lbs)
19	<b>J3519M</b>	1-11/16	1/4	6-1/4	0.22
21	<b>J3521M</b>	1-11/16	1/4	6-1/4	0.22
22	<b>J3522M</b>	1-11/16	1/4	6-1/4	0.22
24	<b>J3524M</b>	1-7/8	1/4	6-7/8	0.25
27	<b>J3527M</b>	1-7/8	1/4	6-7/8	0.25
30	<b>J3530M</b>	2-1/16	1/4	7	0.31
32	<b>J3532M</b>	2-1/16	1/4	7	0.30
36	<b>J3536M</b>	2-1/2	1/4	7-5/8	0.45
37	<b>J3537M</b>	2-1/2	9/32	7-5/8	0.43
38	<b>J3538M</b>	2-1/2	9/32	7-5/8	0.42
40	<b>J3540M</b>	2-5/8	9/32	7-5/8	0.43
41	<b>J3541M</b>	2-5/8	9/32	7-5/8	0.43
42	<b>J3542M</b>	2-5/8	9/32	7-5/8	0.43
44	<b>J3544M</b>	2-5/8	9/32	7-5/8	0.43
46	<b>J3546M</b>	3-1/8	9/32	7-5/8	0.70
48	<b>J3548M</b>	3-1/8	5/16	8-1/2	0.70
50	<b>J3550M</b>	3-1/8	5/16	8-1/2	0.68
52	<b>J3552M</b>	3-1/2	5/16	8-1/2	0.66
55	<b>J3555M</b>	3-1/2	5/16	8-1/2	0.66
60	<b>J3560M</b>	3-1/2	5/16	8-1/2	0.61
65	<b>J3565M</b>	3-1/2	5/16	8-1/2	0.57



-  FULL POLISH
  SATIN
  BLACK OXIDE
  BLACK CHROME
  INSULATED